

Issuing date 15-Jan-2015

Revision Date 15-Jan-2015

Version 1.03

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING****Product identifier****Product name** 80-921 TORQ 2 PENETRATING OIL WITH GRAPHITE**Recommended use of the chemical  
and restrictions on use****Product code** F00532**Product Type** Extremely flammable aerosol  
**Synonyms** None**Supplier's details****Recommended Use** Penetrating lubricant.  
**Uses advised against** No information available**Manufactured For:**  
Kimball Midwest  
4800 Roberts Rd.  
Columbus, OH 43228**Emergency telephone number**  
**Chemical Emergency Phone** 1-800-424-9300  
**Number**  
**Company Emergency Phone** 1-800-233-1294  
**Number**

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### DANGER

#### Hazard Statements

Causes skin irritation  
 Causes serious eye irritation  
 May cause drowsiness or dizziness  
 May be fatal if swallowed and enters airways  
 Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated



**Appearance** Clear

**Physical state** Aerosol

**Odor** Solvent

#### Precautionary Statements - Prevention

Wash hands and face thoroughly after handling  
 Wear eye/face protection  
 Wear protective gloves  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Do not spray on an open flame or other ignition source  
 Pressurized container: Do not pierce or burn, even after use

#### Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation occurs: Get medical advice/attention  
 Remove/Take off immediately all contaminated clothing  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
Protect from sunlight. Store in a well-ventilated place  
Do not expose to temperatures exceeding 122°F (50°C)  
Keep container tightly closed.

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

None

**Other information**

- Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %*
HYDROTREATED LIGHT DISTILLATES	64742-47-8	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	15-25
NAPHTHENIC OIL, SEVERELY HYDROT	64742-52-5	10-20
ACETONE	67-64-1	10-20
HYDROCARBON SOLVENT	64742-96-7	10-20
MINERAL OIL, DEWAXED	64742-65-0	1-10

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****First aid measures for different exposure routes**

<b>General advice</b>	Avoid contact with eyes, and clothing. Avoid breathing, vapors, mist, or gas.
<b>Eye contact</b>	In the case of contact with eyes, rinse immediately with plenty of water for 15 minutes and seek medical advice.
<b>Skin contact</b>	Rinse with plenty of water. Consult a physician if irritation persists. Wash off immediately with plenty of water. Remove and wash contaminated clothing before re-use. Get medical attention immediately if symptoms occur.
<b>Inhalation</b>	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

**Most important symptoms/effects, acute and delayed**

<b>Main Symptoms</b>	May cause skin irritation. Inhalation causing Central Nervous System effects. Ingestion causing lung damage.
----------------------	--

---

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media**

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Flammable or extremely flammable aerosol. Container may burst in fire.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use with adequate ventilation to keep the exposure levels below the OELS.

**Environmental precautions**

**Environmental precautions** Report spills as required by local and federal regulations.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Contain liquid and collect with an inert, non-combustible material.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

**Conditions for safe storage, including any incompatibilities**

**Technical measures/Storage conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible products** Store away from strong oxidizers and acids.

**Aerosol Level** 3

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> 106-97-8: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup> 75-28-5: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
MINERAL OIL, DEWAXED 64742-65-0	ACGIH TLV: 5 mg/m <sup>3</sup> (oil mist)	OSHA PEL: 5 mg/m <sup>3</sup> (oil mist)	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety &amp; Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls****Engineering Measures**

Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

**Individual protection measures, such as personal protective equipment****Eye/Face Protection**

Safety glasses with side-shields.

**Skin and body protection**

Chemical resistant apron. Protective gloves.

**Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Physical and chemical properties****Physical state**

Aerosol

**Appearance**

Clear

**Color**

amber

**Odor**

Solvent

**Odor Threshold**

No information available

**Property****Values****Remarks • Methods****pH**

No information available

**Melting/freezing point**

No information available

**Boiling point/boiling range**

No information available

**Flash Point**

-96.4 °C / -141 °F

Based on propellant

Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit	No information available	
lower flammability limit	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	0.772	
Water solubility	Practically insoluble	
Partition coefficient: n-octanol/water	No information available	
Autoignition temperature	No information available	Not applicable
Decomposition temperature	No information available	
Viscosity	No information available	
Explosive properties	No information available	

**Other information**

VOC Content(%) 21.99

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Incompatible Materials**

Store away from strong oxidizers and acids.

**Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known information		
<b>Inhalation</b>	Exposure to high vapour concentrations may cause nervous systems effects such as headache, nausea, and dizziness.		
<b>Eye contact</b>	May cause slight irritation.		
<b>Skin contact</b>	Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.		
<b>Ingestion</b>	Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.		

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h

ACETONE 67-64-1	-	20,000 mg/kg (Rabbit)	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
HYDROCARBON SOLVENT 64742-96-7	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
MINERAL OIL, DEWAXED 64742-65-0	-	-	= 2.18 mg/L (Rat) 4 hr

**Information on toxicological effects**

**Symptoms**

Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. May cause mild irritation. Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation**

Irritating to skin.

**Eye damage/irritation**

Irritating to eyes.

**Sensitization**

No information available.

**Germ Cell Mutagenicity**

No information available.

**Carcinogenicity**

There are no known carcinogenic chemicals in this product.

**Reproductive toxicity**

The ingredients are not reproductive hazards.

**Specific target organ systemic toxicity (single exposure)**

May cause drowsiness and dizziness.

**Specific target organ systemic toxicity (repeated exposure)**

No information available.

**Chronic toxicity**

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis.

**Target Organ Effects**

Central nervous system, Eyes, Respiratory system, Skin.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity**

0% of the mixture consists of ingredient(s) of unknown toxicity

**The following values are calculated based on chapter 3.1 of the GHS document .**

**ATEmix (oral)**

12652 mg/kg

**ATEmix (dermal)**

5061 mg/kg

**ATEmix (inhalation-dust/mist)**

665.2 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
NAPHTHENIC OIL, SEVERELY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h

ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
MINERAL OIL, DEWAXED 64742-65-0	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
ACETONE 67-64-1	-0.24

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods**

Dispose of in accordance with federal, state, and local regulations.

**Contaminated packaging**

Do not re-use empty containers.

**14. TRANSPORT INFORMATION****DOT Ground**CONSUMER COMMODITY ORM-D  
or  
LIMITED QUANTITY**IATA**

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

**IMDG**

UN1950, AEROSOLS, 2.1, LTD. QTY.

**15. REGULATORY INFORMATION****International Inventories**

Chemical Name	TSCA	DSL/NDL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
HYDROTREATED LIGHT DISTILLATES	X	X	X	X	X	X	X	X
PROPANE/ISOBUTANE/N-BUTANE	X	X	X	Not listed	X	X	X	X
NAPHTHENIC OIL, SEVERELY HYDROT	X	X	X	X	X	X	X	X



ACETONE	X	X	X	X	X	X	X	X
HYDROCARBON SOLVENT	X	X	X	Not listed	X	X	X	X
MINERAL OIL, DEWAXED	X	X	X	X	X	X	X	X

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**U.S. Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	Yes
<b>Reactive Hazard</b>	no

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**U.S. State Regulations**

**California Proposition 65**

This product does not contain any known Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

This product does not contain any substances regulated by state right-to-know regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X

**EPA Pesticide Registration Number** Not applicable

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

## 16. OTHER INFORMATION

<b>NFPA</b>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<b>HMIS</b>	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B

<b>Prepared By</b>	Regulatory Affairs
<b>Issuing date</b>	15-Jan-2015
<b>Revision Date</b>	15-Jan-2015

**Revision Note**

No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**