

Reviewed on 11/21/2014

1 Identification

- · Product identifier
- Trade name: 80-135 / Torque-Lok Extreme Maintenance Grade Threadlocker
- · Application of the substance / the mixture Adhesive
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kimball Midwest 4800 Roberts Road Columbus, OH 43228

Corporate Telephone: 800.233.1294

Emergency Telephone: Chemtrec 1.800.424.9300

- · Information department: Product safety department
- · Emergency telephone number: Emergency Telephone: Chemtrec 1.800.424.9300

2 Hazard(s) identification

· Classification of the substance or mixture



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



X Harmful

Harmful by inhalation, in contact with skin and if swallowed.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Information concerning particular hazards for human and environment:
- The product has to be labeled due to the calculation procedure of international guidelines.
- Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

1,4-bis(vinyloxy)butane Polyethylene Glycol 200 Dimethacrylate Di-Trimethylolpropane Tetraacrylate 2,4,6-triallyloxy-1,3,5-triazine

Hazard statements

Harmful if swallowed or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.

Printing date 05/14/2015 Reviewed on 11/21/2014

Trade name: 80-135 / Torque-Lok Extreme Maintenance Grade Threadlocker

(Contd. of page 1)

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

If swallowed: Call a poison center/doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Rinse mouth.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:			
	Polyethylene Glycol 200 Dimethacrylate	25-50%	
	1,4-bis(vinyloxy)butane	25-50%	
101-37-1	2,4,6-triallyloxy-1,3,5-triazine	2.5-<10%	
	Di-Trimethylolpropane Tetraacrylate	2.5-<10%	
57-55-6	propane-1,2-diol	2.5-<10%	
80-15-9	lpha, lpha -dimethylbenzyl hydroperoxide	0.1-<1%	

4 First-aid measures

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Seek medical treatment.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Call a doctor immediately.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed Breathing difficulty
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing date 05/14/2015 Reviewed on 11/21/2014

Trade name: 80-135 / Torque-Lok Extreme Maintenance Grade Threadlocker

(Contd. of page 2)

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Pick up mechanically.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

- Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters

Components with limit values that require monitoring at the workplace:

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m³

80-15-9 α,α -dimethylbenzyl hydroperoxide

WEEL Long-term value: 6 mg/m³, 1 ppm

Skin

Additional information: The lists that were valid during the creation were used as basis.

Printing date 05/14/2015 Reviewed on 11/21/2014

Trade name: 80-135 / Torque-Lok Extreme Maintenance Grade Threadlocker

(Contd. of page 3)

- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not necessary if room is well-ventilated.
- Protection of hands:



Impervious gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR Nitrile rubber, NBR Neoprene gloves

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not suitable are gloves made of the following materials:

Cotton or natural fibers

PVC gloves

· Eye protection: Safety glasses

Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Liquid

Color: According to product specification

Odor: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

'Flash point:

'Flammability (solid, gaseous):

Undetermined.

> 148 °C (> 298 °F)

> 93 °C (> 199 °F)

Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower:
Upper:
Not determined.
Not determined.

Vapor pressure:
Not determined.

Not determined.

Not determined.

Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2015 Reviewed on 11/21/2014

Trade name: 80-135 / Torque-Lok Extreme Maintenance Grade Threadlocker

(Contd. of page 4)

Vapour density Not determined.Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Solvent content:

 Organic solvents:
 0.0 %

 Water:
 0.2 %

 Solids content:
 99.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Danger of polymerization.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Nitrogen oxides Sulfur oxides (SOx)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Carcinogenic categories

· IARC (International Agency for Research on Cancer)				
	Polyethylene	3		
81-07-2	1,2-benzisothiazol-3(2H)-one 1,1-dioxide	3		
13463-67-7	titanium dioxide	2B		
7631-86-9	silicon dioxide, chemically prepared	3		
	nal Toxicology Program)			
None of the	ingredients is listed.			
	Occupational Safety & Health Administration)			
None of the	ingredients is listed.			

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.

Printing date 05/14/2015 Reviewed on 11/21/2014

Trade name: 80-135 / Torque-Lok Extreme Maintenance Grade Threadlocker

(Contd. of page 5)

- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADN, IMDG, IATA Void

UN proper shipping name

· DOT, ADN, IMDG, IATA Void

· Transport hazard class(es)

DOT, ADN, IMDG, IATA

· Class Void

Packing group

· DOT, IMDG, IATA Void

· Environmental hazards:

· Marine pollutant: No

Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara

Sara					
· Section 35	5 (extremely hazardous substances):				
None of the	ingredients is listed.				
Section 31	3 (Specific toxic chemical listings):				
81-07-2 1,2	81-07-2 1,2-benzisothiazol-3(2H)-one 1,1-dioxide				
80-15-9 α,α	80-15-9 α,α -dimethylbenzyl hydroperoxide				
· TSCA (Tox	ric Substances Control Act):				
	Polyethylene Glycol 200 Dimethacrylate				
	1,4-bis(vinyloxy)butane				
101-37-1	2,4,6-triallyloxy-1,3,5-triazine				
	Silica				
	Di-Trimethylolpropane Tetraacrylate				
9002-88-4	Polyethylene				
57-55-6	propane-1,2-diol				

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2015 Reviewed on 11/21/2014

Trade name: 80-135 / Torque-Lok Extreme Maintenance Grade Threadlocker

(Contd. of page 6)

	(conta. or page o)
81-07-2	1,2-benzisothiazol-3(2H)-one 1,1-dioxide
80-15-9	α,α -dimethylbenzyl hydroperoxide
	2'-phenylacetohydrazide
13463-67-7	titanium dioxide
64-02-8	tetrasodium ethylenediaminetetraacetate
7631-86-9	silicon dioxide, chemically prepared
	aluminium hydroxide
14233-37-5	Solvent Blue 36

Proposition 65

· Chemicals	known	to cause	cancer:
-------------	-------	----------	---------

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

13463-67-7 titanium dioxide

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning

Hazard-determining components of labeling:

1,4-bis(vinyloxy)butane

Polyethylene Glycol 200 Dimethacrylate

Di-Trimethylolpropane Tetraacrylate

2,4,6-triallyloxy-1,3,5-triazine

Hazard statements

Harmful if swallowed or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Printing date 05/14/2015 Reviewed on 11/21/2014

Trade name: 80-135 / Torque-Lok Extreme Maintenance Grade Threadlocker

(Contd. of page 7)

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

If swallowed: Call a poison center/doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Rinse mouth.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Kimball Midwest Regulatory
- · Date of preparation / last revision 05/14/2015 / -
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3