

The following SDS references the product below:

DYNATEX® 49643 HEAT TRANSFER COMPOUND

Vendor Item Number: 49643

Manufactured By:

Soudal Accumetric

Distributed by Kimball Midwest with the KM product-  
identification number:

80-601



# Safety Data Sheet

## Dynatex® 49643 Heat Transfer Compound

### Section 1. Identification

Product Identifier	Dynatex® 49643 Heat Transfer Compound
Synonyms	N/A
Manufacturer Stock Numbers	N/A

Recommended use	Refer to Technical Data
Uses advised against	Refer to Technical Data

#### Manufacturer Contact

Address	SODAL Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA
---------	--

Phone
(270) 769-3385

Emergency Phone
(800) 424-9300 CHEMTREC

Fax
N/A

### Section 2. Hazards Identification

Classification	N/A
Signal Word	
Pictogram	
Hazard Statements	Not classified as hazardous under 29CFR 1910.1200 (HazCom 2012)
Precautionary Statements	
Response	N/A
Prevention	N/A
Storage	N/A
Disposal	N/A

Ingredients of unknown toxicity	0%
---------------------------------	----

Hazards not Otherwise  
Classified

### Section 3. Ingredients

CAS	Ingredient Name	Weight %
1314-13-2	Zinc Oxide	< 75 %

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-Aid Measures

Ingestion	If ingested, dilute stomach contents with two glasses of milk or water. (NOTE: Do NOT give anything by mouth to an unconscious person.) Do not induce vomiting without medical supervision. If vomiting occurs spontaneously, keep airway clear. If symptoms of ingestion persist, seek medical attention.
Inhalation	If signs or symptoms of overexposure occur, remove the employee to fresh air. If symptoms persist, seek medical attention.
Skin Contact	Remove product from the skin by washing with a mild soap and water. Contaminated clothing should be removed to prevent prolonged exposure. If product is injected under the skin, seek treatment immediately. If symptoms of exposure persist, contact a physician.
Eye Contact	Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. If symptoms persist, contact a physician.
Note to Physician	No further data known.

### Section 5. Fire Fighting Measures

Suitable Extinguishing Media	No data available.
Unsuitable Extinguishing Media	Do not use water jet as an extinguisher, as this will spread the fire
Unusual Fire & Explosion Hazards	No further data known.
Firefighting Procedures and Equipment	Emergency responders in the danger area should wear bunker gear and self-contained breathing apparatus for fires beyond the incipient stage. See Section 8 of the MSDS for other PPE to be worn as conditions warrant.

### Section 6. Accidental Release Measures

Clean-up Measures	<p>Important: As with any spill or leak, before responding ensure that you are familiar with the potential hazards and recommendations of the MSDS. Appropriate personal protective equipment must be worn. See Section 8 of this MSDS for PPE recommendations.</p> <p>If possible, safely contain the spill with dikes or other spill response equipment appropriate for petroleum or organic material releases. Take measures to prevent spreading of product. Note that while product will ignite it</p>
-------------------	---

will not readily burn. However, as a precaution eliminate ignition sources. Prevent from entering sewers or waterways. Large volumes may be transferred to an appropriate container for proper disposal. Small volumes or residues may be soaked up with absorbents. Spill response materials should be collected for proper disposal.

## Section 7. Handling and Storage

### Handling

As with any industrial chemical, handle the product in a manner that minimizes exposure to practicable levels. Prior to handling, consult Section 8 of this MSDS to evaluate personal protective equipment needs. Open containers slowly to relieve any pressure. Follow all other standard industrial hygiene practices.

Empty containers may contain product residue. All safety precautions taken when handling this product should also be taken when handling empty drums and containers. Keep containers closed when not in use.

Product residue in empty containers is combustible but will not readily burn. NOTE however, that excessive heating or cutting of empty containers may create an ignition source sufficient to start a fire and in extreme cases, cause an explosion.

### Storage

Protect product quality by storing indoors and away from extreme temperatures. Close all containers when not in use.

## Section 8. Exposure Controls/Personal Protection

### Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Zinc Oxide	2 mg/m <sup>3</sup> dust	5 mg/m <sup>3</sup> dust	10 mg/m <sup>3</sup>

### Personal Protective Equipment

Goggles, Gloves

### Personal Protective Equipment

Selection of personal protective equipment should be based upon the anticipated exposure and made in accordance with OSHA's Personal Protective Equipment Standard found in 29 CFR 1910 Subpart I. The following information may be used to assist in PPE selection.

### Eye Protection

Wear eye protection appropriate to prevent eye exposure. Where splashing is not likely, chemical safety glasses with side shields are recommended. Where splashing may occur, chemical goggles or full face shield is recommended.

### Skin Protection

Gloves are not normally needed during normal conditions of use. If health effects are experienced, oil or chemical resistant gloves such as butyl or nitrile are recommended.

Where splashing or soaking is likely, wear oil or chemical resistant clothing to prevent exposure.

### Respiratory Protection

A respirator may be worn to reduce exposure to vapors, dust, or mist. Select a NIOSH/MSHA approved respirator appropriate for the type and physical character of the airborne material. A self-contained breathing apparatus is recommended in all situations where airborne contaminant concentration

has not been confirmed to be below safe levels. Respirator use should comply with the OSHA Respirator Protection Standard found in 29 CFR 1910.134.

#### Engineering Controls

Normal general ventilation is expected to be adequate. It is recommended that ventilation be designed in all instances to maintain airborne concentrations at lowest practicable levels. Ventilation should at a minimum, prevent airborne concentrations from exceeding any exposure limits listed in Section 2 of this MSDS.

The user may wish to refer to 29 CFR 1910.1000(d)(2) and the ACGIH "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices" (Appendix C) for the determination of exposure limits of mixtures. An industrial hygienist or similar professional may be consulted to confirm that the calculated exposure limits apply.

## Section 9. Physical and Chemical Properties

Physical State	Semi-solid
Color	White
Odor	Odorless
Odor Threshold	No data available
Solubility	Insoluble in water
Partition coefficient Water/n-octanol	No data available
VOC%	N/A
Viscosity	> 20.5 mm <sup>2</sup> /s (40C)
Specific Gravity	2.35
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	500F 260C
FP Method	COC
Ph	No data available
Melting Point	No data available
Boiling Point	No data available
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	No data available
Flammability	No data available
Decomposition Temperature	No data available

Auto-ignition Temperature	No data available
Vapor Pressure	No data available
Vapor Density	No data available

**Note**

The above information is not intended for use in preparing product specifications. Contact Soudal Accumentric before writing specifications.

## Section 10. Stability and Reactivity

Incompatibilities	This product is incompatible with strong oxidizing agents.
Decomposition Products May Include	Thermal decomposition products are dependent on combustion conditions. A complex mixture of airborne solid, liquid, particulates and gasses may evolve when the material burns. Combustion byproducts may include: oxides of carbon, oxides of zinc, incompletely burned hydrocarbons as fumes and smoke.
Conditions to Avoid	Avoid contact with incompatible materials and exposure to extreme temperatures.
Hazardous Polymerization	Not likely to occur.
Chemical Stability	Stable

## Section 11. Toxicological Information

Ingestion	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation	Inhalation is the primary route of exposure. In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact	Prolonged skin contact may cause redness and irritation.
Eye Contact	Eye contact is possible and should be avoided.

## Section 12. Ecological Information

Ecotoxicological Information	This product has not been evaluated for ecotoxicity. As with any industrial chemical, exposure to the environment should be prevented and minimized wherever possible.
Environmental Fate	The degree of biodegradability and persistence of this product has not been determined.

## Section 13. Disposal

Disposal instructions	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.
-----------------------	--

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

## Section 14. Transport Information

UN Number N/A  
UN Proper Shipping Name N/A  
DOT Classification N/A  
Packing Group N/A  
Road Shipment Information (DOT) Not subject to DOT regulations.

## Section 15. Regulatory Information

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.  
SARA 313 (TRI Reporting) Chemical Identity: Zinc compound  
Reporting threshold for other users: 10000 lbs  
Reporting threshold for manufacturing and processing: 25000 lbs

## Section 16. Other Information

Revision Date 6/26/2015

Disclaimer The data contained herein is based upon information that SOUDAL Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.