

The following SDS references the products below:

Isopropyl Fuel Dryer & Antifreeze

Vendor Item Number: PYFDI12

Manufactured By:

Niteo Products

Distributed by Kimball Midwest with the KM product-
identification number:

80-980



SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

 Pyroil™ FUEL DRYER & ANTIFREEZE
 PYFDI12

Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION
Product identifier

 Trade name : Pyroil™ FUEL DRYER &
 ANTIFREEZE

Recommended use of the chemical and restrictions on use
Details of the supplier of the safety data sheet

 Niteo Products, LLC
 P.O. Box 191629
 Dallas TX 75219
 United States of America

Emergency telephone number

CHEMTREC DIRECT 1-800-424-9300

Product Information

1-844-696-4836

SECTION 2. HAZARDS IDENTIFICATION
GHS Classification

 Flammable liquids : Category 2
 Eye irritation : Category 2A
 Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

GHS Label element

Hazard pictograms



Signal Word : Danger

 Hazard Statements : Highly flammable liquid and vapor.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.

 Precautionary Statements : **Prevention:**
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
ISOPROPANOL	67-63-0	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	99.83

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Administration of high doses of isopropanol in combination with known hepatotoxic chemicals resulted in enhanced liver toxicity in experimental animals.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
confusion
lung edema (fluid buildup in the lung tissue)
Causes serious eye irritation.
May cause drowsiness or dizziness.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

 Pyroil™ FUEL DRYER & ANTIFREEZE
 PYFDI12

Version: 1.1

 Foam
 Alcohol-resistant foam
 Carbon dioxide (CO2)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

 Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

 Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

 Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
 Remove all sources of ignition.
 Use personal protective equipment.
 Ensure adequate ventilation.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

 Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

 Pyroil™ FUEL DRYER & ANTIFREEZE
 PYFDI12

Version: 1.1

Other information : Comply with all applicable federal, state, and local regulations.
 Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.
 Avoid formation of aerosol.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Take precautionary measures against static discharges.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.
 Container may be opened only under exhaust ventilation hood.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 No smoking.
 Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ISOPROPANOL	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		REL	400 ppm 980 mg/m3	NIOSH/GUID E
		STEL	500 ppm 1,225 mg/m3	NIOSH/GUID E
		PEL	400 ppm 980 mg/m3	OSHA_TRA NS
		TWA	400 ppm	TN OEL

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

			980 mg/m3	
		STEL	500 ppm 1,225 mg/m3	TN OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
ISOPROPANOL	67-63-0	acetone	Urine	Sampling time: End of shift at end of work week.	40 mg/l	
Remarks:	Nonspecific, Background					

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

: Wear as appropriate:
impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.
When using do not eat or drink.

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: colourless
Odour	: alcohol-like
Odour Threshold	: No data available
pH	: No data available
	: No data available
Boiling point/boiling range	: 180.5 °F / 82.5 °C (1,013.232 hPa) Calculated Phase Transition Liquid/Gas
Flash point	: 50 °F / 10 °C Method: Tag closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 12 %(V) Calculated Explosive Limit
Lower explosion limit	: 2.5 %(V) Calculated Explosive Limit
Vapour pressure	: 60.52728 hPa (25 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.790 g/cm3 (25 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids
Aldehydes
alkalis
Amines
Ethylene oxide
halogenated hydrocarbons
halogens
isocyanates
Strong oxidizing agents
Do not use with aluminum equipment at temperatures above
49C or 120 degrees F.

Hazardous decomposition products : carbon dioxide and carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

ISOPROPANOL:

Acute oral toxicity : LD 50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC 50 (Rat): 16000 ppm
Exposure time: 4 h
Test atmosphere: vapour

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

Acute dermal toxicity : LD 50 (Rabbit): 12,800 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

ISOPROPANOL:

Result: Slightly irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ISOPROPANOL:

Result: Irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

ISOPROPANOL:

Remarks: Central nervous system

Carcinogenicity:**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

ISOPROPANOL:

Toxicity to fish : LC 50 (Fathead minnow (*Pimephales promelas*)): 5,770 -
7,450 mg/l
Exposure time: 96 h
Test Type: flow-through testToxicity to daphnia and other : LC 50 (Water flea (*Daphnia magna*)): > 10,000 mg/l
aquatic invertebrates
Exposure time: 24 h
Test Type: static test**Persistence and degradability****Components:**

No data available

Bioaccumulative potential**Components:**

ISOPROPANOL:

Partition coefficient: n- : log Pow: 0.05
octanol/water**Mobility in soil****Components:**

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

UN	1219	Isopropanol	3	II	LIMITED QUANTITY
----	------	-------------	---	----	------------------

U.S. DOT - RAIL

UN	1219	Isopropanol	3	II	LIMITED QUANTITY
----	------	-------------	---	----	------------------

U.S. DOT - INLAND WATERWAYS

UN	1219	Isopropanol	3	II	LIMITED QUANTITY
----	------	-------------	---	----	------------------

TRANSPORT CANADA - ROAD

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Version: 1.1

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

UN	1219	ISOPROPANOL SOLUTION	3	II	LIMITED QUANTITY

TRANSPORT CANADA - RAIL

UN	1219	ISOPROPANOL SOLUTION	3	II	LIMITED QUANTITY

TRANSPORT CANADA - INLAND WATERWAYS

UN	1219	ISOPROPANOL SOLUTION	3	II	LIMITED QUANTITY

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1219	ISOPROPANOL SOLUTION	3	II	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1219	Isopropanol SOLUTION	3	II	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1219	Isopropanol SOLUTION	3	II	

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1219	ISOPROPANOL SOLUTION	3	II	

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
XYLENE	1330-20-7	100	303951.367781

SARA 311/312 Hazards : Fire Hazard

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

 Pyroil™ FUEL DRYER & ANTIFREEZE
 PYFDI12

Version: 1.1

Acute Health Hazard
**SARA 313
 Component(s)SARA 313**

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA

: On TSCA Inventory

DSL

: All components of this product are on the Canadian DSL.

AICS

: On the inventory, or in compliance with the inventory

ENCS

: On the inventory, or in compliance with the inventory

KECI

: On the inventory, or in compliance with the inventory

PICCS

: On the inventory, or in compliance with the inventory

IECSC


: On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION
Further information

Revision Date: 07/31/2015

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p> 	<table border="1"> <tr> <td>HEALTH</td><td>2</td></tr> <tr> <td>FLAMMABILITY</td><td>3</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	3	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	3						
PHYSICAL HAZARD	0						

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IB

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H333	May be harmful if inhaled.

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

SAFETY DATA SHEET

Revision Date: 07/31/2015

Print Date: 09/29/2017

SDS Number: 600000000450

Pyroil™ FUEL DRYER & ANTIFREEZE
PYFDI12

Version: 1.1

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System