

The following SDS references the products below:

QUIK TITANIUM 7 INCH EPOXY STICK

Vendor Item Number: FG600478055

Manufactured By:

Polymetric Systems, Inc.

Distributed by Kimball Midwest with the KM productidentification number:

*80-203* 



# **SAFETY DATA SHEET**

## **Section 1. Identification**

Manufacturer

Polymeric Systems, Inc. 47 Park Avenue Elverson, PA 19520 Tel: (610) 286-2500

Fax: (610) 286-2510

Web: polymericsystems.com

**Emergency telephone** 

number

(610)286-2500 (24 Hours) Chemtrec Contract No.: 17567

**Supplier** 

Polymeric Systems, Inc.

47 Park Avenue

Elverson, PA 19520

Tel: (610) 286-2500

Fax: (610) 286-2510

Web: polymericsystems.com

Product name KNEADATITE® QUIK TITANIUM-24 CT. 3-1/2

Code FG600478070-24

Specific uses Sealants and adhesives

### Section 2. Hazards identification

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

SKIN SENSITIZATION - Category 1

GHS label elements
Hazard pictograms



Signal word Warning

**Hazard statements** May cause an allergic skin reaction.

**Precautionary statements** 

Prevention Wear protective gloves. Avoid breathing dust. Contaminated work clothing must not be

allowed out of the workplace.

Response IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before

reuse. If skin irritation or rash occurs: Get medical attention.

Storage Not applicable.

Disposal Dispose of contents and container in accordance with all local, regional, national and

international regulations.

**Hazards not otherwise** 

classified

None known.

## Section 3. Composition/information on ingredients

Substance/mixture

Mixture

#### **United States**

Ingredient name	% by weight	CAS number
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	10 - 30	25068-38-6
crystalline silica, non-respirable	0.1 - 1	14808-60-7

#### **Canada**

Name	%	CAS number
Talc (none asbestiform)	30 - 60	14807-96-6
Epichlorhydrin-bisphenol A resin	10 - 30	25068-38-6
calcium carbonate	10 - 30	471-34-1
Quartz	0.1 - 1	14808-60-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Eye contact** 

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects

**Inhalation** No known significant effects or critical hazards.

**Skin contact** May cause an allergic skin reaction.

**Eye contact**No known significant effects or critical hazards.
Ingestion
No known significant effects or critical hazards.

Over-exposure signs/symptoms

Date of issue/Date of revision 26 July 2019 Date of previous issue 3 Aug 2018. Version 3 2/11

### Section 4. First aid measures

Inhalation No specific data.

**Skin contact** Adverse symptoms may include the following:

irritation redness

**Eye contact**No specific data.
Ingestion
No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities

have been ingested or inhaled.

**Specific treatments** No specific treatment.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing

media

Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

None known.

Specific hazards arising

from the chemical

No specific fire or explosion hazard.

#### National Fire Protection Association (U.S.A.)



Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision 26 July 2019 Date of previous issue 3 Aug 2018. Version 3 3/11

### Section 6. Accidental release measures

#### **Environmental precautions**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** 

Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Shelf life: 12.

### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	CAS#	Exposure limits
crystalline silica, non-respirable	14808-60-7	OSHA PEL (United States, 5/2018).  TWA: 50 μg/m³ 8 hours. Form: Respirable dust OSHA PEL Z3 (United States, 6/2016).  TWA: 30 mg/m³ / (%SiO2+2) 8 hours. Form: Total dust

#### Canada

Date of issue/Date of revision 26 July 2019 Date of previous issue 3 Aug 2018. Version 3 4/11

## Section 8. Exposure controls/personal protection

### Ingredient name **Exposure limits** Talc (none asbestiform) CA British Columbia Provincial (Canada, 7/2018). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable TWA: 0.1 f/cc 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 3 mg/m<sup>3</sup> 8 hours. Form: Respirable CA Ontario Provincial (Canada, 1/2018). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction. TWA: 2 f/cc 8 hours. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable fraction calcium carbonate CA Quebec Provincial (Canada, 1/2014). TWAEV: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m<sup>3</sup> 8 hours.

Appropriate engineering controls

Quartz

**Environmental exposure** controls

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Respirable dust.

CA Quebec Provincial (Canada, 1/2014). TWAEV: 0.1 mg/m³ 8 hours. Form:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Skin protection Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision26 July 2019Date of previous issue3 Aug 2018.Version 35/11

## Section 8. Exposure controls/personal protection

Other skin protection Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

**Eye/face protection** Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-

shields.

## Section 9. Physical and chemical properties

**Physical state** Solid.

Color Brownish-White.

Odor Pungent. Sulfurous. [Strong]

**Odor threshold** Not available. pH Not applicable. **Melting point** Not available. Not available. **Boiling point** 

Flash point Closed cup: Not applicable. [Product does not sustain combustion.]

**Evaporation rate** Not applicable. Not available. Flammability (solid, gas) Lower and upper explosive Not available.

(flammable) limits

Not available. Vapor pressure Vapor density Not available.

Relative density 1.947

Solubility Easily soluble in the following materials: methanol and acetone.

Insoluble in the following materials: cold water and hot water.

Solubility in water Not applicable. Not available. **Auto-ignition temperature** >220°C (>428°F) **Decomposition temperature** 

**Viscosity** Kinematic (room temperature): Not applicable.

Kinematic (40°C (104°F)): Not applicable.

VOC 0.0541 lbs/gal (6.5 g/l)

**Aerosol product** 

## Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid No specific data.

Incompatible materials No specific data.

**Hazardous decomposition** 

products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision 26 July 2019 Date of previous issue 3 Aug 2018. Version 3

## Section 11. Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

No specific data.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-

#### **Sensitization**

No specific data.

### **Mutagenicity**

No specific data.

### **Carcinogenicity**

No specific data.

### **Conclusion/Summary**

: This product contains talc in a polymer matrix. Sanding the cured product may release particles containing talc with the polymer and other components of the matrix into the air. The talc contains less than 1% crystalline silica. Appropriate evaluations of the use of the product should be performed to determine if exposure to talc occurs due to handling and use. If such exposures occur, appropriate precautions must be taken to prevent exposure in excess of the OSHA Permissible Exposure Limit (PEL).

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
crystalline silica, non-respirable	-	1	Known to be a human carcinogen.

#### **Reproductive toxicity**

No specific data.

### **Teratogenicity**

No specific data.

### **Specific target organ toxicity (single exposure)**

No specific data.

#### Specific target organ toxicity (repeated exposure)

No specific data.

#### **Aspiration hazard**

No specific data.

Information on the likely routes of exposure

Not available.

#### Potential acute health effects

**Eye contact**No known significant effects or critical hazards.
Inhalation
No known significant effects or critical hazards.

**Skin contact** May cause an allergic skin reaction.

**Ingestion** No known significant effects or critical hazards.

Date of issue/Date of revision 26 July 2019 Date of previous issue 3 Aug 2018. Version 3 7/11

## **Section 11. Toxicological information**

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact Inhalation**No specific data.

No specific data.

**Skin contact** Adverse symptoms may include the following:

irritation

redness

**Ingestion** No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate Not available.

effects

Potential delayed effects Not available.

Long term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

#### Potential chronic health effects

No specific data.

General Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

No specific data.

## Section 12. Ecological information

#### **Toxicity**

No specific data.

#### Persistence and degradability

No specific data.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin	2.64 to 3.78	31	low

#### **Mobility in soil**

Date of issue/Date of revision 26 July 2019 Date of previous issue 3 Aug 2018. Version 3 8/11

## Section 12. Ecological information

Soil/water partition coefficient (K<sub>oc</sub>)

Not available.

Other adverse effects

No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**RCRA** classification

Not applicable.

## **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN Number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 15. Regulatory information

**United States** 

**U.S. Federal regulations** 

TSCA 5(a)2 final significant new use rules: 4-nonylphenol, branched

TSCA 8(a) PAIR: 4-nonylphenol, branched

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: zinc sulphide; zinc oxide

Date of issue/Date of revision26 July 2019Date of previous issue3 Aug 2018.Version 39/11

## Section 15. Regulatory information

Clean Air Act Section 112

None of the components are listed.

(b) Hazardous Air Pollutants (HAPs)

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

SARA 304 RQ Not applicable.

**SARA 311/312** 

Classification SKIN SENSITIZATION - Category 1

Composition/information on ingredients

Name	%	Classification
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin crystalline silica, non-respirable	≥10 - ≤25 ≤1	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	zinc sulphide	1314-98-3	5 - 10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

Massachusetts The following components are listed: TALC; SOAPSTONE

**New York** None of the components are listed.

New Jersey The following components are listed: SOAPSTONE; SILICA, QUARTZ; QUARTZ

(SiO2); TITANIUM; ZINC compounds

Pennsylvania The following components are listed: TALC; SOAPSTONE DUST; QUARTZ DUST;

QUARTZ; ZINC COMPOUNDS

**Minnesota Hazardous** 

**Substances** 

None of the components are listed.

California Prop. 65



**WARNING!**: This product can expose you to chemicals including Carbon black, Silica, crystalline, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	Cancer	Reproductive		Maximum acceptable dosage level
carbon black, non respirable crystalline silica, non-respirable	Yes. Yes.	No. No.	<u> </u>	-

Not applicable

### Canada

**Canadian lists** 

Canadian NPRI The following components are listed: zinc (and its compounds)

**CEPA Toxic substances** None of the components are listed.

EU Regulation (EC) No. 1907/2006 (REACH)

Substances of very high concern

Date of issue/Date of revision 26 July 2019 Date of previous issue 3 Aug 2018. Version 3 10/11

## Section 15. Regulatory information

Ingredient name	Intrinsic property		Reference number	Date of revision
4-Nonylphenol, branched and linear [substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof]	Substance of equivalent concern for environment	Candidate	ED/169/2012	12/19/2012

### **Inventory list**

Australia : Not determined.
Canada : Not determined.
China : Not determined.
Europe : Not determined.

Japan : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

New Zealand : Not determined.

**Philippines** : All components are listed or exempted.

Republic of Korea : Not determined.
Taiwan : Not determined.
Thailand : Not determined.
Turkey : Not determined.

**United States** : All components are listed or exempted.

Viet Nam : Not determined.

### Section 16. Other information

**Key to abbreviations** ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

References Not available.

Indicates information that has changed from previously issued version.

#### **Notice to reader**

NON-WARRANTY: The information presented in this publication is based upon the research and experience of Whitford. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Whitford makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Whitford are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. Whitford assumes no responsibility for the selection of products suitable to the particular purposes of any particular buyer. Whitford shall in no event be liable for any special, incidental, or consequential damages.

Date of issue/Date of revision 26 July 2019 Date of previous issue 3 Aug 2018. Version 3 11/11