

The following SDS references the products below:

LPS 3 Heavy Duty Rust Inhibitor

Vendor Item Number: 00316

Manufactured By:

ITW Brands

Distributed by Kimball Midwest with the KM productidentification number:

<u>80-614</u>



SAFETY DATA SHEET

1. Identification

Product identifier	LPS® 3 (Aerosol)	
Other means of identification		
Part Number	00316	
Recommended use	A specialized soft-film spray coating designed to prevent rust and corrosion on steel, aluminum and other metals.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	Distributor information	
Manufacturer		
Manufacturer		
Company name	ITW Pro Brands	
Address	4647 Hugh Howell Rd.	
	Tucker, GA 30084	
Country	(U.S.A.)	
	Tel: +1 770-243-8800	
In Case of Emergency	1-800-424-9300 (inside U.S.)	
	+001 703-527-3887 (outside U.S.)	
Website	www.lpslabs.com	
E-mail	lpssds@itwprobrands.com	
2. Hazard(s) identification		
Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Contains gas un irritation. Causes serious eye irritation.	nder pressure; may explode if heated. Causes skin
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves and eye/face protection.	
Response	If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention.	
Storage	Keep container tightly closed. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance v	with local/regional/national/international regulations.
Material name: LPS® 3 (Aerosol)		SDS US

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreated Light	I	64742-47-8	50 - 60
1-butoxy-2-propanol		5131-66-8	1 - 10
Acetone		67-64-1	1 - 10
Distillates Petroleum Hydrotreated Heavy		64742-54-7	1 - 10
Carbon Dioxide		124-38-9	1 - 5
Calcium Carbonate		471-34-1	0.1 - 1
Hydrodesulferized Heavy Petroleum Naptha		64742-82-1	0.1 - 1
Petrolatum		8009-03-8	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Rash. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is stopped.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.
General information	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Alcohol resistant foam. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

50165
Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.
Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment.
Level 3 Aerosol.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store locked up.

8. Exposure controls/personal protection

Occupational exposure limits

U.S OSHA Components	Туре	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	PEL	5 mg/m3	Oil mist
US. OSHA Table Z-1 Limits for Air Con			
Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
ACGIH			
Components	Туре	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m3	Oil mist
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form	
Acetone (CAS 67-64-1)	TWA	590 mg/m3		
		250 ppm		
Calcium Carbonate (CAS 471-34-1)	TWA	5 mg/m3	Respirable.	
		10 mg/m3	Total	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3		
		30000 ppm		
	TWA	9000 mg/m3		
		5000 ppm		

Dialogical limit

Biological limit values ACGIH Biological Exposure Indices				
Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
* - For sampling details, ple	ase see the source do	cument.		
Appropriate engineering controls	should be matche or other engineeri	d to conditions. If an ng controls to maint	oplicable, use pro ain airborne leve	nour) should be used. Ventilation rates cess enclosures, local exhaust ventilation, ls below recommended exposure limits. If rborne levels to an acceptable level.
Individual protection measure	s, such as personal	protective equipme	ent	
Eye/face protection	Wear safety glass	es with side shields	(or goggles). Ey	e wash fountain is recommended.
Skin protection				
Hand protection	Chemical resistan	t gloves are recomm	nended.	
Other	Avoid contact with	clothing. Wear suit	able protective cl	othing. Chemical resistant gloves.
Respiratory protection	No personal respiratory protective equipment normally required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.			
Thermal hazards	Not applicable.			
General hygiene considerations	as washing after h		I and before eatin	ve good personal hygiene measures, such ng, drinking, and/or smoking. Routinely e contaminants.

9. Physical and chemical properties

Appearance	Cloudy. Liquid.	
Physical state	Gas.	
Form	Aerosol.	
Color	Brown.	
Odor	Mild. Cherry.	
Odor threshold	Not available.	
рН	Not applicable	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	Not available.	
Flash point	64.4 °F (18.0 °C) Tag Closed Cup	
Evaporation rate	151 (Ethyl Ether)	
Flammability (solid, gas)	Flammable gas.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	0.6 %	

(%) Flammability limit - upper 6 % (%)

Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	446 °F (230 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.28 lb/gal
Percent volatile	63 - 82 %
Specific gravity	0.87
VOC	62.8 % per U.S. State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide, water and other products of combustion.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms related to the physical, chemical and toxicological characteristics	Irritating to eyes, respiratory system and skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
1-butoxy-2-propanol (CAS 5	5131-66-8)	
Acute		
Dermal		
LD50	Rabbit	1400 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Inhalation		
LC50	Rat	50 mg/l, 8 Hours

Components	Species	Test Results
Oral LD50	Rat	5800 mg/kg
alcium Carbonate (CAS 471-34		Soco ng/kg
Acute	,	
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Distillates Petroleum Hydrotreate	ed Heavy (CAS 64742-54-7)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 3.9 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Distillates Petroleum Hydrotreate	ed Light (CAS 64742-47-8)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
Vapor	-	
LC50	Rat	> 4.5 mg/l, 4 Hours
		> 0.1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg
lydrodesulferized Heavy Petrole	eum Naptha (CAS 64742-82-1)	
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Oral		1000 "
LD50	Rat	4800 mg/kg
Petrolatum (CAS 8009-03-8)		
<u>Acute</u>		
Dermal LD50	Rabbit	> 2000 ma/kg 24 Hours
	Παυμι	> 2000 mg/kg, 24 Hours
Oral LD50	Rat	> 5000 ma/ka
		> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye rritation	Causes serious eye irritation.	
Respiratory or skin sensitizati	on	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause sk	kin sensitization.
Germ cell mutagenicity		any components present at greater than 0.1% are
Carcinogenicity	This product is not considered to be a ca	arcinogen by IARC, ACGIH, NTP, or OSHA.
ACGIH Carcinogens		
Acetone (CAS 67-64-1)	A4 Not c	lassifiable as a human carcinogen.
Not listed.		
Material name: LPS® 3 (Aerosol)		

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052) Not regulated. US. National Toxicology Program (NTP) Report on Carcinogens Not listed. **Reproductive toxicity** This product is not expected to cause reproductive or developmental effects. Not classified. Specific target organ toxicity single exposure Specific target organ toxicity -Not classified. repeated exposure Aspiration hazard Not likely, due to the form of the product. **Chronic effects** Prolonged inhalation may be harmful. **Further information** None known.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

LOUGHIN		ed to be nammal to aquatio organiomo.	
Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Calcium Carbonate (CAS 47	1-34-1)		
Aquatic			
Fish	LC50	Western mosquitofish (Gambusia affi	nis) > 56000 mg/l, 96 hours
Distillates Petroleum Hydroti	eated Light (C	AS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Persistence and degradability	Not inherer	ntly biodegradable.	
Bioaccumulative potential	No data av	ailable for this product.	
Partition coefficient n-octa Acetone	nol / water (lo	og Kow) -0.24	
Mobility in soil	Not availab	le.	
Other adverse effects	None know	n.	
13. Disposal consideration	ons		
Disposal instructions	under pres disposed o not contam	I reclaim or dispose in sealed containers a sure. Do not puncture, incinerate or crush f as hazardous waste. Do not allow this m inate ponds, waterways or ditches with ch ontainer in accordance with local/regional/	. This material and its container must be aterial to drain into sewers/water supplies. D emical or used container. Dispose of
Hazardous waste code		te Flammable material with a flash point < te Reactive material	:140 F
Waste from residues / unused products		in accordance with local regulations. Emp idues. This material and its container mus structions).	
Contaminated packaging	Since empt		aste handling site for recycling or disposal. e, follow label warnings even after container is
14 Transport information			

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1

Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	
Marine pollutant	No
Special precautions for user	
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	No.
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	
Marine pollutant	No
EmS	Not available.
Special precautions for user	Not available.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.

DOT





15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
Toxic Substances Contro	ol Act (TSCA)
TSCA Section 12(b)	Export Notification (40 CFR 707, Subpt. D)
Not regulated.	
CERCLA Hazardous Sub	stance List (40 CFR 302.4)
Acetone (CAS 67-64-	1) Listed.
SARA 304 Emergency re	lease notification
Not regulated.	
OSHA Specifically Regul	ated Substances (29 CFR 1910.1001-1052)
Not regulated.	
Superfund Amendments and	Reauthorization Act of 1986 (SARA)
SARA 302 Extremely haz	ardous substance
Net listed	

Not listed.

SARA 311/312 Hazardous	Yes
SANA STI/STZ Hazaruous	163

chemical	

Classified hazard	Flammable (gases, aerosols, liquids, or solids)
categories	Gas under pressure
0	Skin corrosion or irritation
	Serious eye damage or eye irritation
	Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

35 %WV

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532 FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Low priority

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Carbon Dioxide (CAS 124-38-9)

Acetone (CAS 67-64-1)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1) Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7) Hydrodesulferized Heavy Petroleum Naptha (CAS 64742-82-1) Petrolatum (CAS 8009-03-8)

International Inventories

Country(s) or region	Inventory name On	inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	10-14-2015
Revision date	02-12-2019
Version #	09
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.