



# SAFETY DATA SHEET

Issuing date 01-Mar-2019

Revision Date 02-May-2023

Version 3.01

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier**

**Product name** 80-1235 BRAKE POWER

**Other means of identification**

**Product code** 80-1235

**Product Type** Extremely Flammable Aerosol

**Synonyms** None

**Recommended use of the chemical and restrictions on use**

**Recommended Use** Brake Parts Cleaner.

**Uses advised against** No information available

**Manufactured For:**

Kimball Midwest  
4800 Roberts Rd.  
Columbus, OH 43228  
800-233-1294

**Emergency telephone number**

**Chemical Emergency Phone Number** 1-800-424-9300

**2. HAZARDS IDENTIFICATION**

**Classification**


Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

**Label elements**

**Emergency Overview**

**Danger**

**Hazard statements**  
 Causes skin irritation  
 Causes serious eye irritation  
 Suspected of causing cancer  
 Suspected of damaging fertility or the unborn child  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 May cause damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways  
 May cause damage to organs ( Eyes, Skin, Respiratory System, Central Nervous System, and Hearing) through prolonged or repeated exposure.  
 Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated



**Appearance** Clear

**Physical state** Aerosol

**Odor** Solvent

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Wear protective gloves, protective clothing, eye protection, face protection.  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust, fumes, gas, mist, vapors, spray.  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 Do not spray on an open flame or other ignition source  
 Pressurized container: Do not pierce or burn, even after use

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice, attention.  
 Specific treatment (see first aid on this label).  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice, attention.  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice, attention.  
 Take off contaminated clothing and wash it before reuse.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing  
 Call a POISON CENTER or doctor, physician if you feel unwell.  
 IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.  
 Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

**Precautionary Statements - Disposal**

Dispose of contents, container to an approved waste disposal plant.

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other information**

No information available.

0.000034 % of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
ACETONE	67-64-1	50-60
HEPTANE,BRANCHED,CYCLIC/LINEAR	426260-76-6	10-20
XYLENE	1330-20-7	10-20
CARBON DIOXIDE	124-38-9	1-10
ETHYL BENZENE	100-41-4	1-10
HEPTANE	64742-49-0	<1
TOLUENE	108-88-3	<1
BENZENE	71-43-2	<0.01

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
<b>Eye contact</b>	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
<b>Skin contact</b>	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
<b>Ingestion</b>	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

**Protection of First-aiders** Remove all sources of ignition.

**Most important symptoms and effects, both acute and delayed**

**Main Symptoms** Causes skin and serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

**Specific hazards arising from the chemical**

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers. In the event of fire and/or explosion do not breathe fumes.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions**

**Environmental precautions** Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Should not be released into the environment.

**Methods and material for containment and cleaning up**

**Methods for Containment** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods for cleaning up** Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Advice on safe handling**

Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges.

**Conditions for safe storage, including any incompatibilities****Technical measures/Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

**Incompatible products**

Strong acids, alkalis, oxidizing agents.

**Aerosol Level**

2

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
XYLENE 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	Not Established
CARBON DIOXIDE 124-38-9	STEL: 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m <sup>3</sup> (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m <sup>3</sup>	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> STEL: 30000 ppm STEL: 54000 mg/m <sup>3</sup>
ETHYL BENZENE 100-41-4	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
HEPTANE 64742-49-0	TLV: 400 ppm STEL: 500 ppm	TWA: 500 ppm	-
TOLUENE 108-88-3	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
BENZENE 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm S*	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm

		(vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	
--	--	---	--

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Measures** Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits.

**Individual protection measures, such as personal protective equipment**

- Eye/Face Protection** Tightly fitting safety goggles.
- Skin and body protection** Chemical resistant apron. Protective gloves.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	Aerosol	<b>Odor</b>	Solvent
<b>Appearance</b>	Clear	<b>Odor Threshold</b>	
<b>Color</b>	Colorless		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash Point	-20 °C / -4 °F	Based on lowest flashpoint of the products constituents.	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit			
lower flammability limit	No information available		
Vapor pressure			
Vapor density	No information available		
Specific gravity	0.781		
Water solubility	No information available		
Partition coefficient: n-octanol/water			
Autoignition temperature	No information available	Not applicable	
Hyphen			
Viscosity	No information available		
Explosive properties			

**Other information**

VOC Content(%) 40.52

## 10. STABILITY AND REACTIVITY

### Reactivity

Stable under recommended storage conditions

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to Avoid

Heat, flames and sparks. Exposure to air or moisture over prolonged periods. Extremes of temperature and direct sunlight.

### Incompatible materials

Strong acids, alkalis, oxidizing agents.

### Hazardous decomposition products

Carbon oxides , Hydrocarbons, Fumes.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	May cause respiratory irritation, May cause drowsiness or dizziness.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Causes skin irritation.
<b>Ingestion</b>	May be fatal if swallowed and enters airways.

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
HEPTANE 64742-49-0	> 5000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 73680 ppm ( Rat ) 4 h
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
BENZENE 71-43-2	= 810 mg/kg ( Rat )	> 8200 mg/kg ( Rabbit )	= 44.66 mg/L ( Rat ) 4 h

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Causes skin and serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause respiratory irritation. May cause damage to organs (listed below) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Irritating to skin.
<b>Eye damage/irritation</b>	Irritating to eyes.
<b>Sensitization</b>	Not a known sensitizer.
<b>Germ cell mutagenicity</b>	Not a germ cell mutagen.
<b>Carcinogenicity</b>	The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7	-	Group 3	-	-
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
TOLUENE 108-88-3	-	Group 3	-	-
BENZENE 71-43-2	A1	Group 1	Known	X

**Legend:**

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - *Animal Carcinogen*

IARC: (International Agency for Research on Cancer)

Group 2B - *Possibly Carcinogenic to Humans*Group 3 - *Not Classifiable as to Carcinogenicity in Humans*

OSHA: (Occupational Safety &amp; Health Administration)

X - *Present*

<b>Reproductive toxicity</b>	Product is or contains a chemical which is a known or suspected reproductive hazard.
<b>Specific target organ systemic toxicity (single exposure)</b>	May cause respiratory irritation. May cause drowsiness or dizziness.
<b>Specific target organ systemic toxicity (repeated exposure)</b>	May cause damage to Target Organs listed below through prolonged or repeated exposure.
<b>Chronic toxicity</b>	May cause adverse liver effects. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
<b>Target organ effects</b>	Eyes, Skin, Respiratory System, Central Nervous System, and Hearing.
<b>Neurological effects</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product Information**

**Unknown acute toxicity** 0.000034 % of the mixture consists of ingredient(s) of unknown toxicity

**The following values are calculated based on chapter 3.1 of the GHS document**

<b>ATEmix (oral)</b>	61141 mg/kg
<b>ATEmix (dermal)</b>	14121 mg/kg
<b>ATEmix (inhalation-gas)</b>	96971 mg/l
<b>ATEmix (inhalation-dust/mist)</b>	18.5 mg/l
<b>ATEmix (inhalation-vapor)</b>	1037.5 mg/l

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Very toxic to aquatic life with long lasting effects

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ACETONE 67-64-1	-	LC50: 4.74 - 6.33mL/L (96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h, Lepomis macrochirus)	-	EC50: 10294 - 17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)
XYLENE 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)



		LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)		
CARBON DIOXIDE 124-38-9	-	0.46 mg/L LC50 Oncorhynchus mykiss	-	-
ETHYL BENZENE 100-41-4	EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)	-	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)
HEPTANE 64742-49-0	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	-
TOLUENE 108-88-3	EC50: >433mg/L (96h, Pseudokirchneriella subcapitata) EC50: =12.5mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 15.22 - 19.05mg/L (96h, Pimephales promelas) LC50: =12.6mg/L (96h, Pimephales promelas) LC50: 5.89 - 7.81mg/L (96h, Oncorhynchus mykiss) LC50: 14.1 - 17.16mg/L (96h, Oncorhynchus mykiss) LC50: =5.8mg/L (96h, Oncorhynchus mykiss) LC50: 11.0 - 15.0mg/L (96h, Lepomis macrochirus) LC50: =54mg/L (96h, Oryzias latipes) LC50: =28.2mg/L (96h, Poecilia reticulata) LC50: 50.87 - 70.34mg/L (96h, Poecilia reticulata)	-	EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) EC50: =11.5mg/L (48h, Daphnia magna)
BENZENE 71-43-2	EC50: =29mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 10.7 - 14.7mg/L (96h, Pimephales promelas) LC50: =5.3mg/L (96h, Oncorhynchus mykiss) LC50: =22.49mg/L (96h, Lepomis macrochirus) LC50: =28.6mg/L (96h, Poecilia reticulata) LC50: 22330 - 41160µg/L (96h, Pimephales promelas) LC50: 70000 - 142000µg/L (96h, Lepomis macrochirus)	-	EC50: 8.76 - 15.6mg/L (48h, Daphnia magna) EC50: =10mg/L (48h, Daphnia magna)

**Persistence and degradability****Bioaccumulation**

Chemical name	Partition coefficient
ACETONE 67-64-1	-0.24
XYLENE 1330-20-7	3.15
ETHYL BENZENE 100-41-4	3.6
TOLUENE 108-88-3	2.73
BENZENE 71-43-2	2.13

**Other adverse effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment

**Waste Disposal Methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with local regulations.

**Contaminated packaging** Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** LIMITED QUANTITY

**IATA** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD .QTY.

**IMDG** UN1950, AEROSOLS, 2.1, (6.1),LTD. QTY.

### 15. REGULATORY INFORMATION

#### International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	X	X	X	X	X	X	X	X
HEPTANE, BRANCHED, CYCLIC/LINEAR	X	X	Not listed	Not listed	Not listed	Not listed	X	Not listed
XYLENE	X	X	X	X	X	X	X	X
CARBON DIOXIDE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
HEPTANE	X	X	X	Not listed	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
BENZENE	X	X	X	X	X	X	X	X

**Legend:** \_\_\_\_\_

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**CHINA** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	10-20	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-10	0.1
TOLUENE - 108-88-3	108-88-3	<1	1.0
BENZENE - 71-43-2	71-43-2	<0.01	0.1

#### **SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	Yes
<b>Reactive Hazard</b>	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
TOLUENE 108-88-3	1000 lb	X	X	X
BENZENE 71-43-2	10 lb	X	X	X

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
TOLUENE 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE 71-43-2	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

### US State Regulations

**California Proposition 65**

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Chemical name	California Proposition 65
ETHYL BENZENE - 100-41-4	Cancer/ 1-10%
TOLUENE - 108-88-3	Developmental / <1%
BENZENE - 71-43-2	Cancer Developmental (Male) / <0.01%

Note

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
XYLENE 1330-20-7	X	X	X
CARBON DIOXIDE 124-38-9	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
TOLUENE 108-88-3	X	X	X
BENZENE 71-43-2	X	X	X

EPA Pesticide Registration Number Not applicable

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

**16. OTHER INFORMATION**

<b>NFPA</b>	Health hazards 2	Flammability 4	Instability 0	Special hazards -
<b>HMIS</b>	Health hazards 2*	Flammability 4	Physical hazards 1	Personal protection B
Chronic Hazard Star Legend	* = Chronic Health Hazard			

<b>Prepared By</b>	Regulatory Affairs
<b>Issuing date</b>	01-Mar-2019
<b>Revision Date</b>	02-May-2023
<b>Revision Note</b>	

**Disclaimer**

---

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

**End of Safety Data Sheet**