

Safety Data Sheet acc. to OSHA HCS

Printing date 10/30/2019 Reviewed on 10/30/2019

1 Identification

- Product identifier
 - Trade name: Nickel Anti-Seize Quick Pump
 - Part number: 80-117
 - Application of the substance / the mixture

Lubricant

- Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kimball Midwest 4800 Roberts Road Columbus, OH 43228 Tel: 800-233-1294

- Information department: Product Safety Department
- Emergency telephone number:

United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- Label elements
 - GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms





GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labeling:

Lubricating greases

nicke

- Hazard statements

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash face, hands and any exposed skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Safety Data Sheet

Printing date 10/30/2019 Reviewed on 10/30/2019

(Contd. of page 1)

P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:

- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- Other hazards

- Results of PBT and vPvB assessment
 - PBT: Not applicable.- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:		
CAS: 74869-21-9 Lubricating greases	Carc. 1B, H350	70 – 79%
CAS: 7440-02-0 nickel	Flam. Sol. 2, H228; Carc. 2, H351; STOT RE 1, H372; Skin Sens. 1, H317	10 – 19%
CAS: 7782-42-5 Graphite	Eye Irrit. 2A, H319	5 – 9%

4 First-aid measures

- Description of first aid measures

- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

Safety Data Sheet

Printing date 10/30/2019 Reviewed on 10/30/2019

(Contd. of page 2)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
 - Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
 - Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

CAS	: 7440-02-0 nickel
PEL	Long-term value: 1 mg/m³
	Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A
	Long-term value: 1.5* mg/m³ elemental, *inhalable fraction

- Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
 - Personal protective equipment:
 - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

Safety Data Sheet acc. to OSHA HCS

Printing date 10/30/2019 Reviewed on 10/30/2019

(Contd. of page 3)

9 Physical and chemical properties

5 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -			
- Information on basic physical and chemical properties - General Information - Appearance:			
- Form:	Pasty		
- Color:	Silver grey		
- Odor:			
- Odor threshold:	Petrol-like		
- Odor threshold:	Not determined.		
- pH-value at 20 °C (68 °F):	7		
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	> 232 °C (> 449.6 °F) ≥ 2,730 °C (≥ 36.930 °F)		
- Flash point:	> 232 °C (> 449.6 °F)		
- Flammability (solid, gaseous):	Not applicable.		
- Decomposition temperature:	Not determined.		
- Auto igniting:	Product is not selfigniting.		
- Danger of explosion:	Product does not present an explosion hazard.		
- Explosion limits: - Lower: - Upper:	Not determined. Not determined.		
- Vapor pressure:	Not determined.		
- Density at 20 °C (68 °F): - Relative density - Vapor density - Evaporation rate	~ 1.145 g/cm³ (~ 9.55503 lbs/gal) Not determined. Not determined. Not determined.		
- Solubility in / Miscibility with - Water:	Not miscible or difficult to mix.		
- Partition coefficient (n-octanol/w	- Partition coefficient (n-octanol/water): Not determined.		
- Viscosity: - Dynamic: - Kinematic:	Not determined. Not determined.		
- Solvent content: - VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal		
- Solids content:	19.0 %		
- Other information	No further relevant information available.		

10 Stability and reactivity

- Reactivity No further relevant information available.
 - Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
 - Acute toxicity:
 - Primary irritant effect:
 - on the skin: No irritant effect.
 - on the eye: No irritating effect.
 - Sensitization: Sensitization possible through skin contact.
 - Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Safety Data Sheet acc. to OSHA HCS

Printing date 10/30/2019 Reviewed on 10/30/2019

(Contd. of page 4)

Carcinogenic.

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)	
CAS: 7440-02-0 nickel	2B
- NTP (National Toxicology Program)	
CAS: 7440-02-0 nickel	R
- OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Additional ecological information:
 - General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:

14 Transport information

Recommendation: Disposal must be made according to official regulations.

- UN-Number - DOT, IMDG, IATA	not regulated
- UN proper shipping name - DOT, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT, ADN, IMDG, IATA - Class	not regulated
- Packing group - DOT, IMDG, IATA	not regulated
- Environmental hazards: - Marine pollutant:	No
- Special precautions for user	Not applicable.
- Transport in bulk according to Annex II of	MARPOL73/78

Not applicable.

not regulated

- UN "Model Regulation": 15 Regulatory information

and the IBC Code

- Safety, health and environmental regulations/legislation specific for the substance or mixture - Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/30/2019 Reviewed on 10/30/2019

(Contd. of page 5)

- Section 313 (Specific toxic chemical listings): CAS: 7440-02-0 nickel

- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65

Chemicals known to cause cancer:

CAS: 7440-02-0 nickel

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

CAS: 7440-02-0 nickel A5

- NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 7440-02-0 nickel

- National regulations:

- Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
 - Date of preparation / last revision 10/30/2019 / 52
 - Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit Flam. Sol. 2: Flammable solids - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1

Carc. 1B: Carcinogenicity – Category 1B Carc. 2: Carcinogenicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

* Data compared to the previous version altered.

Disclaimer:

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.