



Specializing in Materials Management

HIGH PERFORMANCE SMOOTH THREAD SEALANT WITH PTFE SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product Name: 80-138 and 80-139 High Performance Smooth Thread Sealant with PTFE

Manufacturer: Kimball Midwest
4800 Roberts Road
West Mansfield, OH 43228
Phone: 800-233-1294

Emergency Phone Number: Chemtrec 1-800-424-9300

Product Use: Pipe Thread Sealant

Restriction on Use: None known

SDS Date of Preparation: April 7 2016

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification (Hazcom 2012):

Flammable Liquid, Category 2

Eye Irritant Category 2

Specific Target Organ Toxicity – Single Exposure Category 3 (Narcotic effects)

Label Elements:



Signal Word: Danger

Hazard Phrases:

H225 Highly flammable liquid and vapor

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

Precautionary Phrases:

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P233 Keep container tightly closed.

P260 Do not breathe mist, vapor or fumes.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves and eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical attention.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER or doctor if you feel unwell.
P370+P378 In case of fire: Use fog, foam, carbon dioxide or dry chemical to extinguish.
P405 Store locked up
P501 Dispose of contents in accordance with local, regional and national laws.

Other Hazards: None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	%
Isopropyl alcohol	67-63-0	40-50
Talc	14807-96-6	15-30
Vegetable oil	Proprietary	10-20
Calcium carbonate	471-34-1	4-9
Titanium dioxide (bound in sealant)	13463-67-7	1-5
PTFE	9002-84-0	1-5

The specific identity and/or exact percentage of composition has been withheld as a trade secret.

SECTION 4: FIRST AID MEASURES

Eye: Flush eyes thoroughly with water for several minutes, holding the eyelids apart. Get medical attention if irritation develops or persists.

Skin: Wash thoroughly with plenty of water. Get medical attention if irritation persists.

Inhalation: Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

Ingestion: If large amounts ingested, seek medical attention. Do NOT induce vomiting.

Most Important symptoms and effects, both acute and delayed: May cause serious eye irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness.

Indication of any immediate medical attention and special treatment needed: Immediate medical attention generally not required.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable and Unsuitable Extinguishing Media: Use water fog, foam, carbon dioxide or dry chemical.

Special Hazards Arising from the Chemical: Hazardous decomposition compounds may yield acrid smoke and fumes, oxides of calcium and carbon and fumes of fluoride.

Special Equipment and Precautions for Fire-Fighters: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment. Use caution: slip hazard.

Environmental Hazards: Report spills and releases as required to appropriate authorities.

Methods and Material for Containment and Cleaning Up: Because of its viscous nature, this product

is not expected to leak or spill. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal. Clean area thoroughly with mineral spirits.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged skin contact. Avoid inhalation. Do not transfer to unlabeled containers.

Conditions for Safe Storage, Including any Incompatibilities: Store away from extreme heat and open flames. Store away from oxidizers. At Temperatures exceeding 650°F, PTFE can emit toxic substances. This product should not be used at temperatures exceeding its recommended service temperatures of 300°F.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits
Isopropyl alcohol	200 ppm TWA ACGIH TLV 400 ppm STEL ACGIH TLV 400 ppm TWA OSHA PEL
Talc	2 mg/m ³ TWA ACGIH TLV (respirable) 20 mppcf TWA OSHA PEL (containing <1% Quartz)
Vegetable oil (as vegetable oil mist)	15 mg/m ³ TWA OSHA PEL (total dust) 5 mg/m ³ TWA OSHA PEL (respirable fraction)
Calcium carbonate	15 mg/m ³ TWA OSHA PEL (total dust) 5 mg/m ³ TWA OSHA PEL (respirable fraction)
Titanium dioxide	10 mg/m ³ TWA ACGIH TLV (respirable) 15 mg/m ³ TWA OSHA PEL (total dust)
PTFE	15mg/m ³ TWA OSHA PEL (as respirable dust)

Appropriate Engineering Controls: This product contains Isopropyl Alcohol which evaporates slowly when it is applied. Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. If the product is used at high temperatures, local exhaust ventilation may be required.

Individual Protection Measures:

Respiratory Protection: In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin Protection: Impervious gloves such as rubber or nitrile recommended where needed to avoid prolonged skin contact.

Eye Protection: Safety glasses or goggles recommended where needed to avoid eye contact.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White colored paste	Vapor Density (air = 1): Not available
Odor: Alcohol odor	Specific Gravity: 1.1
Odor Threshold: Not established	Water Solubility: Partial until dry
pH: Not available	Octanol/Water Partition Coefficient: Not available
Melting Point/Freezing Point: Not available	Autoignition Temperature: Not available
Boiling Point: 180°F	Decomposition Temperature: Not available
Flash Point: 54°F	Viscosity: Not available

Evaporation Rate: Not available	Explosion Properties: None
Flammable Limits: LEL: Not established UEL: Not established	Oxidizing Properties: Not oxidizing
Vapor Pressure: 30.75 mmHg@20°C	Aerosol Fire Protection Level: Not applicable
VOC Content: 43%	Flammability (solid, gas): Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Open flames and intense heat.

Incompatible Materials: None known.

Hazardous Decomposition Products: Hazardous decomposition compounds may yield acrid smoke, fumes of fluoride, oxides of calcium and oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

Potential Health Effects:

Eye: May cause serious eye irritation.

Skin: Prolonged contact may cause irritation and drying of the skin.

Inhalation: Inhalation of vapors and fumes from thermal decomposition may cause respiratory irritation and metal fume fever (from PTFE thermal decomposition) with symptoms of fever and chills. Inhalation of vapors may also cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, drowsiness, tingling, numbness and shooting pains in the hands and arms, tremors, narcosis, nausea, vomiting, and unconsciousness. High vapor concentrations may cause burning sensation of the nose and throat and watering of the eyes. Severe overexposures may cause respiration depression, blurred vision, blindness, anemia, liver and kidney damage, coma and death.

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea.

Chronic Hazards: Prolonged inhalation of mists or vapors may result in lung damage.

Carcinogen Status: Titanium dioxide is listed by IARC as a group 2B carcinogen (possible human carcinogen). Titanium dioxide is only known to cause cancer by inhalation. The titanium dioxide is bound in the product matrix so inhalation exposure does not occur during use. None of the other components of this product are listed as carcinogens by OSHA, IARC, NTP, ACGIH, or the EU CLP.

Acute Toxicity Values:

Isopropyl alcohol: Oral rat LD50: 5840 mg/kg, inhalation rat LC50 > 10000 ppm/6hr, dermal rabbit LD50: 16.4 mL/kg

Calcium Carbonate: Oral rat LD50 > 2000 mg/kg, inhalation rat LC50 > 3 mg/L, dermal rat LD50 > 2000 mg/kg.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Isopropyl alcohol: Pimephales promelas LC50 9640 mg/L/96hr
Calcium Carbonate: Oncorhynchus mykiss LC50 > 100 mg/L/96hr

Persistence and Degradability: No data available

Bioaccumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: None known

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, regional and national regulations.

SECTION 14: TRANSPORT INFORMATION

DOT

U.S. department of transportation ground (49 cfr):

Proper shipping name: RESIN SOLUTION

Hazard class or division: 3

Identification number: UN 1866

Packing group: III

Exceptions: LTD QTY, exempt from labeling less than 5 liters

(ICAO/IATA):

Proper shipping name: RESIN SOLUTION

Hazard class or division: 3

Identification number: UN 1866

Packing group: III

Exceptions: LTD QTY ,

(IMO/IMDG):

Proper shipping name: RESIN SOLUTION

Hazard class or division: 3

Identification number: UN 1866

Packing group: III. LTD QTY, exempt from labeling less than 5 liters

Note: This product may be shipped as a limited quantity or ORM-D if the packaging meets the requirements.

SECTION 15: REGULATORY INFORMATION

Safety, health, and environmental regulations specific for the product in question.

CERCLA Hazardous Substances (Section 103)/RQ: This product is not subject to reporting requirements under CERCLA. However, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Fire Hazard, Acute Health

SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: None

EPA TSCA Inventory: All of the components of this product are listed on the TSCA inventory.

CALIFORNIA PROPOSITION 65: This product is not known to contain listed chemicals.

SECTION 16: OTHER INFORMATION

Revision Summary: New format to comply with OSHA Hazcom 2012

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.