

The following SDS references the products below:

*Crimped Control Cup Brush, 3.1/4" outside diameter, Brass
Coated steel wire gauge .020", 5/8"-11 UNC threaded nut, JAZ
standard markings and KIMBALL packaging. Maximum safety
RPM: 8,500. Recommended working max. RPM: 6,000*

Vendor Item Number: 67552-215

Manufactured By:

Jaz USA, Inc

Distributed by Kimball Midwest with the KM product-
identification number:

87-187




MATERIAL DATA SHEET	PAGE: 1 OF 2
MODEL: 67552-215	DATE: 17-05-2016

SECTION I. PRODUCT DESCRIPTION

Crimped Control Cup Brush, 3.1/4" outside diameter, Brass Coated steel wire gauge .020", 5/8"-11 UNC threaded nut, JAZ standard markings and KIMBALL packaging. Maximum safety RPM: 8,500. Recommended working max. RPM: 6,000

SECTION II. PHYSICAL DATA AND DIMENSIONS



**According to above drawing, 3.1/4" diameter, 1.1/8" trim length.
Total N° of .020" wire ends in the brush: 2,160
Weight of total product: 500 gr.**

SECTION III. CHEMICAL COMPOSITION OF WIRE

Brass Coated Steel Wire with following chemical composition:

C = 0,65 – 0,85%

Mn = 0,40 – 0,80%

Si = 0,15 – 0,30 %

There is no special requirements nor standards in the technical brushware industry related to the steel wires used in our products.



MATERIAL DATA SHEET	PAGE: 2 OF 2
MODEL: 67552-215	DATE: 17-05-2016

SECTION IV. SAFETY DATA

The European Standard EN 1083-2 about Safety Requirements in the use of Power-driven brushes states the safety instructions that all brush operators must observe. These requirements and common safety practices will reduce the likelihood of physical injury and brush fail:

Wear safety goggles, protective clothing and equipment.

Observe all speed restrictions indicated on the brushes, packaging or catalogue.

And do not exceed Maximum Safe Free Speed (Max. RPM) under any circumstances.

Keep machine guards in place.

Do not use deteriorated brushes

The power tool speed influences the performance of the brush and the safety of the operator. If load speed marked on the power tool is higher than the brush Maximum RPM do not mount brush. Maximum RPM are indicated on brush side-plates and shall never be exceeded. For most brushing applications optimum results are achieved at the Recommended RPM specified in our catalogue for every power driven brush.

Eibar, Spain, May 17th, 2016.

Signed by: OSCAR VAZQUEZ
Manufacturing Director

Signed by: MANUEL LEDO
Quality Manager