



Page 1 of 13

Revision: August 1, 2019

1 Identification

· Product identifier

· Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

Item No. 80-1151

· Article number: No other identifiers

· Recommended use and restriction on use

· Recommended use:

Penetrating oil Lubricant

· Restrictions on use: See Sections 8 and 10 for further information.

· Details of the supplier of the Safety Data Sheet

· Manufactured For:

Kimball Midwest

· 4800 Roberts Rd

· Columbus, OH 43228

Telephone: 800-233-1294

· Emergency telephone number:

CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Additional information:

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of ingredient(s) of unknown toxicity.

(Contd. on page 2)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 1)

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS02 GHS04 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light heptane

Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P261 Avoid breathing mist/vapors/spray.

P280 Wear protective gloves and eye protection.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P331 Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Hazard description:

· WHMIS-symbols:

A - Compressed gas

B5 - Flammable aerosol

D2B - Toxic material causing other toxic effects



(Contd. on page 3)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 3

· HMIS-ratings (scale 0 - 4)



1 Health = 1 3 Fire = 3 REACTIVITY 3 Reactivity = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
64742-47-8 Distillates (petroleum), hydrotreated light			
♦ Asp. Tox. 1, H304			
142-82-5 heptane	10-25%		
Flam. Liq. 2, H225 Asp. Tox. 1, H304			
Skin Irrit. 2, H315; STOT SE 3, H336			
124-38-9 carbon dioxide	2.5-10%		
Press. Gas, H280			

Additional information:

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.

4 First-aid measures

- Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

(Contd. on page 4)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 3)

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Frostbite

Irritating to eyes and skin.

Coughing

Breathing difficulty

Dizziness

Nausea

· Danger

Danger of pulmonary edema.

Danger of pneumonia.

Danger of impaired breathing.

· Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

Treat frost-bitten areas appropriately.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water stream.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Danger of receptacles bursting because of high vapor pressure if heated.

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Cool endangered receptacles with water fog.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol.

(Contd. on page 5)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 4)

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

· Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable receptacles.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:
- · Precautions for safe handling

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Avoid splashes or spray in enclosed areas.

Information about protection against explosions and fires:

Protect against electrostatic charges.

Emergency cooling must be available in case of nearby fire.

Keep ignition sources away - Do not smoke.

Do not spray on a naked flame or any incandescent material.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· Specific end use(s) No further relevant information available.

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 5)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

<u> </u>	· Control parameters				
· Components with limit values that require monitoring at the workplace:					
64742-47-8 Distillates (petroleum), hydrotreated light					
EL (Canada)	Long-term value: 200 mg/m³ Skin				
142-82-5 heptane					
PEL (USA)	Long-term value: 2000 mg/m³, 500 ppm				
REL (USA)	Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min				
TLV (USA)	Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm				
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm				
EV (Canada)	Short-term value: 2.045 mg/m³, 500 ppm Long-term value: 1.635 mg/m³, 400 ppm				
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm				
124-38-9 carbo	124-38-9 carbon dioxide				
PEL (USA)	Long-term value: 9000 mg/m³, 5000 ppm				
REL (USA)	Short-term value: 54.000 mg/m³, 30.000 ppm Long-term value: 9000 mg/m³, 5000 ppm				
TLV (USA)	Short-term value: 54.000 mg/m³, 30.000 ppm Long-term value: 9000 mg/m³, 5000 ppm				
EL (Canada)	Short-term value: 15000 ppm Long-term value: 5000 ppm				
EV (Canada)	Short-term value: 54.000 mg/m³, 30.000 ppm Long-term value: 9.000 mg/m³, 5.000 ppm				
LMPE (Mexico)	Short-term value: 30000 ppm Long-term value: 5000 ppm				

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Engineering controls: No further relevant information available.

(Contd. on page 7)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 6)

Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when high concentrations are present.

For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Color:
Odor:
Odor:
Odor threshold:
Aerosol
Translucent
Solvent-like
Not determined.

pH-value:
Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Not applicable, as aerosol.
Not applicable, as aerosol.
Extremely flammable aerosol.

Flammability (solid, gaseous):
Extremely flammable aerosol.

· Auto-ignition temperature: 210 °C (410 °F)

(Contd. on page 8)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 7)

• **Decomposition temperature:** Not determined.

• **Auto igniting:** Product is not self-igniting.

· Danger of explosion: Not determined.

· Explosion limits:

Lower: 1.1 Vol % **Upper:** 7 Vol %

Vapor pressure: Not determined.
Density: Not determined.
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC (California) < 25%

Exempt VOCs are excluded from this value
Other information
No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

Danger of receptacles bursting because of high vapor pressure if heated.

· Possibility of hazardous reactions

Develops readily flammable gases / fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Extremely flammable aerosol.

Used empty containers may contain product gases which form explosive mixtures with air.

Reacts with strong oxidizing agents.

Toxic fumes may be released if heated above the decomposition point.

Conditions to avoid

Keep ignition sources away - Do not smoke.

Keep away from heat and direct sunlight.

Store away from oxidizing agents.

- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

(Contd. on page 9)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 8)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:				
64742-47-	64742-47-8 Distillates (petroleum), hydrotreated light			
Oral	LD50	> 5000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rabbit)		
142-82-5	142-82-5 heptane			
Oral	LD50	> 5000 mg/kg (rat) (Estimate)		
Inhalative	LC50/4h	103 mg/l (rat)		

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Irritant

Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

- · Carcinogenic categories
- · NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Probable Routes of Exposure

Inhalation.

Eye contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Vapors have narcotic effect.

Irritating to skin.

May be fatal if swallowed and enters airways.

Repeated Dose Toxicity: May cause damage to organs through prolonged or repeated exposure.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: Toxic for aquatic organisms
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish

(Contd. on page 10)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 9)

- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Contact waste processors for recycling information.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN1950
- · UN proper shipping name



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal).

· **DOT** Aerosols, flammable

· ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (HEPTANES), MARINE POLLUTANT

IATA AEROSOLS, flammable

· Transport hazard class(es)

· DOT



· Class 2.1

(Contd. on page 11)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 10) · Label 2.1 · ADR 2 5F Gases · Class · Label 2.1 ·IMDG · Class 2.1 · Label 2.1 · IATA · Class 2.1 · Label 2.1 · Packing group · DOT, ADR, IMDG, IATA Not Regulated · Environmental hazards: Product contains environmentally hazardous substances: heptane · Marine pollutant: Yes Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · Special precautions for user Warning: Gases Danger code (Kemler): · EMS Number: F-D,S-U · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: On passenger aircraft/rail: 75 kg · Quantity limitations On cargo aircraft only: 150 kg · ADR Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · IMDG · Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity (Contd. on page 12)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 11)

UN "Model Regulation":

UN1950, Aerosols, ENVIRONMENTALLY HAZARDOUS,

2.1

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

142-82-5 heptane

D

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

State Right to Know Listings

None of the ingredients is listed.

- · Canadian substance listings:
- · Canadian Domestic Substances List (DSL)

All ingredients are listed.

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

(Contd. on page 13)

Revision: August 1, 2019

Trade name: Motive-Power Crystal Synthetic Penetrating Oil (Aerosol)

(Contd. of page 12)

	(Contd. or page 12)			
· Canadiar	· Canadian Ingredient Disclosure list (limit 1%)			
142-82-5	heptane			
124-38-9	carbon dioxide			

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 03/11/2015 / 06/18/2015

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Press. Gas: Gases under pressure: Liquefied gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· Sources

SDS Prepared by:

Environmental Protection Department