

## Safety Data Sheet

Printing date 08/20/2021

Revised On 08/20/2021

## 1 Identification of the substance and manufacturer

**Trade name:** DARK SHIELD  
**Product code:** 80-1225  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.  
**Manufacturer/Supplier:** Kimball Midwest  
 4800 Roberts Road  
 Columbus, OH 43228  
 800-233-1294  
 www.kimballmidwest.com  
**Emergency telephone number:** ChemTrec: 800-424-9300

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 Carc. 1B H350 May cause cancer.  
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.  
 STOT SE 3 H336 May cause drowsiness or dizziness.  
 STOT RE 2 H373 May cause damage to the central nervous system and the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

## Additional information:

## GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

## Signal word

## Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause cancer.  
 Suspected of damaging fertility or the unborn child.  
 May cause drowsiness or dizziness.  
 May cause damage to the central nervous system and the lung through prolonged or repeated exposure. Route of exposure: Inhalation.  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 Take off contaminated clothing and wash it before reuse.  
 If eye irritation persists: Get medical advice/attention.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## Precautionary statements

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

74-98-6	propane	15-25%
67-64-1	Acetone	10-15%
8052-41-3	Stoddard Solvent	10-15%
106-97-8	n-butane	5-10%
110-19-0	Isobutyl Acetate	5-10%
110-54-3	hexane	≥5-<10%
108-65-6	PM acetate	1-5%
1330-20-7	xylene (mix)	1-5%

(Contd. on page 2)

## Safety Data Sheet

Printing date 08/20/2021

Revised On 08/20/2021

Trade name: DARK SHIELD

(Contd. of page 1)

14807-96-6	Talc	1-5%
1333-86-4	Carbon black	1-5%

**4 First-aid measures**

<b>After inhalation:</b>	Supply fresh air; consult doctor in case of complaints.
<b>After skin contact:</b>	Remove contaminated clothing. Wash exposed area with soap and water.
<b>After eye contact:</b>	Rinse opened eye for several minutes under running water. Then consult a doctor.
<b>After swallowing:</b>	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
<b>Most important symptoms and effects:</b>	Dizziness
<b>Indication of any immediate medical attention needed:</b>	No further relevant information available.

**5 Fire-fighting measures**

<b>Extinguishing agents:</b>	CO2, extinguishing powder or water spray. Fight larger fires with water spray.
<b>Special hazards:</b>	Can form explosive gas-air mixtures.
<b>Protective equipment for firefighters:</b>	A respiratory protective device may be necessary.

**6 Accidental release measures**

<b>Personal precautions, protective equipment and emergency procedures:</b>	Use respiratory protective device against the effects of fumes/dust/aerosol.
<b>Methods and material for containment and cleaning up:</b>	Dispose contaminated material as waste according to section 13.

**7 Handling and storage**

<b>Precautions for safe handling</b>	Use only in well ventilated areas.
<b>Storage requirements:</b>	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****74-98-6 propane**

PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV (USA)	refer to Appendix F in TLVs&BEIs book; D, EX

**67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm BEI

**8052-41-3 Stoddard Solvent**

PEL (USA)	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min
TLV (USA)	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm

**106-97-8 n-butane**

REL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm (EX)

**110-19-0 Isobutyl Acetate**

PEL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
TLV (USA)	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

**110-54-3 hexane**

PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 180 mg/m <sup>3</sup> , 50 ppm

(Contd. on page 3)

## Safety Data Sheet

Printing date 08/20/2021

Revised On 08/20/2021

Trade name: DARK SHIELD

(Contd. of page 2)

TLV (USA)	Long-term value: 176 mg/m <sup>3</sup> , 50 ppm Skin; BEI
<b>108-65-6 PM acetate</b>	
WEEL (USA)	Long-term value: 50 ppm
<b>1330-20-7 xylene (mix)</b>	
PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
<b>9006-04-6 Rubber</b>	
TLV (USA)	Long-term value: 0.0001* mg/m <sup>3</sup> Skin; DSEN, RSEN,* inh. fraction
<b>1333-86-4 Carbon black</b>	
PEL (USA)	Long-term value: 3.5 mg/m <sup>3</sup>
REL (USA)	Long-term value: 3.5* mg/m <sup>3</sup> *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m <sup>3</sup> *inhalable fraction

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

**110-54-3 hexane**

BEI (USA)	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2.5-Hexanedione without hydrolysis
-----------	---

**1330-20-7 xylene (mix)**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

**Hygienic protection:**

Wash hands after use.  
Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.  
The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties**

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octanol/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.

(Contd. on page 4)

## Safety Data Sheet

Printing date 08/20/2021

Revised On 08/20/2021

Trade name: DARK SHIELD

Water: 0.0 %

(Contd. of page 3)

## 10 Stability and reactivity

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

## LD/LC50 values that are relevant for classification:

## 110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rbt)

## 108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

## 1330-20-7 xylene (mix)

Oral LD50 8,700 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rbt)

Inhalative LC50/4 h 6,350 mg/l (rat)

## 1333-86-4 Carbon black

Oral LD50 10,000 mg/kg (rat)

**Information on toxicological effects:** No data available.  
**Skin effects:** No irritant effect.  
**Eye effects:** No irritating effect.  
**Sensitization:** No sensitizing effects known.

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Remark:** Harmful to fish  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

**UN-Number** UN1950  
**DOT** UN1950  
**DOT** Aerosols, flammable  
**ADR** 1950 Aerosols  
**Transport hazard class(es):**  
**Class** 2.1  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Packaging Group:** --  
**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

## SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

## SARA Section 313 (Specific toxic chemical listings):

110-54-3 hexane

1330-20-7 xylene (mix)

(Contd. on page 5)

# Safety Data Sheet

Printing date 08/20/2021

Revised On 08/20/2021

Trade name: DARK SHIELD

(Contd. of page 4)

**Toxic Substances Control Act****(TSCA):**

All hazardous ingredients are found on the inventory list of substances.

**Canadian Domestic Substances List****(DSL):**

All ingredients are listed or exempted.

**Consumer Product Safety****Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

1333-86-4 Carbon black

100-41-4 ethyl benzene

**Prop 65 chemicals known to cause birth defects or reproductive harm:**

110-54-3 hexane

**EPA:**

67-64-1 Acetone

110-19-0 Isobutyl Acetate

110-54-3 hexane

1330-20-7 xylene (mix)

I

D

II

I

**16 Other information****Contact:**

Regulatory Affairs