# alpha

Safety Data Sheet

# Safety Data Sheet

# Section 1. Identification

Product name : Solder Wire Cored 96.5Sn/4Cu/0.5Ag Alloy, AC94 Flux

: May 15 2015.

Product code : M478AC94
Product type : Solid.

revision

Date of issue/Date of

Manufacturer - Supplier	Telephone no.:	Fax no.	Emergency phone:
ALPHA Global Headquarters 300 Atrium Drive Somerset, New Jersey 08873	Toll Free: (800) 367-5460 Main Phone: (908) 791-3000	(908) 791-3090	UNITED STATES AND CANADA Tel: 800-424-9300 INTERNATIONAL, CALL Tel: +1 703-527-3887 (collect calls accepted) Alpha Chemtrec #5591
ALPHA METALS MEXICO SA DE CV Ave Nafta 800, Parque Industrial STIVA Apodaca NL 66600 Mexico	Tel: +52 81 1156-6602	Fax: +52 81 1156-6655	Tel: 01 800 022 1400 Tel: +52 55 5559-1588
Alent Brasil Soldas Ltda. Rio Jaguarão, 1540 - Vila Buriti Manaus Amazonas 69072-055 Brasil	Tel: 55 92 3614-7400	Fax: 55 92 3614-7400	Tel: 55 92 3614-7423

### Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : AQUATIC HAZARD (ACUTE) - Category 1
substance or mixture : AQUATIC HAZARD (LONG-TERM) - Category 3

**GHS label elements** 

Hazard pictograms :



Signal word : Warning

**Hazard statements**: Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

General : Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

**Prevention**: Avoid release to the environment.

Response : Collect spillage.

Storage : Store in cool/well-ventilated place. Keep container tightly closed.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Alpha is an Alent plc Company Solder Wire Cored 96.5Sn/4Cu/0.5Ag Alloy, AC94 Flux

### Section 2. Hazards identification

Hazards not otherwise

: None known.

classified

Eye contact

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
tin	80-100	7440-31-5
copper	1-10	7440-50-8
Additive	1-10	-
Ammonium salt.	0.1-1.0	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open. Get medical attention if irritation occurs.

Page: 2/12

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and

keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

#### Over-exposure signs/symptoms

**Eye contact** : No specific data. Inhalation : No specific data.

Alpha is an Alent plc Company

Solder Wire Cored 96.5Sn/4Cu/0.5Ag Alloy, AC94 Flux

Page: 3/12

### Section 4. First aid measures

Skin contact : No specific data.

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: This material is very toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

### Section 6. Accidental release measures

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
tin	OSHA PEL (United States, 9/2005).
	TWA: 2 mg/m <sup>3</sup> 8 hours.
	ACGIH TLV (United States, 4/2014).
	TWA: 2 mg/m³, (as Sn) 8 hours.
	NIOSH REL (United States, 10/2013).
	TWA: 2 mg/m³, (as Sn) 10 hours.
copper	OSHA Final Rule (United States, 1989). Notes: As copper
	TWA: 1 mg/m³ 8 hours. Form:
	TWA: 0.1 mg/m³ 8 hours. Form:
	ACGIH TLV (United States, 4/2014). Notes: as Cu
	TWA: 1 mg/m³, (as Cu) 8 hours. Form: Dust and mist
	NIOSH REL (United States, 10/2013). Notes: Note: The REL and
	PEL also apply to other copper compounds (as Cu) except
	Copper fumes.
	TWA: 1 mg/m³, (as Cu) 10 hours. Form: Dusts and Mists
	OSHA PEL (United States, 2/2013).
	TWA: 1 mg/m <sup>3</sup> 8 hours. Form: Dusts and Mists
	TWA: 0.1 mg/m³ 8 hours. Form: Fume
	ACGIH TLV (United States, 4/2014). Notes: Substances for which
	the TLV is higher than the OSHA Permissible Exposure Limit
	(PEL) and/or the NIOSH Recommended Exposure Limit (REL).
	See CFR 58(124) :36338-33351, June 30, 1993, for revised OSHA
	PEL. Adopted Values enclosed are those for which changes are
	proposed. Consult the Notice of Intended Changes for current
	proposal. See Notice of Intended changes.
	TWA: 0.2 mg/m³ 8 hours. Form: Fume

### Section 8. Exposure controls/personal protection

Additive

AIHA WEEL (United States, 10/2011).

TWA: 10 mg/m³ 8 hours.

ACGIH TLV (United States, 4/2014).

STEL: 20 mg/m³ 15 minutes. Form: Fume
TWA: 10 mg/m³ 8 hours. Form: Fume
NIOSH REL (United States, 10/2013).

STEL: 20 mg/m³ 15 minutes. Form: Fume
TWA: 10 mg/m³ 10 hours. Form: Fume

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures**: Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless

the assessment indicates a higher degree of protection: safety glasses with side-

shields.

**Skin protection** 

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

**Body protection**: Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protection : Use a properly fitted, particulate filter respirator complying with an approved standard if

a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working

limits of the selected respirator.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state : Solid.
Color : Gray.
Odor : None.

Odor threshold : Not available.

pH : Not available.

Melting point : Not available.

Boiling point : Not available.

# Section 9. Physical and chemical properties

Flash point : Not available. **Evaporation rate** : Not available. Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available. Vapor density : Not available. Relative density : Not available.

**Solubility** : Insoluble in the following materials: cold water and hot water.

VOC Partition coefficient: noctanol/water

: Not available.

: 21.3 g/l

**Auto-ignition temperature Decomposition temperature** 

: Not available. : Not available. : Not available.

# Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Incompatibility with various** 

substances

: Reactive or incompatible with the following materials: oxidizing materials, reducing

materials, metals, acids, alkalis and moisture. Chlorine, peroxides

Hazardous decomposition

products

**Viscosity** 

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

**Other Hazardous** 

decomposition products

: metal oxides, toxic. fumes

**Hazardous polymerization** 

: Under normal conditions of storage and use, hazardous polymerization will not occur.

# Section 11. Toxicological information

: Dermal contact. Eye contact. Inhalation. Ingestion. **Routes of entry** 

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
tin	LD50 Oral	Rat	>2000 mg/kg	-
copper	LC50 Inhalation Dusts and mists	Rat	5.11 mg/l	4 hours
Additive	LD50 Oral	Mouse	11 g/kg	-
	LD50 Oral	Rat	8471 mg/kg	-
	LDLo Oral	Rabbit	10 g/kg	-
Ammonium salt.	LD50 Oral	Rat	1650 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Additive	Skin - Mild irritant	Human	-	72 hours 22 milligrams Intermittent	-
	Skin - Moderate irritant	Human	-	24 hours 20 Percent	-
Ammonium salt.	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100	-

Alpha is an Alent plc Company

Solder Wire Cored 96.5Sn/4Cu/0.5Ag Alloy, AC94 Flux

Page: 7/12

# **Section 11. Toxicological information**

milligrams

#### **Sensitization**

Not available.

#### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
Additive	-	Experiment: In vitro Subject: Mammalian-Human Cell: Germ	Positive

#### Carcinogenicity

No applicable toxicity data

#### **Additional information:**

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

General : No known significant effects or critical hazards.

# Section 11. Toxicological information

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

# Numerical measures of toxicity Acute toxicity estimates

Not available.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
copper	Acute EC50 1100 μg/l Fresh water Acute EC50 2.1 μg/l Fresh water	Aquatic plants - Lemna minor Daphnia - Daphnia longispina - Juvenile (Fledgling, Hatchling, Weanling)	4 days 48 hours
	Acute IC50 13 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute IC50 5.4 mg/l Marine water	Aquatic plants - Plantae - Exponential growth phase	72 hours
	Acute LC50 0.072 μg/l Marine water Acute LC50 7.56 μg/l Marine water	Crustaceans - Amphipoda - Adult Fish - Periophthalmus waltoni - Adult	48 hours 96 hours
	Chronic NOEC 2.5 µg/l Marine water	Algae - Nitzschia closterium - Exponential growth phase	72 hours
	Chronic NOEC 7 mg/l Fresh water	Aquatic plants - Ceratophyllum demersum	3 days
	Chronic NOEC 0.02 mg/l Fresh water	Crustaceans - Cambarus bartonii - Mature	21 days
	Chronic NOEC 2 μg/l Fresh water Chronic NOEC 0.8 μg/l Fresh water	Daphnia - Daphnia magna Fish - Oreochromis niloticus - Juvenile (Fledgling, Hatchling, Weanling)	21 days 6 weeks
Additive	Acute EC50 6573.1 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute EC50 3910000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 22.5 ppt Fresh water	Fish - Oreochromis mossambicus - Young	96 hours
Ammonium salt.	Chronic NOEC 2 g/L Fresh water Acute EC50 0.07 mg/l Marine water	Fish - Heteropneustes fossilis Algae - Hormosira banksii - Gamete	30 days 72 hours
	Acute EC50 0.1 mg/l Fresh water Acute LC50 390 μg/l Fresh water	Crustaceans - Cypris subglobosa Daphnia - Daphnia magna - Young	48 hours 48 hours
	Acute LC50 80 µg/l Fresh water Chronic NOEC 0.6 mg/l Marine water	Fish - Oncorhynchus mykiss Algae - Entomoneis punctulata - Exponential growth phase	96 hours 72 hours
	Chronic NOEC 330 μg/l Fresh water	Crustaceans - Crangonyx sp Juvenile (Fledgling, Hatchling, Weanling)	21 days
	Chronic NOEC 19.66 mg/l Fresh water Chronic NOEC 0.006 mg/l Fresh water	Daphnia - Daphnia magna Fish - Ictalurus punctatus - Fry	21 days 30 days

#### Persistence and degradability

Not available.

# **Section 12. Ecological information**

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Additive	<-1.73	-	low
Ammonium salt.	-3.2	-	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	<u> </u>					
	DOT Classification	TDG Classification	Mexico Classification	UN	IMDG	IATA
UN number	Not regulated.	UN3077	UN3077	UN3077	UN3077	UN3077
UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.				
Transport hazard class(es)	-	9	9	9	9	9
Packing group	-	-	-	-	-	-
Environmental hazards	No.	Yes.	Yes.	Yes.	Yes.	Yes.

Additional information - TDG Classification	The product is not regulated as a dangerous good when transported by road or rail.

Alpha is an Aler	nt plc Company	Solder Wire Cored 96.5Sn/4Cu/0.5Ag Alloy, AC94 Flux	Page: 10/12
Section 14	. Transport ir	nformation	
Additional information - Mexico Classification	The environmentally ≤5 kg.	/ hazardous substance mark is not required when transported in siz	es of ≤5 L or
Additional information - UN Classification	The environmentally ≤5 kg.	/ hazardous substance mark is not required when transported in siz	es of ≤5 L or
Additional information - IMDG Classification	The marine pollutan	t mark is not required when transported in sizes of ≤5 L or ≤5 kg.	
Additional information - IATA Classification	The environmentally ≤5 kg.	/ hazardous substance mark is not required when transported in siz	es of ≤5 L or

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 proposed significant new use rule (SNUR): No products were found.

TSCA 5(a)2 final significant new use rules: Aliphatic alcohol. TSCA 12(b) one-time export notification: No products were found. TSCA 12(b) annual export notification: No products were found.

**United States inventory** 

(TSCA 8b)

: All components are listed or exempted.

#### **SARA 302/304**

#### Composition/information on ingredients

No products were found.

#### **SARA 311/312**

Classification : Not applicable.

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	copper	7440-50-8	1-10
Supplier notification	copper	7440-50-8	1-10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### California Prop. 65

**WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer. WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

#### Canada

WHMIS (Canada) : Not controlled under WHMIS (Canada). **Canada inventory** : All components are listed or exempted.

#### Page: 11/12

# **Section 15. Regulatory information**

#### **International lists**

**National inventory** 

Australia : All components are listed or exempted. China : All components are listed or exempted. **Europe** : All components are listed or exempted. **Japan** : All components are listed or exempted. **New Zealand** : All components are listed or exempted. **Philippines** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. : All components are listed or exempted. **Taiwan** 

### Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**



#### Procedure used to derive the classification

Classification	Justification
, , , , , , , , , , , , , , , , , , , ,	Calculation method Calculation method

#### **History**

Date of issue/Date of

revision

: May 15 2015.

Date of previous issue

: No previous validation.

Version

: 1

Prepared by

: Regulatory Affairs Department

**Enthone Inc** 

350 Frontage Road West Haven, CT 06516 Phone: (203) 934-8611 Fax: (203) 799-8179

enthonemsds@enthone.com

www.enthone.com

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

#### Page: 12/12

### Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.5b3271

Alpha SDS GHS Americas

