

The following SDS references the product below:

Vulcanizing Cement

Vendor Item Number: 14-513 8oz Activator Cement

Manufactured By:

31 Incorporated

Distributed by Kimball Midwest with the KM product-
identification number:

52-237

KIMBALL MIDWEST

Specializing in Materials Management

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Vulcanizing Cement
- **Article number:** 14-513, 14-514
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Rubber compounding
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
31 Incorporated
100 Enterprise Dr.
Newcomerstown, OH 43832
Phone: (740) 498-8324
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.



health hazard

Muta. 2	H341 Suspected of causing genetic defects.
Carc. 1B	H350 May cause cancer.



Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H336 May cause drowsiness or dizziness.

Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.
-------------------	---------------------------------------------------------

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R45:	May cause cancer.
------	-------------------



Xn; Harmful

R68:	Possible risk of irreversible effects.
------	----------------------------------------

(Contd. on page 2)

Safety Data Sheet


according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 1)

 Xi; Irritant

R36/38: Irritating to eyes and skin.

 Xi; Sensitising

R43: May cause sensitisation by skin contact.

R52/53-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

• **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

• **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

• **Hazard pictograms**



GHS07 GHS08

• **Signal word** Danger

• **Hazard-determining components of labelling:**

trichloroethylene

Natural rubber latex

• **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

• **Precautionary statements**

P281 Use personal protective equipment as required.

P264 Wash thoroughly after handling.

P261 Avoid breathing mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 2)

P302+P352

IF ON SKIN: Wash with plenty of water.

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Restricted to professional users.

- **Hazard description:**

- **WHMIS-symbols:**

D1B - Toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects



- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 0

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *2

Fire = 0

Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

- **HMIS Long Term Health Hazard Substances**

79-01-6 | trichloroethylene

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.• **vPvB:** Not applicable.

3 Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 79-01-6 EINECS: 201-167-4 Index number: 602-027-00-9	trichloroethylene T Carc. Cat. 2 R45; Xn R68; Xi R36/38 R52/53-67 Muta. Cat. 3 Muta. 2, H341; Carc. 1B, H350 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H336 Aquatic Chronic 3, H412	>70%
-----------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 3)

CAS: 9006-04-6

Natural rubber latex

10-25%

 Xi R43 Skin Sens. 1B, H317• **SVHC**

79-01-6 | trichloroethylene

• **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

• **4.1 Description of first aid measures**• **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

• **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

• **After skin contact:**

Do not pull solidified product off the skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

• **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

• **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Dizziness

Coughing

Allergic reactions

Irritant to skin and mucous membranes.

Irritant to eyes.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Disorientation

• **Hazards**

Danger of disturbed cardiac rhythm.

Danger of impaired breathing.

Vapours may cause drowsiness and dizziness.

Carcinogenic.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 4)

- May be harmful if inhaled.
- Repeated exposure may cause skin dryness or cracking.
- Danger of serious damage to health by prolonged exposure.
- **4.3 Indication of any immediate medical attention and special treatment needed**
- May produce a hepatotoxic effect.
- If necessary oxygen respiration treatment.
- Vapours may cause drowsiness and dizziness.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **5.2 Special hazards arising from the substance or mixture**
- During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:**
- Wear self-contained respiratory protective device.
- Wear fully protective suit.
- **Additional information** Evacuate area and fight fire from from the upwind side.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
- Use respiratory protective device against the effects of fumes/dust/aerosol.
- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- Keep people at a distance and stay on the windward side.
- **6.2 Environmental precautions:**
- Do not allow to enter sewers/ surface or ground water.
- Prevent from spreading (e.g. by damming-in or oil barriers).
- Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Pick up mechanically.
- Send for recovery or disposal in suitable receptacles.
- Dispose contaminated material as waste according to item 13.
- Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 5)

7 Handling and storage

7.1 Precautions for safe handling

- Prevent formation of aerosols.
- Avoid splashes or spray in enclosed areas.
- Use only in well ventilated areas.
- Take note of emission threshold.

Information about fire - and explosion protection: Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

- Avoid storage near extreme heat, ignition sources or open flame.
- Store only in the original receptacle.

Information about storage in one common storage facility:

- Store away from foodstuffs.
- Store away from flammable substances.
- Store away from oxidizing agents.
- Do not store together with acids.

Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

79-01-6 trichloroethylene

PEL (USA)	Long-term value: 100 ppm Ceiling limit: 200; 300* ppm *5-min peak in any 2 hrs
REL (USA)	See Pocket Guide Apps. A and C
TLV (USA)	Short-term value: 135 mg/m ³ , 25 ppm Long-term value: 54 mg/m ³ , 10 ppm BEI
EL (Canada)	Short-term value: 25 ppm Long-term value: 10 ppm ACGIH A2, IARC 2A
EV (Canada)	Short-term value: 25 ppm Long-term value: 10 ppm

1330-20-7 xylene

IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
------------	--------------------------------------------------------------------------------------------------------------

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 6)

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

• **Ingredients with biological limit values:**

79-01-6 trichloroethylene

BEI (USA)	15 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Trichloroacetic acid (nonspecific)
	0,5 mg/L Medium: blood Time: end of shift at end of workweek Parameter: Trichloroethanol without hydrolysis (nonspecific)
	- Medium: blood Time: end of shift at end of workweek Parameter: Trichloroethylene (semi-quantitative)
	- Medium: end-exhaled air Time: end of shift at end of workweek Parameter: Trichloroethylene (semi-quantitative)

1330-20-7 xylene

BEI (USA)	1,5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	----------------------------------------------------------------------------------------------

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Pregnant women should strictly avoid inhalation or skin contact.
Immediately remove all soiled and contaminated clothing.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 7)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Shower or take a bath at the end of work.

• **Respiratory protection:**

Not required under normal conditions of use.

Use suitable respiratory protective device when high concentrations are present.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

• **Material of gloves**

PVA gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Safety glasses

• **Body protection:** Solvent resistant protective clothing

• **Limitation and supervision of exposure into the environment**

No further relevant information available.

• **Risk management measures**

Organizational measures should be in place for all activities involving this product.

See Section 7 for additional information.

No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 8)

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Colour:	Cloudy
Odour:	Sweetish
Odour threshold:	Not determined.
pH-value:	Not determined.

· Change in condition

Melting point/Melting range:	Not Determined.
Boiling point/Boiling range:	189 ° F / 87 °C

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Auto/Self-ignition temperature: 770 ° F / 410 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not self-igniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	8,0 Vol %
Upper:	10,5 Vol %

· Vapour pressure at 20 °C: 77 hPa

· Density at 20 °C: 1,45 g/cm³

· Relative density: Not determined.

· Vapour density at 20 °C: 4,54 g/cm³ (air = 1)

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· 9.2 Other information: No further relevant information available.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 9)

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with strong acids and oxidizing agents.
Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid** Store away from oxidizing agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Chlorine compounds
Chlorine

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

79-01-6 trichloroethylene

Oral	LD50	2402 mg/kg (mouse)
Dermal	LD50	8450 mg/kg (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant
Carcinogenic.
Suspected of causing genetic defects.
May cause cancer.
- **Acute effects (acute toxicity, irritation and corrosivity):**
May be harmful if inhaled.
Carcinogenic.
Danger through skin adsorption.
- **Sensitisation:** Sensitization possible by skin contact.
- **Repeated dose toxicity:**
Repeated exposure may cause skin dryness or cracking.
May cause damage to organs through prolonged or repeated exposure.
Repeated exposures may result in skin and/or respiratory sensitivity.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 10)

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
Muta. 2, Carc. 1B

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The material is harmful to the environment.
- **12.2 Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **12.3 Bioaccumulative potential** May be accumulated in organism
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Harmful to aquatic organisms
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1710
- **14.2 UN proper shipping name**
- **DOT** Trichloroethylene

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 11)

- ADR
- IMDG, IATA
- 14.3 Transport hazard class(es)
- DOT

1710 TRICHLOROETHYLENE
TRICHLOROETHYLENE



- Class
- Label

6.1 Toxic substances.
6.1

- ADR



- Class
- Label

6.1 (T1) Toxic substances.
6.1

- IMDG, IATA



- Class
- Label
- 14.4 Packing group
- DOT, ADR, IMDG, IATA
- 14.5 Environmental hazards:
- Marine pollutant:
- 14.6 Special precautions for user
- Danger code (Kemler):
- EMS Number:
- Segregation groups
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
- Transport/Additional information:

6.1 Toxic substances.
6.1
III
No
Warning: Toxic substances.
60
F-A, S-A
Liquid halogenated hydrocarbons
Not applicable.

- ADR
- Limited quantities (LQ)
- Transport category
- Tunnel restriction code
- UN "Model Regulation":

5L
2
E
UN1710, TRICHLOROETHYLENE, 6.1, III

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 12)

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

79-01-6 | trichloroethylene

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

79-01-6 | trichloroethylene

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

79-01-6 | trichloroethylene

CaH

- **IARC (International Agency for Research on Cancer)**

79-01-6 | trichloroethylene

2A

- **TLV (Threshold Limit Value established by ACGIH)**

79-01-6 | trichloroethylene

A2

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

79-01-6 | trichloroethylene

- **Canada**

- **Canadian Domestic Substances List (DSL)**

Not all ingredients listed.

- **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

- **Canadian Ingredient Disclosure list (limit 1%)**

79-01-6 | trichloroethylene

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

(Contd. of page 13)

• **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

• **Substances of very high concern (SVHC) according to REACH, Article 57**

79-01-6	trichloroethylene
---------	-------------------

• **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Relevant phrases**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H412 Harmful to aquatic life with long lasting effects.

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R45 May cause cancer.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

R68 Possible risk of irreversible effects.

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B

Muta. 2: Germ cell mutagenicity, Hazard Category 2

Carc. 1B: Carcinogenicity, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

(Contd. on page 15)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 25.06.2014

Revision: 25.06.2014

Trade name: Vulcanizing Cement

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

(Contd. of page 14)

· Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com