The following SDS references the products below:

**PRO-MAX Liquid Paint Marker** 

<u>Vendor Item Number: WHITE, YELLOW, RED, BLACK ORANGE, BLUE, PURPLE, GREY</u>

Manufactured By:

LA-CO Industries, Inc.

Distributed by Kimball Midwest with the KM productidentification number:

*83-780, 83-781, 83-782, 83-783, 83-784, 83-785* 



according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

Date of issue: 07/29/2015

LA-CO Industries, Inc.

Version: 1.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article

Trade name : PRO-LINE® Fine Line PAINT MARKER Blue, Green, Light Green, Orange, Red, Yellow; PRO-

LINE® Microline PAINT MARKER Red, Yellow; PRO-MAX™ PAINT MARKER Blue, Brown,

Gray, Orange, Pink, Purple, Red, Yellow, Silver

Synonyms : PRO-LINE® Fine Line PAINT MARKER Blue, Green, Light Green, Orange, Red, Yellow

PRO-LINE® Microline PAINT MARKER Red, Yellow

PRO-MAX™ PAINT MARKER Blue, Brown, Gray, Orange, Pink, Purple, Red, Yellow, Silver

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking.

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc. 1201 Pratt Boulevard Elk Grove Village, IL. 60007-5746 Phone: (847) 956-7600 Fax: (847) 956-9885

E-mail: customer\_service@laco.com

1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Not classified

#### 2.2 Label elements

#### **GHS-US** labelling

No labelling applicable

#### 2.3. Other hazards

No additional information available

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
1-Methoxy-2-propanol	(CAS No) 107-98-2	50 – 90	Flam. Liq. 3, H226 STOT SE 3, H336
aluminium powder (stabilised)	(CAS No) 7429-90-5	10 – 25 Silver	Flam. Sol. 1, H228 Water-react. 2, H261

Full text of H-statements: see section 16

29/07/2015 EN (English) SDS Ref.: LACO1507043 1/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you

feel unwell

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.

First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry chemical. Inert gas. Foam. Water spray. Water fog.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

Reactivity : No dangerous reactions known.

#### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter

drains or water courses. Eliminate all ignition sources if safe to do so.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use

self-contained breathing apparatus.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No

smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.

Emergency procedures : Stop leak if safe to do so. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Eliminate all ignition sources. Stop the flow of material, if this is without risk.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take

up in non-combustible absorbent material and shove into container for disposal.

#### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

29/07/2015 EN (English) SDS Ref.: LACO1507043 2/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling

: No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist. Use

only outdoors or in a well-ventilated area.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Incompatible products

 $: \ \, \hbox{Proper grounding procedures to avoid static electricity should be followed. Ground/bond}$ 

container and receiving equipment. Use only non-sparking tools.

Storage conditions : Keep container tightly closed. Keep away from open flames, hot surfaces and sources of

: Strong oxidizers.

Incompatible materials

: Heat sources.

Heat and ignition sources
Prohibitions on mixed storage

Keep away from heat, sparks and flame.Keep away from incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

#### 7.3. Specific end use(s)

Marking.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

PRO-LINE® Fine Line PAINT MARKER Blue, Green, Light Green, Orange, Red, Yellow; PRO-LINE® Microline PAINT MARKER Red, Yellow; PRO-MAX™ PAINT MARKER Blue, Brown, Gray, Orange, Pink, Purple, Red, Yellow, Silver			
ACGIH	Not applicable	Not applicable	
OSHA	Not applicable	Not applicable	
1-Methoxy-2-propanol (	107-98-2)		
ACGIH	ACGIH TWA (mg/m³)	369 mg/m³	
ACGIH	ACGIH TWA (ppm)	50 ppm	
ACGIH	ACGIH STEL (mg/m³)	553 mg/m³	
ACGIH	ACGIH STEL (ppm)	100 ppm	
ACGIH	Remark (ACGIH)	Eye irr; CNS impair; A4	
OSHA	Not applicable		
Canada (Quebec)	VECD (mg/m³)	553 mg/m³	
Canada (Quebec)	VECD (ppm)	150 ppm	
Canada (Quebec)	VEMP (mg/m³)	369 mg/m³	
Canada (Quebec)	VEMP (ppm)	100 ppm	
aluminium powder (stal	bilised) (7429-90-5)		
ACGIH	ACGIH TWA (mg/m³)	1 mg/m³	
ACGIH	Remark (ACGIH)	Pneumoconiosis; LRT irr	
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable dust)	
Canada (Quebec)	VEMP (mg/m³)	10 mg/m³	
Canada (Quebec)	Notations and remarks	(Métal)	

#### 8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust ventilation of closed transfer systems to minimize exposures.

Personal protective equipment : Avoid all unnecessary exposure.

29/07/2015 EN (English) SDS Ref.: LACO1507043 3/8

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

Hand protection : None under normal use. It is a good industrial hygiene practice to minimize skin contact. Wear

suitable gloves. rubber.

: No data available

: No data available

Eye protection : Eye protection should only be necessary where liquid could be splashed or sprayed. Respiratory protection

: In case of inadequate ventilation wear respiratory protection. Use an approved respirator

equipped with oil/mist cartridges.

Other information : Do not eat, drink or smoke when using this product.

#### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Physical state : Liquid

**Appearance** : Solid marker containing liquid colored paint.

Colour Ether Odour

Odour threshold : No data available рΗ : No data available Relative evaporation rate (butyl acetate=1) : No data available : No data available Melting point Freezing point : No data available

: 120 °C Boiling point Flash point : 31 °C : > 250 °C Auto-ignition temperature

Flammability (solid, gas) : No data available : 12 mbar @ 20 °C Vapour pressure Relative vapour density at 20 °C : No data available Relative density : No data available : 0.9 - 1.3 g/cm3 @ 20 °C Density Solubility : No data available Log Pow : No data available Log Kow : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidising properties : No data available

Other information 9.2.

Decomposition temperature

VOC content : < 82 %

### **SECTION 10: Stability and reactivity**

#### Reactivity

**Explosive limits** 

No dangerous reactions known.

#### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

#### Incompatible materials

Strong oxidizing agents.

#### Hazardous decomposition products

May release flammable gases.

29/07/2015 EN (English) SDS Ref.: LACO1507043 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

1-Methoxy-2-propanol (107-98-2)	
LD50 oral rat	4016 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 inhalation rat (ppm)	> 7000 ppm 6 hr
ATE CLP (oral)	4016.000 mg/kg bodyweight
aluminium powder (stabilised) (7429-90-5)	

aluminium powder (stabilised) (7429-90-5)	
LD50 oral rat	> 15900 mg/kg
LC50 inhalation rat (mg/l)	> 2.3 mg/l/4h No mortality observed in this study.

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure)

Specific target organ toxicity (repeated

exposure)

: Not classified

37.2 mg/l

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

NOEC (acute)

1-Methoxy-2-propanol (107-98-2)	
LC50 fish 1	20800 mg/l
EC50 Daphnia 1	23300 mg/l
ErC50 (algae)	> 1000 mg/l
aluminium powder (stabilised) (7429-90-5)	
LC50 fish 1	> 218.64 mg/l ASTM 2000; test material: aluminium chloride hexahydrate; Pimephales promelas
EC50 Daphnia 1	1.4 mg/l OECD Guideline 202; test material: Aluminium hydroxide
LOEC (acute)	72.89 mg/l

#### 12.2. Persistence and degradability

1-Methoxy-2-propanol (107-98-2)	
Persistence and degradability	Readily biodegradable.
Biodegradation	96 % 28 d

#### 12.3. Bioaccumulative potential

1-Methoxy-2-propanol (107-98-2)	
Bioaccumulative potential	Not expected to bioaccumulate.

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

29/07/2015 EN (English) SDS Ref.: LACO1507043 5/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment.

#### **SECTION 14: Transport information**

In accordance with DOT and TDG

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid

filler, and liquid lacquer base), 3, III

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and

liquid lacquer base

Transport hazard class(es) (DOT) : 3 - Flammable liquid Packing group (DOT) : III - Minor Danger

**ADR** 

Transport document description : UN 1263 PAINT, 3, III, (D/E)

Proper Shipping Name (ADR) : PAINT Packing group (ADR) : III

Class (ADR) : 3 - Flammable liquid

Transport by sea

UN-No. (IMDG) : UN 1263
Proper Shipping Name (IMDG) : PAINT

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III

Air transport

UN-No. (IATA) : UN 1263
Proper Shipping Name (IATA) : Paint

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : III

#### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

#### 1-Methoxy-2-propanol (107-98-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### aluminium powder (stabilised) (7429-90-5)

Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

#### CANADA

#### 1-Methoxy-2-propanol (107-98-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### aluminium powder (stabilised) (7429-90-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### **EU-Regulations**

#### 1-Methoxy-2-propanol (107-98-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

29/07/2015 EN (English) SDS Ref.: LACO1507043 6/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

#### aluminium powder (stabilised) (7429-90-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### National regulations

PRO-LINE® Fine Line PAINT MARKER Blue, Green, Light Green, Orange, Red, Yellow; PRO-LINE® Microline PAINT MARKER Red, Yellow; PRO-MAX™ PAINT MARKER Blue, Brown, Gray, Orange, Pink, Purple, Red, Yellow, Silver

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

All ingredients are listed in the Toxic Substances Control Act (TSCA).

#### 15.3. US State regulations

#### 1-Methoxy-2-propanol (107-98-2)

U.S. - Minnesota - Hazardous Substance List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New York - Right to Know List of Hazardous Chemicals

#### aluminium powder (stabilised) (7429-90-5)

U.S. - Minnesota - Hazardous Substance List

U.S. - New York - Right to Know List of Hazardous Chemicals

U.S. - New Jersey - Right to Know Hazardous Substance List

#### **SECTION 16: Other information**

Indication of changes

: Original Document.

Data sources

: ACGIH (American Conference of Government Industrial Hygienists).

European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <a href="http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database">http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database</a>.

Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing",

Fifth Edition.

National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th

edition.

OSHA 29CFR 1910.1200 Hazard Communication Standard.

TSCA Chemical Substance Inventory. Accessed at

http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html.

Abbreviations and acronyms

: ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number.

CLP: Classification, Labelling, Packaging.

EC50: Environmental Concentration associated with a response by 50% of the test population.

GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).

LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration.

PBT: Persistent, Bioaccumulative, Toxic.

TWA: Time Weight Average.

TSCA: Toxic Substances Control Act.

Other information

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

: None.

injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and not reactive with water.



#### Full text of H-statements:

Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3,
	Narcosis

29/07/2015 EN (English) SDS Ref.: LACO1507043 7/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations according to Canadian Hazardous Products Regulations (HPR)

Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H226	Flammable liquid and vapour
H228	Flammable solid
H261	In contact with water releases flammable gases
H336	May cause drowsiness or dizziness

SDS Prepared by: The Redstone Group, LLC

6077 Frantz Rd. Suite 206 Dublin, OH USA 43016 T 614-923-7472 www.redstonegrp.com

#### LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

29/07/2015 EN (English) SDS Ref.: LACO1507043 8/8