SAFETY DATA SHEET

1. Identification

Product identifier: HIGH-GLOSS EXTERIOR TRIM COATING - 80-1194

Other means of identification SDS number: RE1000025772

Recommended restrictions Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Company Name:	KIMBALL MIDWEST
Address:	4800 ROBERTS RD
	COLUMBUS, OH 43228
Telephone:	1-800-233-1294

Emergency telephone number: 1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Physical Hazards	
Flammable aerosol	Category 1
Gases under pressure	Liquefied gas
Health Hazards	
Skin Corrosion/Irritation	Category 2
Toxic to reproduction	Category 2
Specific Target Organ Toxicity - Single Exposure	Category 3 ^{1.}
Specific Target Organ Toxicity - Repeated Exposure	Category 2
Aspiration Hazard	Category 1
Target Organs	
1. Narcotic effect.	
Environmental Hazards	
Acute hazards to the aquatic environment	Category 2
Chronic hazards to the aquatic	Category 2

Label Elements

Hazard Symbol:

environment



Signal Word:

Danger

Hazard Statement:	Extremely flammable aerosol. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Contains gas under pressure; may explode if heated.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well- ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid release to the environment.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Wash with plenty of water If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing. Collect spillage.
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Hexane	110-54-3	25 - <50%
Butane	106-97-8	20 - <50%
Propane	74-98-6	5 - <10%
Heptane	142-82-5	0.25 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth. Call a physician or poison control center immediately. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation:	Move to fresh air.
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.

Version: 2.0 Revision Date: 04/19/2022

utes. If easy to do,
ight fire from a can do so without
g materials.
ad the fire.
ignition and flash
luding flame oots, and in
TE all ignition ate area). Keep /e Equipment. Do wearing onnel away.
place in a container
fined areas. Stop ignition sources). Stop leak if you

7. Handling and storage	
Precautions for safe handling:	Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.
Conditions for safe storage, including any incompatibilities:	Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 3

8. Exposure controls/personal protection

Control Parameters

Chemical Identity	Туре	Exposure	Limit Values	Source
Hexane	TWA	50 ppm	180 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	PEL	500 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	REL	50 ppm	180 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (2008
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended (03 2018)
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Cyclohexane	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2008
	TWA	300 ppm	1,050 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	REL	300 ppm	1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	300 ppm	1,050 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Heptane	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	REL	85 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	400 ppm		US. ACGIH Threshold Limit Values, as amended (02 2012)
	STEL	500 ppm		US. ACGIH Threshold Limit Values, as amended (02 2012)
	Ceil_ Time	440 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
White mineral oil (petroleum) - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
White mineral oil (petroleum) - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2010)
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)

	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (02 2006)
	OSHA_ ACT	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (02 2006)
	TWA	10 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	MAX. CONC	50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (02 2006)
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
Naphthalene	STEL	15 ppm	75 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	REL	10 ppm	50 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	10 ppm	50 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	10 ppm	50 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	10 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
	STEL	15 ppm	75 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2005)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (12 2010)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End of shift.)	0.5 mg/l (Urine)	ACGIH BEL (03 2018)
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 µg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 µg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering	No data available.
Controls	

Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	No data available.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance	
Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	Estimated -104 °C
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive	e limits
Flammability limit - upper (%):	Estimated 9.5 %(V)
Flammability limit - lower (%):	Estimated 1.9 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	2,068 - 3,447 hPa (20 °C) 3,447 - 6,205 hPa (54 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.

Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix: 2,446.55 mg/kg
Dermal Product:	ATEmix: 2,446.55 mg/kg
Inhalation Product:	Not classified for acute toxicity based on available data.
Specified substance(s): Hexane	LC 50 (Rat): > 31.86 mg/l
Butane	LC 50: > 100 mg/l LC 50: > 100 mg/l

Propane	LC 50: > 100 mg/l LC 50: > 100 mg/l	
Heptane	LC 50 (Rat): > 29.29 mg/l LC 50: > 100 mg/l	
Repeated dose toxicity Product:	No data available.	
Specified substance(s): Hexane	NOAEL (Mouse(Male), Inhalation, 13 Weeks): 500 ppm(m) Inhalation Experimental result, Key study LOAEL (Mouse(Male), Inhalation, 13 Weeks): 1,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Male), Inhalation, 16 Weeks): 3,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Mouse(Female), Inhalation, 13 Weeks): 500 ppm(m) Inhalation Experimental result, Key study	
Butane	LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study	
Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study	
Heptane	NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental result, Key study	
Skin Corrosion/Irritation Product:	No data available.	
Specified substance(s): Heptane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study	
Serious Eye Damage/Eye Irritation Product: No data available. Specified substance(s):		
Hexane	Rabbit, 1 - 72 hrs: Not irritating	
Heptane	Rabbit, 24 - 72 hrs: Not irritating	
Respiratory or Skin Sensitizatio Product:	n No data available.	
Specified substance(s): Heptane	Skin sensitization:, in vivo (Guinea pig): Non sensitising	
Carcinogenicity Product:	No data available.	
IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified		
US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified		
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:		

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended: No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	No data available.	
Specified substance(s): Hexane	Suspected of damaging fertility or the unborn child.	
Specific Target Organ Toxicity - Product:	Single Exposure No data available.	
Specified substance(s): Hexane Heptane	Inhalation - vapor: Narcotic effect Category 3 with narcotic effects. Narcotic effect Category 3 with narcotic effects.	
Specific Target Organ Toxicity - Repeated Exposure Product: No data available. Specified substance(s):		
Hexane	Inhalation - vapor: Nervous System - Category 2	
Target Organs Specific Target Organ Toxicity - Single Exposure: Narcotic effect.		
Aspiration Hazard Product:	No data available.	
Specified substance(s):		
Hexane Heptane	May be fatal if swallowed and enters airways. May be fatal if swallowed and enters airways.	
Other effects:	No data available.	

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Hexane	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2.101 - 2.981 mg/l Mortality
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Aquatic Invertebrates Product:	No data available.
Specified substance(s): Hexane	EC 50 (Daphnia magna, 48 h): 21.85 mg/l QSAR QSAR, Key study LC 50 (Water flea (Daphnia magna), 24 h): > 50 mg/l Mortality
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Chronic hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Hexane	NOAEL (Oncorhynchus mykiss): 2.8 mg/I QSAR QSAR, Key study
Aquatic Invertebrates Product:	No data available.
Specified substance(s): Hexane	NOAEL (Daphnia magna): 4.888 mg/I QSAR QSAR, Key study
Toxicity to Aquatic Plants Product:	No data available.
Persistence and Degradability	
Biodegradation Product:	No data available.
Specified substance(s): Hexane	81 % Detected in water. Read-across based on grouping of substances (category approach), Key study
Butane	100 % (385.5 h) Detected in water. Experimental result, Key study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
BOD/COD Ratio Product:	No data available.
Bioaccumulative potential Bioconcentration Factor (BC Product:	F) No data available.
Specified substance(s): Hexane	Pimephales promelas, Bioconcentration Factor (BCF): 501.19 Aquatic sediment QSAR, Key study
Partition Coefficient n-octanol / w Product:	vater (log Kow) No data available.
Mobility in soil:	No data available.
-	tion to environmental compartments
Hexane Butane	No data available. No data available.
Propane	No data available.
Heptane	No data available.
Other adverse effects:	Toxic to aquatic life with long lasting effects.
13. Disposal considerations	
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws.
Contaminated Packaging:	No data available.

14. Transport information

DOT

UN Number: UN Proper Shipping Name: Transport Hazard Class(es)	UN 1950 Aerosols, flammable
Class: Label(s):	2.1 -
Packing Group: Marine Pollutant:	– No
Environmental Hazards: Marine Pollutant	No No
Special precautions for user:	Not regulated.
IMDG UN Number: UN Proper Shipping Name: Transport Hazard Class(es) Class: Label(s): EmS No.: Packing Group:	UN 1950 Aerosols, flammable 2.1 – F-D, S-U
	_
Environmental Hazards: Marine Pollutant	Yes No
Special precautions for user:	Not regulated.
IATA UN Number: Proper Shipping Name: Transport Hazard Class(es): Class: Label(s):	UN 1950 Aerosols, flammable 2.1 –
Packing Group:	_
Environmental Hazards: Marine Pollutant	Yes No
Special precautions for user: Cargo aircraft only:	Not regulated. Allowed.

The classification shown in this section may be eligible for use of an exception, such as "Limited Quantity", per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Chemical Identity	<u>OSHA hazard(s)</u>
Benzene	Flammability
	Cancer
	Aspiration
	Eye
	Blood
	Skin
	respiratory tract irritation
	Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Hexane	lbs. 5000
Butane	lbs. 100
Cyclopentane, methyl-	lbs. 100
Propane	lbs. 100
Cyclohexane	lbs. 1000
Heptane	lbs. 100
Benzene, methyl-	lbs. 1000
Benzene	lbs. 10
Naphthalene	lbs. 100
Benzene, ethyl-	lbs. 1000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Flammable (gases, aerosols, liquids, or solids) Skin Corrosion or Irritation Reproductive toxicity Specific target organ toxicity (single or repeated exposure) Aspiration Hazard

SARA 302 Extremely Hazardous Substance

Chemical IdentityReportable quantityThreshold Planning QuantityHexane

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

None present or none present in regulated quantities.

SARA 313 (TRI Reporting)

	Reporting threshold	Reporting threshold for
Chemical Identity	for other users	manufacturing and processing
Hexane	lbs	lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

US. California Proposition 65



WARNING: This product can expose you to chemicals including, Benzene which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm.

This product can expose you to chemicals including, Naphthalene Benzene, ethyl- which is [are] known to the State of California to cause cancer.

This product can expose you to chemicals including, Hexane, Benzene, methyl- which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act <u>Chemical Identity</u>

Hexane Butane Cyclopentane, methyl-Propane White mineral oil (petroleum)

US. Massachusetts RTK - Substance List

No ingredient regulated by MA Right-to-Know Law present.

US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Hexane Butane Cyclopentane, methyl-Propane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol Hexane

Tiexune

Stockholm convention Hexane

Rotterdam convention Hexane

Kyoto protocol

Inventory Status:	
Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Ontario Inventory:	On or in compliance with the inventory
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Japan (ENCS) List:	Not in compliance with the inventory.
Japan ISHL Listing:	On or in compliance with the inventory
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Mexico INSQ:	Not in compliance with the inventory.
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Philippines PICCS:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.

16.Other information, including date of preparation or last revision

Issue Date:	04/19/2022
Revision Information:	No data available.
Version #:	2.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.