Date of issue: 03/24/2025	Revised On 03/12/2025
1 Identification of the substance	and manufacturar
Trade name: Other means of identification	CR BEIGE
Product code: Article category	KB00080555
Recommended use: Uses advised against: Manufacturer/Supplier:	Paint and coatings application. Any that differs from the recommended use. Kimball Midwest 4800 Roberts Road Columbus, OH 43228 800-233-1294
Emergency telephone number:	www.kimballmidwest.com ChemTrec: 800-424-9300
2 Hazard(s) identification	
Classification of the substance or	
Aerosols 1	H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
Eye irritation 2A	H319 Causes serious eye irritation.
Carcinogenicity 2	H351 Suspected of causing cancer. Route of exposure: Inhalation.
Specific target organ toxicity (single e Specific target organ toxicity (repeate Additional information:	
GHS Hazard pictograms	
	GHS02 GHS07 GHS08
Signal word	Danger
Hazard statements	Extremely flammable aerosol. Pressurized container: may burst if heated. Causes serious eye irritation. Suspected of causing cancer. Route of exposure: Inhalation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing fume/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store in a well ventilated place. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents/container in accordance with local/regional/national/international regulations.
3 Composition/information on ing	aredients
Chemical characterization: Mixture	
Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.
Dangerous components:	
67-64-1 Acetone	25-50%
74-98-6 propane	15-25%
106-97-8 n-butane	5-10%
110-19-0 Isobutyl Acetate	5-10%
2807-30-9 Glycol Ether EP	≥5-<10%
13/63-67-7 titanium dioxide	25-410 /0 1-5%

13463-67-7 titanium dioxide 108-10-1 methyl isobutyl ketone 107-87-9 Methyl Propyl Ketone

4 First-aid measures

After inhalation: After skin contact: After eye contact:

Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 2)

1-5%

1-5%

1-5%

Safety Data Sheet

Date of issue: 03/24/2025

Revised On 03/12/2025

Trade name: CR BEIGE		
After swallowing:	(Contd. of page 1) Rinse mouth with water. Do not induce vomiting.	
Most important symptoms and effects: Indication of any immediate medical attention needed:	Dizziness	
	No further relevant information available.	
5 Fire-fighting measures		
Extinguishing agents: Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.	
Protective equipment for firefighters:	A respiratory protective device may be necessary.	
<u>_</u>		
6 Accidental release measures		
Personal precautions, protective equipment and emergency		
procedures: Methods and material for	Use respiratory protective device against the effects of fumes/dust/aerosol.	
containment and cleaning up:	Absorb liquid components with liquid-binding material.	
7 Handling and storage		
Precautions for safe handling	Use only in well ventilated areas.	
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.	
8 Exposure controls/personal prote		
Components with limit values that re 67-64-1 Acetone	quire monitoring at the workplace:	
PEL (USA) Long-term value: 2400 mg/		
REL (USA) Long-term value: 590 mg/n		
TLV (USA) Short-term value: 1187 mg Long-term value: 594 mg/n	/m², 500 ppm 1³, 250 ppm	
A4, BEI		
PEL (USA) Long-term value: 1800 mg/	'm ³ , 1000 ppm	
REL (USA) Long-term value: 1800 mg/	/m³, 1000 ppm	
TLV (USA) see Appendix F Minimal ox 106-97-8 n-butane	ygen content (D, EX)	
REL (USA) Long-term value: 1900 mg/	/m³, 800 ppm	
TLV (USA) Short-term value: 2370 mg	/m³, 1000 ppm	
110-19-0 Isobutyl Acetate		
PEL (USA) Long-term value: 700 mg/n		
REL (USA) Long-term value: 700 mg/n TLV (USA) Short-term value: 712 mg/r		
Long-term value: 238 mg/n	n ³ , 50 ppm	
108-10-1 methyl isobutyl ketone PEL (USA) Long-term value: 410 mg/n	n³ 100 nnm	
REL (USA) Short-term value: 300 mg/r	n ³ . 75 ppm	
Long-term value: 205 mg/m³, 50 ppm		
TLV (USA) Short-term value: 307 mg/m³, 75 ppm Long-term value: 82 mg/m³, 20 ppm		
BEI, A3 107-87-9 Methyl Propyl Ketone		
PEL (USA) Long-term value: 700 mg/m ³ , 200 ppm		
REL (USA) Long-term value: 530 mg/m³, 150 ppm TLV (USA) Short-term value: 529 mg/m³, 150 ppm		
Ingredients with biological limit values:		
67-64-1 Acetone		
BEI (USA) 25 mg/L Medium: urine		
Time: end of shift Parameter: Acetone (nonspecific)		
108-10-1 methyl isobutyl ketone		
BEI (USA) 1 mg/L Medium: urine		
Time: end of shift		
Parameter: MIBK	(Contd. on page 3)	

Page 3/4

Trade name: CR BEIGE	
Hygienic protection:	(Contd. of page 2) Immediately remove all soiled and contaminated clothing. Wash hands after use.
Breathing equipment:	Avoid contact with the eyes and skin. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical
Hand protection:	hygiene. Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

a Physical and chemical propertie	5	
Physical state	Aerosol	
Odor:	Aromatic	
Odor threshold:	Not determined.	
Melting point/Melting range	Undetermined.	
Boiling point:	-44.5 °C (-48.1 °F)	
Flammability:	Extremely flammable.	
Lower Explosion Limit:	1.7 Vol %	
Upper Explosion Limit:	10.9 Vol %	
Flash point:	-19 °C (-2.2 °F)	
Flammability (solid, gas):	Extremely flammable.	
Decomposition temperature:	Not determined.	
pH-value:	Not determined.	
Viscosity:	Not determined.	
Solubility:	Not determined.	
Vapor pressure:	Not determined.	
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)	
Vapor density	Not determined.	
Particle characteristics	Not applicable.	
Appearance:	Aerosol.	
Ignition temperature:	Product is not self-igniting.	
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.	
Water:	0.0 %	
Evaporation rate	Not applicable.	
Partition coefficient: n-octonal/water: Not determined.		

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.	
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit.	Do not warehouse in subfreezing
	temperatures.	C C
Chemical stability:	Not fully evaluated.	
Possibility of hazardous reactions:	No dangerous reactions known.	
Incompatible materials:	No further relevant information available.	
Hazardous decomposition:	No dangerous decomposition products known.	

11 Toxicological information

	groun mine			
LD/LC50 v	LD/LC50 values that are relevant for classification:			
110-19-0 Isobutyl Acetate				
Oral	LD50	4,763 mg/kg (rbt)		
13463-67-	13463-67-7 titanium dioxide			
Oral	LD50	>20,000 mg/kg (ra	t)	
Dermal	LD50	>10,000 mg/kg (rbt)		
Inhalative	LC50/4 h	50/4 h >6.82 mg/l (rat)		
108-10-1 r	108-10-1 methyl isobutyl ketone			
Oral	LD50	2,100 mg/kg (rat)		
Dermal	LD50	16,000 mg/kg (rab		
Inhalative	LC50/4 h	11 mg/l (ATE)		
		8.3-16.6 mg/l (rat)		
Informatio	on on toxi	cological effects:		
Skin effec			No irritant effect.	
Eye effect			Irritating effect.	
Sensitizat	ion:		No sensitizing effects known.	
12 Ecologic	12 Ecological information			
Aquatic to			Hazardous for water, do not empty into drains.	
Persistence and degradability:		gradability:	The product is degradable after prolonged exposure to natural weathering processes.	
				(Contd. on page 4)

	Page 4/4 Safety Data Sheet	
Date of issue: 03/24/2025	Revised On 03/12/2025	
Trade name: CR BEIGE		
Other information: Bioaccumulative potential:	(Contd. of page 3) This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents. No further relevant information available.	
Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available.	
13 Disposal considerations Dispose of in accordance with local, st disposed of responsibly. Do not heat or Recommendation: Recommended cleansing agent:	ate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be cut empty containers with electric or gas torches. Completely empty cans should be recycled. Water, if necessary with cleansing agents.	
14 Transport information		
UN-Number DOT DOT ADR Transport hazard class(es):	UN1950 UN1950 Aerosols, flammable, containing substances in Class 8, Packing Group III 1950 AEROSOLS	
Class Special marking (IATA): Packaging Group: Special precautions for user:	2.1 Gases Warning: Gases	
EMS Number: UN "Model Regulation":	F-D,S-U UN 1950 AEROSOLS, 2.1 (8)	
15 Regulatory information SARA Section 355 (extremely hazard None of the ingredients in this product a SARA Section 313 (Specific toxic chera) 108-10-1 methyl isobutyl ketone	are listed.	
Toxic Substances Control Act (TSCA): Canadian Domestic Substances List (DSL):	All ingredients are found on the inventory list of substances. All ingredients are listed or exempted.	
Consumer Product Safety Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
California Proposition 65 chemicals		
13463-67-7 titanium dioxide 108-10-1 methyl isobutyl ketone 100-41-4 ethyl benzene		
Prop 65 chemicals known to cause b	irth defects or reproductive harm:	
108-10-1 methyl isobutyl ketone EPA:		
67-64-1 Acetone 110-19-0 Isobutyl Acetate		
108-10-1 methyl isobutyl ketone	D 	
16 Other information		
Contact:	Regulatory Affairs	