Date of issue: 04/28/2025		Revised On 04/28/2025		
1 Identification of the substance and manufacturer				
Trade name: Other means of identification	Dark Machinery Gray Ultra Pro-Max (GALLONS)			
Product code: Article category	80643			
Recommended use: Uses advised against: Manufacturer/Supplier:	Paint and coatings application. Any that differs from the recommended use. Kimball Midwest 4800 Roberts Road Columbus, OH 43228 800-233-1294			
Emergency telephone number:	www.kimballmidwest.com ChemTrec: 800-424-9300			
2 Hazard(s) identification				
Classification of the substance or m				
Flammable liquids 3	H226 Flammable liquid and vapor. H319 Causes serious eye irritation.			
Eye irritation 2A Specific target organ toxicity (repeated	exposure) 2 H373 May cause damage to organs through prolonged or repeated ex	nosure		
Additional information: GHS Hazard pictograms				
	GHS02 GHS07 GHS08			
Signal word	Warning			
Hazard statements	Flammable liquid and vapor.			
	Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure.			
Precautionary statements	Keep away from heat, hot surfaces, sparks, open flames and other ignition source	s. No smoking.		
	Keep container tightly closed.	-		
	Ground / bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment.			
	Use non-sparking tools.			
	Take action to prevent static discharge.			
	Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.			
	Wear protective gloves / eye protection / face protection.			
	Wear protective gloves/protective clothing/eve protection/face protection.			
	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with If in eyes: Rinse cautiously with water for several minutes. Remove contact lense	water [or snower].		
	easy to do. Continue rinsing.	bee, in procent and		
	Call a poison center/doctor if you feel unwell.			
	If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish.			
	Store in a well-ventilated place. Keep cool.			
	Dispose of contents/container in accordance with local/regional/national/internation	nal regulations.		
3 Composition/information on ingr Chemical characterization: Mixtures	edients			
Chemical Description:	This product is a mixture of the substances listed below with nonhazardous addition	ons.		
Dangerous components:				
64742-47-8 Mineral Spirits		15-25%		
7727-43-7 barium sulfate		15-25%		
13463-67-7 titanium dioxide		5-10%		
64742-48-9 Naphtha, hydrotreated hea	avy	1-5%		
1330-20-7 xylene (mix)		1-5%		
4 First-aid measures				
After skin contact:	Remove contaminated clothing. Wash exposed area with soap and water.			
After eye contact: After swallowing:	Rinse opened eye for several minutes under running water. Rinse mouth with water. Do not induce vomiting.			
Most important symptoms and				
effects:	No further relevant information available.			
Indication of any immediate medical attention needed:	No further relevant information available.			
5 Fire-fighting measures				
Special hazards:	No further relevant information available.	(Contd. on page 2)		
		(Conta. on page 2)		

Safety Data Sheet

Page 2/4

Date of issue: 04/28/2025	Revised On 04/28/2025
Trade name: DARK GRAY (ANSI 49) (GALL	ONS)
Protective equipment for firefighters:	(Contd. of page 1) No special measures required.
6 Accidental release measures	
Personal precautions, protective	
equipment and emergency	
procedures: Methods and material for	Not required.
containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
7 Handling and storage	
Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.
8 Exposure controls/personal pro	tection
	require monitoring at the workplace:
7727-43-7 barium sulfate	
PEL (USA) Long-term value: 15* 5**	mg/m³
<pre>*total dust **respirable fra REL (USA) Long-term value: 10* 5**</pre>	
` total dust **respirable fra	uction I I I I I I I I I I I I I I I I I I I
TLV (USA) Long-term value: 5* mg/m *inhalable fraction; E	۲ ۰
1330-20-7 xylene (mix)	
PEL (USA) Long-term value: 435 mg REL (USA) Short-term value: 655 mg	
Long-term value: 435 mg/	/m³, 100 ppm
TLV (USA) Long-term value: 20 ppm BEI, A4	
111-76-2 Glycol Ether EB	
PEL (USA) Long-term value: 240 mg/ Skin	/m³, 50 ppm
REL (USA) Long-term value: 24 mg/n Skin	n³, 5 ppm
TLV (USA) Long-term value: 97 mg/n BEI, A3	n³, 20 ppm
Ingredients with biological limit val	ues:
1330-20-7 xylene (mix)	
BEI (USA) 1.5 g/g creatinine	
Medium: urine Time: end of shift	
Parameter: Methylhippuric	acids
111-76-2 Glycol Ether EB	
BEI (USA) 200 mg/g creatinine Medium: urine	
Time: end of shift	acid (RAA) (with hydrolycic)
Hygienic protection:	acid (BAA) (with hydrolysis) Wash hands after use.
	Do not eat or drink while working.
Breathing equipment: Hand protection:	Not required. Nitrile gloves.
· · · · · · · · · · · · · · · · · · ·	The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles
9 Physical and chemical propertie	
Physical state Odor:	Liquid
Odor threshold:	Not determined.
Melting point/Melting range Boiling point:	Undetermined. 175 °C (347 °F)
Flammability:	Flammable.
Lower Explosion Limit:	0.5 Vol %
Upper Explosion Limit: Flash point:	6.5 Vol % 30 °C (86 °F)
Flammability (solid, gas):	Flammable
Decomposition temperature: pH-value:	Not determined. Not determined.
P	(Contd. on page 3)

Viscosity: Solubility: Not determined. Not determined. Vapor pressure: Relative Density: Not determined. Vapor density Not determined. **Particle characteristics** Not applicable. Appearance: Liquid. Ignition temperature: Danger of explosion: Product is not self-igniting. In use, may form flammable/explosive vapour-air mixture. Water: 0.0 % **Evaporation rate** Not determined. Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

11 Toxicological information

	•	t are relevent for elegation.	
	LD/LC50 values that are relevant for classification:		
	13463-67-7 titanium dioxide		
Oral		>20,000 mg/kg (rat)	
		>10,000 mg/kg (rbt)	
Inhalative	Inhalative LC50/4 h >6.82 mg/l (rat)		
64742-48-	64742-48-9 Naphtha, hydrotreated heavy		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>3,000 mg/kg (rab)	
1330-20-7	1330-20-7 xylene (mix)		
Oral	LD50	8,700 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rbt)	
Inhalative	Inhalative LC50/4 h 6,350 mg/l (rat)		
111-76-2 (111-76-2 Glycol Ether EB		
Oral	LD50	1,200 mg/kg (ATE)	
		1,480 mg/kg (rat)	
Dermal	LD50	400 mg/kg (rab)	
Inhalative	LC50/4 h	3 mg/l (ATE)	
Informatio	Information on toxicological effects: No data available.		
	Skin effects: No irritant effect.		
Eye effect		No irritating effect.	
Sensitizat	tion:	No sensitizing effects known.	

12 Ecological information Aquatic toxicity: Persistence and degradability: Other information: Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents. Bioaccumulative potential: Mobility in soil: Other adverse effects: No further relevant information available. No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, s	tate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be	
disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.		
Recommendation:	Completely empty cans should be recycled.	
Recommended cleansing agent:	Water, if necessary with cleansing agents.	

14 Transport information		
UN-Number DOT DOT ADR Transport hazard class(es): Class	UN1263 Paint 1263 PAINT (vapour pressure at 50°C not more than 110 kPa) 3 Flammable liquids	(Contd. on page 4)
		(Conta: on page 4)

(Contd. of page 2)

Revised On 04/28/2025

Trade name: DARK GRAY (ANSI 49) (GALLONS)

Page 4/4

Special marking (IATA);	(Contd. of page 3)
Special marking (IATA): Packaging Group:	
Special precautions for user:	Warning: Flammable liquids
EMS Number:	F-E, <u>S-E</u>
Stowage Category UN "Model Regulation":	B UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II
-	
15 Regulatory information	
SARA Section 355 (extremely hazard	
None of the ingredients in this product	are listed.
SARA Section 313 (Specific toxic ch	emical listings):
7727-43-7 barium sulfate	
1330-20-7 xylene (mix)	
Toxic Substances Control Act	
(TSCA): Canadian Domestic Substances Lis	All ingredients are found on the inventory list of substances.
(DSL):	د All ingredients are listed or exempted.
Consumer Product Safety	
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemicals	known to cause cancer:
13463-67-7 titanium dioxide	
1333-86-4 Carbon black	
100-41-4 ethyl benzene	
Prop 65 chemicals known to cause	birth defects or reproductive harm:
None of the ingredients is listed.	
EPA:	
7727-43-7 barium sulfate	D, CBD(inh), NL(oral)
1330-20-7 xylene (mix)	
16 Other information	
	Pogulatany Affaira
Contact:	Regulatory Affairs

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.