



Slick Tire Mounting Lubricant

Page 1 of 7

Version: 1.0011

Revision Date: 04/12/2018

Print Date: 05/06/2020

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Slick Tire Mounting Lubricant

PRODUCT USE: Lubricant

MANUFACTURED FOR: Warsaw Chemical Holdings LLC.

P.O. Box 858 Warsaw, IN 46581

INFORMATION PHONE: Tel: 1-800-548-3396

Fax: 1-574-267-3884

EMERGENCY PHONE: INFOTRAC

1-800-535-5053 USA & Canada 352-323-3500 International

SECTION 2 - HAZARD(S) IDENTIFICATION

CLASSIFICATION: Acute Toxicity - Oral: Category 5

Eye Damage: Category 2A

PICTOGRAMS:

 \bigcirc

GHS ELELMENTS:

SIGNAL WORD: Warning

HAZARD STATEMENT(S): H303 | May be harmful if swallowed.

H319 | Causes serious eye irritation.

PRECAUTIONARY STATEMENT(S): P264 | Wash any exposed body parts thoroughly after handling.

P280 | Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 | Call a POISON CENTER or doctor/physician if you feel unwell. P337 + P313 | If eye irritation persists: Get medical advice/attention.

ADDITIONAL PRECAUTIONS: None Known

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS #	FUNCTIONAL PURPOSE	PERCENT
Alkylbenzene sulfonic Acid	68584-22-5	Surfactant	1 - 5%
Nonionic Thickener Blend	Not Available	Viscosity	1 - 5%
Sodium Hydroxide 50%	1310-73-2	pH Adjustment	< 1.0%
Sodium Metasilicate Pentahydrate	10213-79-3	Alkaline Builder	< 1.0%



Slick Tire Mounting Lubricant

Page 2 of 7 1.0011

Version: Revision Date: Print Date:

04/12/2018 05/06/2020

Acid Blue 145Not AvailableColorant< 1.0%Dye Basic Violet 1081-88-9Colorant< 1.0%Nonylphenol ethoxylate127087-87-0Surfactant< 1.0%

The chemical identity of some or all components is confidential business information (trade secret) and is being withheld as permitted by 29CFR19191200 (i). No other ingredients known to be hazardous.

SECTION 4 - FIRST AID MEASURES

EYES: Check for and remove contact lenses. Immediately flush eyes with plenty of water

for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get

medical attention immediately.

SKIN: Wash skin surfaces thoroughly after contact. Wash clothing and clean shoes

thoroughly before reuse. Get medical attention if irritation develops.

INHALATION: Move exposed person to fresh air. If breathing is irregular or if respiratory arrest

occurs, provide artificial respiration or oxygen by trained personnel. Loosen

clothing. Get medical attention immediately.

INGESTION: Wash out mouth with water. Do not induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious person. Get

medical attention immediately.

GENERAL: Physicians: No specific treatment. Treat symptomatically. Contact poison

treatment specialist if large quantities have been inhaled or ingested.

See Section 11 for exposure symptoms.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABILITY: In a fire or if heated, a pressure increase will occur and the container may burst.

EXTINGUISHING MEDIA: Use an extinguishing agent suitable for the surrounding fire.

PROTECTIVE EQUIPMENT: Fire-fighters should wear appropriate protective equipment and self-contained

breathing apparatus (SCBA) with full face-piece operated in positive pressure

mode.

ADDITIONAL INFORMATION: Thermal decomposition products-carbon monoxide, sulfur oxides, metal

oxide/oxides, halogenated compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: No action should be taken involving individual risk or without suitable training.

Isolate area. Avoid contact with material. Do not breathe vapors. Provide

adequate ventilation. Wear proper personal protective equipment.

ENVIRONMENTAL: Avoid dispersal of spilled material and runoff and contact with soil, waterways,

drains and sewers. Inform relevant authorities if the product reaches sewers,



Slick Tire Mounting Lubricant

Version:

Print Date:

Page 3 of 7 1.0011 Revision Date: 04/12/2018 05/06/2020

waterways or soil.

CONTAINMENT/CLEANUP:

Stop leak if without risk. Move containers from spill area. Contain or absorb with inert dry material. Dispose of according to local regulations. See Section 1 for emergency contact information and 13 for waste disposal.

SECTION 7 - HANDLING AND STORAGE

SAFE HANDLING: Wear appropriate personal protective equipment (see Section 8). Eating drinking

and smoking should be prohibited. Do not get into eyes or on skin. Do not ingest.

Keep containers tightly closed. Do not reuse container.

Store in accordance with local regulations. Store in original container away from SAFE STORAGE:

foods, drink and incompatible materials. Keep container tightly closed. Do not

store unlabeled. Use appropriate containment.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Apply technical measures to comply with occupational exposure limits. Mechanical **ENGINEERING CONTROLS:**

ventilation, eyewash stations, showers where necessary.

Safety eye-wear/face shield complying with an approved standard should be used EYE PROTECTION:

when a risk assessment indicates this is necessary to avoid exposure to liquid

splashes, mists or dusts.

Use a properly fitted air-purifying or air-fed respirator complying with an approved RESPIRATORY PROTECTION:

> standard if a risk assessment indicates necessity. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product & the

safe working limits of the chosen respirator.

Chemical resistant, impervious gloves complying with an approved standard HAND PROTECTION:

should be worn at all times when handling chemical products if a risk assessment

indicates this is necessary.

SKIN PROTECTION: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

COMPONENT	ACGIH TWA ppm	OSHA/NIOSH STEL ppm	OSHA/ACGIH STEL mg/m3
Alkylbenzene sulfonic Acid	None	None	0.20
Nonionic Thickener Blend	None	None	None
Sodium Hydroxide 50%	2.00	None	None
Sodium Metasilicate Pentahydrate	None	None	None
Acid Blue 145	None	None	None
Dye Basic Violet 10	None	None	None
Nonylphenol ethoxylate	10.00	None	None



Slick Tire Mounting Lubricant

Page 4 of 7
Version: 1.0011
Revision Date: 04/12/2018
Print Date: 05/06/2020

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid UPPER EXPLOSIVE LIMITS: NA

COLOR: Purple LOWER EXPLOSIVE LIMITS: NA

ODOR: None VAPOR PRESSURE: NA

ODOR THRESHOLD: NA VAPOR DENSITY: NA

PH: 10.1 - 11.4 RELATIVE DENSITY: NA

MELTING POINT: NA SOLUBILITY: Completely Water

Soluble

FREEZING POINT: 32.00 F PARTITION COEFFICIENT: NA

BOILING POINT: NA AUTO-IGNITION TEMPERATURE: NA

FLASH PT METHOD: NA DECOMPOSITION TEMPERATURE: NA

FLASH POINT: NA SPECIFIC GRAVITY: 1.00500

EVAPORATION RATE: NA % VOLATILE: NA

FLAMMABILITY: Nonflammable VISCOSITY (cst): NA

SECTION 10 - STABILITY AND REACTIVITY

REACTIVITY: HAZARDOUS DECOMPOSITION PRODUCTS

CHEMICAL STABILITY: Stable under normal conditions.

POSSIBILITY OF HAZARDOUS

REACTIONS:

Non-reactive.

CONDITIONS TO AVOID: Excessive heat or open flame.

INCOMPATIBLE MATERIALS: Avoid contact with acidic materials and strong oxidizers.

HAZARDOUS Under normal conditions, none are known.

DECOMPOSITION PRODUCTS:

SECTION 11 - TOXICOLOGICAL INFORMATION

ROUTES OF ENTRY: Inhalation Absorption Ingestion

ACUTE EXPOSURE HAZARDS:

EYE CONTACT: Irritation, stinging, redness, burns.



Slick Tire Mounting Lubricant

Page 5 of 7

Version: 1.0011

Revision Date: 04/12/2018

Print Date: 05/06/2020

DERMAL: Irritation, burns upon prolonged exposure.

ORAL: Nausea, vomiting.

INHALATION: No expected route of entry. Irritation.

Alkylbenzene sulfonic Acid (CAS No. 68584-22-5)

Oral LD50: greater than 5mg/kg

Sodium Metasilicate Pentahydrate (CAS No. 10213-79-3)

Oral LD50: Rat 1152-1349 mg

Nonylphenol ethoxylate (CAS No. 127087-87-0)

Oral LD50: Rat 1600 mg/kg

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY: No data available.

PERSISTENCE & DEGRADABILITY: No data available.

BIOACCUMULATIVE POTENTIAL: No data available.

MOBILITY IN SOIL: No data available.

OTHER ADVERSE EFFECTS: No data available.

Alkylbenzene sulfonic Acid (CAS No. 68584-22-5)

Fish LC50: greater than 1000mg/L

Crustacean LC50: greater than 1000mg/L daphnia

Sodium Hydroxide 50% (CAS No. 1310-73-2)

Fish LC50: 144mg/L, 96H guppy

Sodium Metasilicate Pentahydrate (CAS No. 10213-79-3) Fish LC50: Danio Rerio (Zebra Fish) 210 mg/L 96h

SECTION 13 - DISPOSAL CONSIDERATION

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of the product may change the waste management options. Waste generators must decide if discarded material is a hazardous waste. State and local disposal regulations may differ from federal disposal definitions. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 - TRANSPORT INFORMATION

DOT (US)

UN NUMBER: NA

SHIPPING NAME: NA

TECHNICAL NAME: NA



Slick Tire Mounting Lubricant

Page 6 of 7 1.0011

Version: 1.0011
Revision Date: 04/12/2018
Print Date: 05/06/2020

Warsaw Chemical HOLDINGS LLC

RO. BOX 858 • Warsaw, Indiana 46581

800-548-3396 • www.warsaw-chem.com

HAZARD CLASS: NA

PACKAGING GROUP: NA

SECTION 15 - REGULATORY INFORMATION

SARA 313 COMPONENTS CAS NO. % LESS THAN

2-Butoxyethanol 111-76-2 < 1.0%

CALIFORNIA PROP. 65 COMPONENTS CAS NO. % LESS THAN

2-Butoxyethanol 111-76-2 < 1.0% Nonylphenol ethoxylate 127087-87-0 < 1.0%

RQ 1,000#

This product can expose you to Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm..

127087-87-0 Nonylphenol polyethylene glycol ether 90 - 100 %

25322-68-3 Polyethylene glycol 1 - 5 %

123-91-1 1,4-Dioxane 0 - 0.1 %

64-19-7 Acetic acid 0 - 0.1 %

75-21-8 Ethylene oxide 0 - 0.1 %

RTK: MA, PA, NJ,

WARNING! This product contains a chemical known to the

State of California to cause cancer birth defects or other reproductive

harm.

123-91-1 1,4-Dioxane 0 - 0.1 %

64-19-7 Acetic acid 0 - 0.1 %

75-21-8 Ethylene oxide 0 - 0.1 %

SECTION 16 - OTHER INFORMATION

HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.)

Health Hazard	1
Fire Hazard	0
Reactivity	0
Personal Protection	Α

Caution: HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks and 4 representing significant hazards or risks.

- A Safety Glasses
- B Safety Glasses, Gloves
- C Safety Glasses, Gloves, Apron
- D Face Shield, Gloves, Apron
- E Safety Glasses, Gloves, Dust Respirator
- F Safety Glasses, Gloves, Apron, Dust Respirator
- G Safety Glasses, Gloves, Vapor Respirator
- H Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- I Safety Glasses, Gloves, Dust & Vapor Respirator
- J Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- K Airline Hood or Mask, Gloves, Full Suit, Boots
- X Consult your supervisor for special handling directions

Flammability



Slick Tire Mounting Lubricant

Version:


Print Date:

Revision Date:

Page 7 of 7 1.0011 04/12/2018

05/06/2020

NATIONAL FIRE PROTECTION ASSOCIATION (U.S.A.)



NFPA warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals.

Information on this form is furnished soley for the purpose of compliance with the Occupational Safety and Health Act of 1970 and shall not be used for any other purpose. Use or dissemination of all or any part of this information can be grounds for legal action.

To the best of our knowledge, the information provided in this Safety Data Sheet is accurate as of the date of its issue. However, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE. The information this Safety Data Sheet contains is being given to that material when combined with other material(s) or when used otherwise than as described herein.

In all cases, it is the responsibility of the user to determine the applicability of such information and recommendations and the suitability of any product for its own particular purpose. All materials may represent unknown hazards and should be used with caution.