Safety Data Sheet

Printing date 06/09/2022 Revised On 06/09/2022

1 Identification of the substance and manufacturer

Trade name: **LIGHT GRAY PRIMER**

80-650 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228 800-233-1294

www.kimballmidwest.com

ChemTrec: 800-424-9300 **Emergency telephone number:**

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Liquids 2 H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed. Acute Toxicity - Oral 4 Skin Irrititation 2 H315 Causes skin irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**





Signal word Danger

Highly flammable liquid and vapor. **Hazard statements**

Harmful if swallowed. Causes skin irritation.

May cause an allergic skin reaction.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use. **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.

In case of fire: Use CO2, powder or water spray to extinguish.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

Onemical Bescription:		This product is a mixture of the substances listed below with hornazardous additions.	
Dangerous components:			
	Calcium Carbonate		25-50%
	p-Chlorobenzotrifluoride		10-15%
64742-47-8	Mineral Spirits		5-10%
13463-67-7	titanium dioxide		5-10%
557-05-1	zinc stearate		1-5%
	ethyl methyl ketoxime		≥0.2-<1%

4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. After eye contact:

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting

Most important symptoms and

effects: No further relevant information available. Indication of any immediate medical

attention needed: No further relevant information available. Safety Data Sheet

Printing date 06/09/2022 Revised On 06/09/2022

Trade name: LIGHT GRAY PRIMER

(Contd. of page 1)

5 Fire-fighting measures

Special hazards: No further relevant information available.

Protective equipment for firefighters: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up: Not required.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

557-05-1 zinc stearate

Long-term value: 15* 5** mg/m³ PEL (USA)

*total dust **respirable fraction Long-term value: 10* 5** mg/m3

REL (USA) *total dust **respirable fraction

Long-term value: 10* 3** mg/m³
*inhalable, **respirable particulate matter, *A4

ethyl methyl ketoxime

TLV (USA)

WEEL (USA) Long-term value: 10 ppm

DSĚN

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Do not eat or drink while working.

Breathing equipment:

Hand protection:

Not required. Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Liquid. Odor threshold: Not determined.

Not determined. Melting point/Melting range Undetermined. 139 °C (282.2 °F) **Boiling point:** Flash point: -19 °C (-2.2 °F) Highly flammable. Flammability (solid, gas): Decomposition temperature: Not determined.

Product is not self-igniting. Auto igniting:

In use, may form flammable/explosive vapour-air mixture. Danger of explosion:

Lower Explosion Limit: 0.5 Vol % **Upper Explosion Limit:** 6.5 Vol % Not determined. Vapor pressure: Vapor density Not determined. Not determined. **Evaporation rate** Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility:

Viscosity: Not determined.

Water: 0.0 %

10 Stability and reactivity

Conditions to avoid: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

Printing date 06/09/2022 Revised On 06/09/2022

Trade name: LIGHT GRAY PRIMER

Hazardous decomposition: No dangerous decomposition products known. (Contd. of page 2)

11 Toxicological information

LD/LC50 values that are relevant for classification: 13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat) Dermal LD50 >10,000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

ethyl methyl ketoxime

Oral LD50 100 mg/kg (ATE) 3,700 mg/kg (rat) Dermal LD50 1,100 mg/kg (ATE) 200-2,000 mg/kg (rat)

Inhalative LC50/4 h 20 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. No irritating effect. Eye effects:

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: No further relevant information available. No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1263 DOT UN1263 DOT Paint **ADR** 1263 Paint

Transport hazard class(es):

3 Flammable liquids Class

Marine pollutant: Nο

Warning: Flammable liquids Special precautions for user:

EMS Number: F-E,S-E

Stowage Category

UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

557-05-1 zinc stearate 7779-90-0 zinc phosphate

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

98-56-6 p-Chlorobenzotrifluoride

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

(Contd. on page 4)

Page 4/4

Safety Data Sheet

Printing date 06/09/2022 Revised On 06/09/2022

Filling date 00/09/2022	Revised OII 00/09/2022		
Trade name: LIGHT GRAY PRIMER			
1333-86-4 Carbon black	(Contd. of page 3)		
Prop 65 chemicals known to cause birth defects or reproductive harm: None of the ingredients is listed.			
EPA: 557-05-1 zinc stearate	D, I, II		
7779-90-0 zinc phosphate	D, I, II		

16 Other information

Contact: Regulatory Affairs