Revised On 06/09/2022

1 Identification of the substance and manufacturer Trade name: NEW FARM & IMPLEMENT GREEN Product code: 80-828 Recommended use: Paint and coatings application. Uses advised against: Any that differs from the recommended use. Manufacturer/Supplier: Kimball Midwest 4800 Roberts Road Columbus, OH 43228 800-233-1294 www.kimballmidwest.com Emergency telephone number: Chem Trec: 800-424-9300 2 Hazard(s) identification H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Eye Irritation 2A H319 Causes erious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Carcinogenicity 2 H336 May cause drowsines or dizziness. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause damage to organs through prolonged or repe Additional information: Gits Hazard pictograms Gits Gaso GHS04 GHS07 GHS08	
Product code: 80-828 Recommended use: Paint and coatings application. Uses advised against: Any that differs from the recommended use. Manufacturer/Supplier: Kimball Midwest 4800 Roberts Road Columbus, OH 432228 800-233-1294 www.kimballmidwest.com Emergency telephone number: ChemTrec: 800-424-9300 2 Hazard(s) identification 1 Classification of the substance or mixture 1 Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Eye Irritation 2A H319 Causes serious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Carcinogenicity 2 H336 May cause drowsiness or dizziness. Specific Target Organ Toxicity - Single Exposure 2 H373 May cause damage to organs through prolonged or repe Additional information: GHS Hazard pictograms Air Quice Air	
2 Hazard(s) identification Classification of the substance or mixture Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Eye Irritation 2A H319 Causes serious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalat Specific Target Organ Toxicity - Single Exposure 3 H373 May cause damage to organs through prolonged or repe Additional information: GHS Hazard pictograms	
Classification of the substance or mixtureFlammable Aerosols 1Gases under Pressure - Liquefied gasEye Irritation 2ASensitization - Skin 1Carcinogenicity 2Specific Target Organ Toxicity - Single Exposure 3Specific Target Organ Toxicity - Repeated Exposure 2Additional information:GHS Hazard pictograms	
Classification of the substance or mixtureFlammable Aerosols 1Gases under Pressure - Liquefied gasEye Irritation 2ASensitization - Skin 1Carcinogenicity 2Specific Target Organ Toxicity - Single Exposure 3Specific Target Organ Toxicity - Repeated Exposure 2Additional information:GHS Hazard pictograms	
Flammable Aerosols 1H222 Extremely flammable aerosol.Gases under Pressure - Liquefied gasH280 Contains gas under pressure; may explode if heated.Eye Irritation 2AH319 Causes serious eye irritation.Sensitization - Skin 1H317 May cause an allergic skin reaction.Carcinogenicity 2H351 Suspected of causing cancer. Route of exposure: InhalatSpecific Target Organ Toxicity - Single Exposure 3H373 May cause drowsiness or dizziness.Specific Target Organ Toxicity - Repeated Exposure 2H373 May cause damage to organs through prolonged or repeAdditional information:GHS Hazard pictograms	
Gases under Pressure - Liquefied gasH280 Contains gas under pressure; may explode if heated.Eye Irritation 2AH319 Causes serious eye irritation.Sensitization - Skin 1H317 May cause an allergic skin reaction.Carcinogenicity 2H351 Suspected of causing cancer. Route of exposure: InhalatSpecific Target Organ Toxicity - Single Exposure 3H373 May cause drowsiness or dizziness.Specific Target Organ Toxicity - Repeated Exposure 2H373 May cause damage to organs through prolonged or repeAdditional information:GHS Hazard pictograms	
GHS02 GHS04 GHS07 GHS08	
GHS02 GHS04 GHS07 GHS08	
Signal word Hazard statements Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. Route of exposure: Inhalation. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	lenses, if present and
Dispose of contents/container in accordance with local/regional/national/intern	national regulations.
3 Composition/information on ingredients	
Chemical characterization: Mixtures Chemical Description: This product is a mixture of the substances listed below with nonhazardous ac	dditions.
Dangerous components:	
67-64-1 Acetone 74-98-6 propane 7727-43-7 barium sulfate 106-97-8 n-butane 110-19-0 Isobutyl Acetate 2807-30-9 Glycol Ether EP 123-86-4 butyl acetate 108-65-6 PM acetate 107-87-9 Methyl Propyl Ketone	15-25% 15-25% 5-10% 5-10% ≥5-<10% 1-5% 1-5%

4 First-aid measures

After inhalation: After skin contact: Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water.

(Contd. on page 2)

Page 2/4

inting data 001001000		Safety Data Sheet		
inting date 06/09/202	22	Revised On 06/09/202		
Frade name: NEW FARM & IMPLEMENT GREEN				
After eye cor After swallov		(Contd. of page 1) Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.		
	ant symptoms and			
effects: Indication of	any immediate medical	Dizziness		
attention nee	eded:	No further relevant information available.		
5 Fire-fighting	g measures			
Extinguishin	g agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.		
Special haza Protective ec	rds: puipment for	Can form explosive gas-air mixtures.		
firefighters:	1	A respiratory protective device may be necessary.		
6 Accidental	release measures			
Personal pre	cautions, protective			
equipment a procedures:	nd emergency	Use respiratory protective device against the effects of fumes/dust/aerosol.		
Methods and	l material for	Use respiratory protective device against the enects of fumes/dust/acrosol.		
containment	and cleaning up:	Absorb liquid components with liquid-binding material.		
7 Handling ar	ad storago			
	for safe handling	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions Store locked up.		
0 5				
•	ontrols/personal prote			
67-64-1 Acet		equire monitoring at the workplace:		
PEL (USA)	Long-term value: 2400 m	ng/m³, 1000 ppm		
REL (USA)	Long-term value: 590 mg			
TLV (USA)	Short-term value: 500 pp Long-term value: 250 pp A4, BEI	m m		
74-98-6 prop				
PEL (USA)	Long-term value: 1800 m			
REL (USA)	Long-term value: 1800 m			
TLV (USA)	see Appendix F Minimal	oxygen content (D, EX)		
7727-43-7 ba PEL (USA)	Long-term value: 15* 5**	mg/m ³		
1 22 (00,1)	*total dust **respirable fr	action		
REL (USA)	Long-term value: 10* 5** *total dust **respirable fr	mg/m ³		
TLV (USA)	Long-term value: 5* mg/			
	*inhalable fraction; E			
	utano			
106-97-8 n-bi		ng/m ³ 800 ppm		
REL (USA)	Long-term value: 1900 m			
REL (USA) TLV (USA)	Long-term value: 1900 m Short-term value: 1000 p (EX)			
REL (USA) TLV (USA) 110-19-0 Isot	Long-term value: 1900 n Short-term value: 1000 p (EX) outyl Acetate	pm		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA)	Long-term value: 1900 n Short-term value: 1000 p (EX) outyl Acetate Long-term value: 700 mg	pm j/m³, 150 ppm		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA) REL (USA)	Long-term value: 1900 n Short-term value: 1000 p (EX) butyl Acetate Long-term value: 700 mg Long-term value: 700 mg	pm g/m³, 150 ppm g/m³, 150 ppm		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA) REL (USA) TLV (USA)	Long-term value: 1900 n Short-term value: 1000 p (EX) butyl Acetate Long-term value: 700 mg Short-term value: 150 pp Long-term value: 50 ppn	pm g/m³, 150 ppm g/m³, 150 ppm g/m		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA) REL (USA) TLV (USA) 123-86-4 but	Long-term value: 1900 m Short-term value: 1000 p (EX) butyl Acetate Long-term value: 700 mg Short-term value: 700 mg Short-term value: 150 pp Long-term value: 50 ppm yl acetate	pm g/m³, 150 ppm g/m³, 150 ppm m		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA) REL (USA) TLV (USA) 123-86-4 but PEL (USA)	Long-term value: 1900 n Short-term value: 1000 p (EX) outyl Acetate Long-term value: 700 mg Short-term value: 700 pp Long-term value: 150 pp yl acetate Long-term value: 710 mg	p/m³, 150 ppm g/m³, 150 ppm m n n g/m³, 150 ppm		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA) REL (USA) TLV (USA) 123-86-4 but	Long-term value: 1900 m Short-term value: 1000 p (EX) outyl Acetate Long-term value: 700 mg Short-term value: 700 mg Short-term value: 150 pp Long-term value: 50 ppm yl acetate Long-term value: 710 mg Short-term value: 950 m Long-term value: 710 mg	pm g/m³, 150 ppm m 1 g/m³, 150 ppm g/m³, 150 ppm g/m³, 200 ppm g/m³, 150 ppm		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA) REL (USA) TLV (USA) 123-86-4 but PEL (USA)	Long-term value: 1900 m Short-term value: 1000 p (EX) outyl Acetate Long-term value: 700 mg Short-term value: 700 mg Short-term value: 150 pp Long-term value: 50 ppm yl acetate Long-term value: 710 mg Short-term value: 710 mg Short-term value: 710 mg Short-term value: 710 mg	pm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 200 ppm g/m ³ , 150 ppm		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA) REL (USA) TLV (USA) 123-86-4 but PEL (USA) REL (USA)	Long-term value: 1900 m Short-term value: 1000 p (EX) butyl Acetate Long-term value: 700 mg Short-term value: 700 mg Long-term value: 50 pp yl acetate Long-term value: 710 mg Short-term value: 950 m Long-term value: 710 mg Short-term value: 710 mg Short-term value: 710 mg	pm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 200 ppm g/m ³ , 150 ppm		
REL (USA) TLV (USA) 110-19-0 Isot PEL (USA) REL (USA) TLV (USA) 123-86-4 buty PEL (USA) REL (USA) TLV (USA) 108-65-6 PM WEEL (USA)	Long-term value: 1900 m Short-term value: 1000 p (EX) Dutyl Acetate Long-term value: 700 mg Short-term value: 150 pp Long-term value: 50 ppm yl acetate Long-term value: 710 mg Short-term value: 710 mg Short-term value: 710 mg Short-term value: 710 mg Short-term value: 50 ppm acetate Long-term value: 50 ppm	pm j/m³, 150 ppm j/m³, 150 ppm j/m³, 150 ppm g/m³, 200 ppm j/m³, 150 ppm j/m³, 150 ppm		
REL (USA) TLV (USA) PEL (USA) REL (USA) TLV (USA) 123-86-4 buty PEL (USA) REL (USA) REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) 107-87-9 Met	Long-term value: 1900 m Short-term value: 1000 p (EX) Dutyl Acetate Long-term value: 700 mg Short-term value: 150 pp Long-term value: 50 ppm yl acetate Long-term value: 710 mg Short-term value: 710 mg Short-term value: 710 mg Short-term value: 710 mg Short-term value: 50 ppm Long-term value: 50 ppm acetate	pm j/m³, 150 ppm j/m³, 150 ppm j/m³, 150 ppm g/m³, 200 ppm j/m³, 150 ppm m h		

Page 3/4

Revised On 06/09/2022

rade name: NEW FARM & IMPLEMENT GR	EEN
	(Contd. of page
REL (USA)Long-term value: 530 mTLV (USA)Short-term value: 150 p	
Ingredients with biological limit value	Ies:
67-64-1 Acetone	
BEI (USA) 25 mg/L	
Medium: urine	
Time: end of shift Parameter: Acetone (nons)	
Hygienic protection:	Immediately remove all soiled and contaminated clothing.
riygienic protection.	Wash hands after use.
	Avoid contact with the eyes and skin.
	Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. cases where short and/or long term overexposure exists, a charcoal filter respirator should be wor
	If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Nitrile gloves.
	The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles
9 Physical and chemical properties	
Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: Upper Explosion Limit:	1.7 Vol % 10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/wate	r: Not determined.
Solubility:	Not determined.
Viscosity:	Not determined. 0.0 %
Water:	0.0 %
0 Stability and reactivity	
Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezi
Chemical stability:	temperatures. Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.
1 Toxicological information LD/LC50 values that are relevant for	
110-19-0 Isobutyl Acetate	CIQ33111-QUVII.
Oral LD50 4,763 mg/kg (rbt)	
123-86-4 butyl acetate	
Oral LD50 14,000 mg/kg (ra	t)
Inhalative LC50/4 h >21 mg/l (rat)	,
108-65-6 PM acetate	
Oral LD50 8,500 mg/kg (rat	
Inhalative LC50/4 h 35.7 mg/l (rat)	
Information on toxicological effects	
Skin effects:	No irritating effect
Eye effects:	Irritating effect. (Contd. on page

Revised On 06/09/2022

Page 4/4

Trade name: NEW FARM & IMPLEMENT GREEN

Sensitization:	No sensitizing effects known. (Contd. of page 3)	
12 Ecological information		
Aquatic toxicity: Persistence and degradability: Other information:	azardous for water, do not empty into drains. he product is degradable after prolonged exposure to natural weathering processes. his product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons ICFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated plyents.	
Bioaccumulative potential: Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available. No further relevant information available.	

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. **Recommendation:** Completely empty cans should be recycled.

14 Transport information

UN-Number DOT DOT	UN1950 UN1950 DOT Aerosols, flammable
ADR Transport hazard class(es):	1950 Aerosols
Class	2.1 Gases
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Packaging Group:	
UN "Model Regulation":	UN1950, Aerosols, 2.1

15 Regulatory information

To Regulatory into			
SARA Section 355 (extremely hazardous substances):			
None of the ingredients in this product are listed.			
SARA Section 313 (Specific toxic chemical listings):			
7727-43-7 barium sulfate			
Toxic Substances (TSCA):	All hazardous ingredients are found on the inventory list of substances.		
(DSL):	All ingredients are listed or exempted.		
Consumer Produ Comission (CPS)	C): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
	sition 65 chemicals known to cause cancer:		
13463-67-7 titaniu			
108-10-1 methy	yl isobutyl ketone		
100-41-4 ethyl	benzene		
1333-86-4 Carbo	on black		
Prop 65 chemical	Is known to cause birth defects or reproductive harm:		
108-10-1 methyl i	isobutyl ketone		
EPA:			
67-64-1 Aceton	ne l		
7727-43-7 barium	n sulfate D, CBD(inh), NL(oral)		
110-19-0 Isobuty	yl Acetate D		
16 Other information	on		
Contact:	Regulatory Affairs		