

## Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

## 1 Identification of the substance and manufacturer

Trade name: LIGHT GRAY PRIMER  
 Other means of identification  
 Product code: 80-884  
 Article category  
 Recommended use: Paint and coatings application.  
 Uses advised against: Any that differs from the recommended use.  
 Manufacturer/Supplier: Kimball Midwest  
 4800 Roberts Road  
 Columbus, OH 43228  
 800-233-1294  
 www.kimballmidwest.com  
 ChemTrec: 800-424-9300  
 Emergency telephone number:

## 2 Hazard(s) identification

## Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.  
 Eye irritation 2A H319 Causes serious eye irritation.  
 Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.  
 Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.  
 Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

## Additional information:

## GHS Hazard pictograms



GHS02 GHS07 GHS08

## Signal word

## Hazard statements

Danger  
 Extremely flammable aerosol. Pressurized container: may burst if heated.  
 Causes serious eye irritation.  
 Suspected of causing cancer. Route of exposure: Inhalation.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Avoid breathing fume/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned:  
 Call a poison center/doctor if you feel unwell.  
 Get medical attention if you feel unwell.  
 Get medical help if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well ventilated place. Keep container tightly closed.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## Precautionary statements

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

|            |                      |        |
|------------|----------------------|--------|
| 67-64-1    | Acetone              | 15-25% |
| 74-98-6    | propane              | 10-15% |
| 110-19-0   | Isobutyl Acetate     | 10-15% |
| 106-97-8   | n-butane             | 5-10%  |
| 13463-67-7 | titanium dioxide     | 5-10%  |
| 64742-89-8 | VM&P Naphtha         | 5-10%  |
| 14807-96-6 | Talc                 | 1-5%   |
| 64-17-5    | ethyl alcohol        | 1-5%   |
| 107-87-9   | Methyl Propyl Ketone | 1-5%   |
| 64742-47-8 | Mineral Spirits      | 1-5%   |
| 67-63-0    | Isopropyl Alcohol    | 1-5%   |

(Contd. on page 2)

## Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

Trade name: LIGHT GRAY PRIMER

108-65-6 | PM acetate

(Contd. of page 1)

1-5%

**4 First-aid measures**

|                                                              |                                                                                                  |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <b>After inhalation:</b>                                     | Supply fresh air; consult doctor in case of complaints.                                          |
| <b>After skin contact:</b>                                   | Remove contaminated clothing. Wash exposed area with soap and water.                             |
| <b>After eye contact:</b>                                    | Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. |
| <b>After swallowing:</b>                                     | Rinse mouth with water. Do not induce vomiting.                                                  |
| <b>Most important symptoms and effects:</b>                  | Dizziness                                                                                        |
| <b>Indication of any immediate medical attention needed:</b> | No further relevant information available.                                                       |

**5 Fire-fighting measures**

|                                               |                                                                                |
|-----------------------------------------------|--------------------------------------------------------------------------------|
| <b>Extinguishing agents:</b>                  | CO2, extinguishing powder or water spray. Fight larger fires with water spray. |
| <b>Special hazards:</b>                       | Can form explosive gas-air mixtures.                                           |
| <b>Protective equipment for firefighters:</b> | A respiratory protective device may be necessary.                              |

**6 Accidental release measures**

|                                                                             |                                                                              |
|-----------------------------------------------------------------------------|------------------------------------------------------------------------------|
| <b>Personal precautions, protective equipment and emergency procedures:</b> | Use respiratory protective device against the effects of fumes/dust/aerosol. |
| <b>Methods and material for containment and cleaning up:</b>                | Absorb liquid components with liquid-binding material.                       |

**7 Handling and storage**

|                                      |                                                                                                                  |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------|
| <b>Precautions for safe handling</b> | Use only in well ventilated areas.                                                                               |
| <b>Storage requirements:</b>         | Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. |

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

|           |                                                    |
|-----------|----------------------------------------------------|
| PEL (USA) | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm |
| REL (USA) | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm   |
| TLV (USA) | Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm |
|           | Long-term value: 594 mg/m <sup>3</sup> , 250 ppm   |
|           | A4, BEI                                            |

**74-98-6 propane**

|           |                                                    |
|-----------|----------------------------------------------------|
| PEL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| TLV (USA) | see Appendix F Minimal oxygen content ( D, EX)     |

**110-19-0 Isobutyl Acetate**

|           |                                                   |
|-----------|---------------------------------------------------|
| PEL (USA) | Long-term value: 700 mg/m <sup>3</sup> , 150 ppm  |
| REL (USA) | Long-term value: 700 mg/m <sup>3</sup> , 150 ppm  |
| TLV (USA) | Short-term value: 712 mg/m <sup>3</sup> , 150 ppm |
|           | Long-term value: 238 mg/m <sup>3</sup> , 50 ppm   |

**106-97-8 n-butane**

|           |                                                     |
|-----------|-----------------------------------------------------|
| REL (USA) | Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm   |
| TLV (USA) | Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm |
|           | (EX)                                                |

**64742-89-8 VM&P Naphtha**

|           |                          |
|-----------|--------------------------|
| TLV (USA) | Long-term value: 100 ppm |
|           | Skin, A3                 |

**64-17-5 ethyl alcohol**

|           |                                                     |
|-----------|-----------------------------------------------------|
| PEL (USA) | Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm  |
| REL (USA) | Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm  |
| TLV (USA) | Short-term value: 1880 mg/m <sup>3</sup> , 1000 ppm |
|           | A3                                                  |

**107-87-9 Methyl Propyl Ketone**

|           |                                                   |
|-----------|---------------------------------------------------|
| PEL (USA) | Long-term value: 700 mg/m <sup>3</sup> , 200 ppm  |
| REL (USA) | Long-term value: 530 mg/m <sup>3</sup> , 150 ppm  |
| TLV (USA) | Short-term value: 529 mg/m <sup>3</sup> , 150 ppm |

(Contd. on page 3)

## Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

Trade name: LIGHT GRAY PRIMER

(Contd. of page 2)

**67-63-0 Isopropyl Alcohol**

|           |                                                    |
|-----------|----------------------------------------------------|
| PEL (USA) | Long-term value: 980 mg/m <sup>3</sup> , 400 ppm   |
| REL (USA) | Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm |
|           | Long-term value: 980 mg/m <sup>3</sup> , 400 ppm   |
| TLV (USA) | Short-term value: 984 mg/m <sup>3</sup> , 400 ppm  |
|           | Long-term value: 491 mg/m <sup>3</sup> , 200 ppm   |
|           | BEI, A4                                            |

**108-65-6 PM acetate**

|            |                         |
|------------|-------------------------|
| WEEL (USA) | Long-term value: 50 ppm |
|------------|-------------------------|

**67-56-1 methanol**

|           |                                                   |
|-----------|---------------------------------------------------|
| PEL (USA) | Long-term value: 260 mg/m <sup>3</sup> , 200 ppm  |
| REL (USA) | Short-term value: 325 mg/m <sup>3</sup> , 250 ppm |
|           | Long-term value: 260 mg/m <sup>3</sup> , 200 ppm  |
|           | Skin                                              |
| TLV (USA) | Short-term value: 328 mg/m <sup>3</sup> , 250 ppm |
|           | Long-term value: 262 mg/m <sup>3</sup> , 200 ppm  |
|           | Skin; BEI                                         |

**Ingredients with biological limit values:****67-64-1 Acetone**

|           |                                  |
|-----------|----------------------------------|
| BEI (USA) | 25 mg/L                          |
|           | Medium: urine                    |
|           | Time: end of shift               |
|           | Parameter: Acetone (nonspecific) |

**67-63-0 Isopropyl Alcohol**

|           |                                              |
|-----------|----------------------------------------------|
| BEI (USA) | 40 mg/L                                      |
|           | Medium: urine                                |
|           | Time: end of shift at end of workweek        |
|           | Parameter: Acetone (background, nonspecific) |

**67-56-1 methanol**

|           |                                               |
|-----------|-----------------------------------------------|
| BEI (USA) | 15 mg/L                                       |
|           | Medium: urine                                 |
|           | Time: end of shift                            |
|           | Parameter: Methanol (background, nonspecific) |

**Hygienic protection:**

Immediately remove all soiled and contaminated clothing.  
Wash hands after use.  
Avoid contact with the eyes and skin.  
Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.  
The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties**

|                                         |                                                          |
|-----------------------------------------|----------------------------------------------------------|
| Physical state                          | Aerosol                                                  |
| Odor:                                   | Aromatic                                                 |
| Odor threshold:                         | Not determined.                                          |
| Melting point/Melting range             | Undetermined.                                            |
| Boiling point:                          | -44.5 °C (-48.1 °F)                                      |
| Flammability:                           | Extremely flammable.                                     |
| Lower Explosion Limit:                  | 1.7 Vol %                                                |
| Upper Explosion Limit:                  | 10.9 Vol %                                               |
| Flash point:                            | -19 °C (-2.2 °F)                                         |
| Flammability (solid, gas):              | Extremely flammable.                                     |
| Decomposition temperature:              | Not determined.                                          |
| pH-value:                               | Not determined.                                          |
| Viscosity:                              | Not determined.                                          |
| Solubility:                             | Not determined.                                          |
| Vapor pressure:                         | Not determined.                                          |
| Relative Density:                       | Between 0.77 and 0.85 (Water equals 1.00)                |
| Vapor density                           | Not determined.                                          |
| Particle characteristics                | Not applicable.                                          |
| Appearance:                             | Aerosol.                                                 |
| Ignition temperature:                   | Product is not self-igniting.                            |
| Danger of explosion:                    | In use, may form flammable/explosive vapour-air mixture. |
| Water:                                  | 0.0 %                                                    |
| Evaporation rate                        | Not applicable.                                          |
| Partition coefficient: n-octanol/water: | Not determined.                                          |

(Contd. on page 4)

## Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

Trade name: LIGHT GRAY PRIMER

(Contd. of page 3)

**10 Stability and reactivity**

|                                            |                                                                                                  |
|--------------------------------------------|--------------------------------------------------------------------------------------------------|
| <b>Reactivity:</b>                         | Stable at normal temperatures.                                                                   |
| <b>Conditions to avoid:</b>                | Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. |
| <b>Chemical stability:</b>                 | Not fully evaluated.                                                                             |
| <b>Possibility of hazardous reactions:</b> | No dangerous reactions known.                                                                    |
| <b>Incompatible materials:</b>             | No further relevant information available.                                                       |
| <b>Hazardous decomposition:</b>            | No dangerous decomposition products known.                                                       |

**11 Toxicological information****LD/LC50 values that are relevant for classification:****110-19-0 Isobutyl Acetate**

|      |      |                      |
|------|------|----------------------|
| Oral | LD50 | 4,763 mg/kg (rabbit) |
|------|------|----------------------|

**13463-67-7 titanium dioxide**

|            |          |                        |
|------------|----------|------------------------|
| Oral       | LD50     | >20,000 mg/kg (rat)    |
| Dermal     | LD50     | >10,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >6.82 mg/l (rat)       |

**64-17-5 ethyl alcohol**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 7,060 mg/kg (rat) |
| Inhalative | LC50/4 h | 20,000 mg/l (rat) |

**67-63-0 Isopropyl Alcohol**

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | 4,570 mg/kg (rat)  |
| Dermal     | LD50     | 13,400 mg/kg (rab) |
| Inhalative | LC50/4 h | 30 mg/l (rat)      |

**108-65-6 PM acetate**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 8,500 mg/kg (rat) |
| Inhalative | LC50/4 h | 35.7 mg/l (rat)   |

**67-56-1 methanol**

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | 5,628 mg/kg (rat)     |
| Dermal | LD50 | 15,800 mg/kg (rabbit) |

|                                              |                               |
|----------------------------------------------|-------------------------------|
| <b>Information on toxicological effects:</b> | No data available.            |
| <b>Skin effects:</b>                         | No irritant effect.           |
| <b>Eye effects:</b>                          | Irritating effect.            |
| <b>Sensitization:</b>                        | No sensitizing effects known. |

**12 Ecological information**

|                                       |                                                                                                                                                                                                                                          |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Aquatic toxicity:</b>              | Hazardous for water, do not empty into drains.                                                                                                                                                                                           |
| <b>Persistence and degradability:</b> | The product is degradable after prolonged exposure to natural weathering processes.                                                                                                                                                      |
| <b>Other information:</b>             | This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents. |
| <b>Bioaccumulative potential:</b>     | No further relevant information available.                                                                                                                                                                                               |
| <b>Mobility in soil:</b>              | No further relevant information available.                                                                                                                                                                                               |
| <b>Other adverse effects:</b>         | No further relevant information available.                                                                                                                                                                                               |

**13 Disposal considerations**

|                                     |                                                                                                                                                                                                                                       |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Disposal:</b>                    | Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. |
| <b>Recommendation:</b>              | Completely empty cans should be recycled.                                                                                                                                                                                             |
| <b>Recommended cleansing agent:</b> | Water, if necessary with cleansing agents.                                                                                                                                                                                            |

**14 Transport information**

|                                      |                       |
|--------------------------------------|-----------------------|
| <b>UN-Number</b>                     | UN1950                |
| <b>DOT</b>                           | UN1950                |
| <b>DOT</b>                           | Aerosols, flammable   |
| <b>ADR</b>                           | 1950 AEROSOLS         |
| <b>Transport hazard class(es):</b>   |                       |
| <b>Class</b>                         | 2.1 Gases             |
| <b>Special marking (IATA):</b>       |                       |
| <b>Packaging Group:</b>              | --                    |
| <b>Special precautions for user:</b> | Warning: Gases        |
| <b>EMS Number:</b>                   | F-D,S-U               |
| <b>UN "Model Regulation":</b>        | UN 1950 AEROSOLS, 2.1 |

(Contd. on page 5)

# Safety Data Sheet

Date of issue: 07/17/2025

Revised On 03/12/2025

Trade name: LIGHT GRAY PRIMER

(Contd. of page 4)

## 15 Regulatory information

### SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

### SARA Section 313 (Specific toxic chemical listings):

67-63-0 | Isopropyl Alcohol

### Toxic Substances Control Act (TSCA):

All ingredients are found on the inventory list of substances.

### Canadian Domestic Substances List (DSL):

All ingredients are listed or exempted.

### Consumer Product Safety Commission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

### California Proposition 65 chemicals known to cause cancer:

13463-67-7 | titanium dioxide

108-10-1 | methyl isobutyl ketone

100-41-4 | ethyl benzene

1333-86-4 | Carbon black

### Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 | methyl isobutyl ketone

67-56-1 | methanol

### EPA:

67-64-1 | Acetone

I

110-19-0 | Isobutyl Acetate

D

## 16 Other information

Contact: Regulatory Affairs