	Treviseu C	JII 00/10/2022	
1 Identification of the substance and manufacturer			
Trade name:	TRAFFIC WHITE		
Product code: Recommended use:	80-892 Paint and coatings application.		
Uses advised against:	Any that differs from the recommended use.		
Manufacturer/Supplier:	Kimball Midwest 4800 Roberts Road		
	Columbus, OH 43228		
	800-233-1294 www.kimballmidwest.com		
Emergency telephone number:	ChemTrec: 800-424-9300		
2 Hazard(s) identification	isture		
Classification of the substance or m Flammable Aerosols 1	H222 Extremely flammable aerosol.		
Gases under Pressure - Liquefied gas	H280 Contains gas under pressure; may explode if heated.		
Carcinogenicity 2	H351 Suspected of causing cancer. Route of exposure: Inhalation.		
Specific Target Organ Toxicity - Single			
	ted Exposure 2 H373 May cause damage to organs through prolonged or repeated exposu	ure.	
Additional information: GHS Hazard pictograms	$\land \land \land \land$		
	$\langle \underline{0} \rangle \langle - \rangle \langle \underline{1} \rangle \langle \underline{0} \rangle$		
	GHS02 GHS04 GHS07 GHS08		
Signal word	Danger		
Hazard statements	Extremely flammable aerosol.		
	Contains gas under pressure; may explode if heated. Suspected of causing cancer. Route of exposure: Inhalation.		
	May cause respiratory irritation.		
	May cause damage to organs through prolonged or repeated exposure.		
Precautionary statements	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces No smoking.		
	Do not spray on an open flame or other ignition source.		
	Pressuriżed container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.		
	Use only outdoors or in a well-ventilated area.		
	IF INHÁLED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.		
	Store locked up.		
	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regu	lations	
3 Composition/information on ing			
Chemical characterization: Mixtures Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.		
Dangerous components:			
64742-89-8 VM&P Naphtha		25-50%	
74-98-6 propane		10-15%	
13463-67-7 titanium dioxide		5-10%	
106-97-8 n-butane 7727-43-7 barium sulfate		5-10% 5-10%	
1317-65-3 Calcium Carbonate		5-10%	
64742-47-8 Mineral Spirits		1-5%	
4 First-aid measures			
After inhalation: After skin contact:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water.		
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.		
After swallowing:	Rinse out mouth and then drink plenty of water.		
Most important symptoms and	Rinse mouth with water. Do not induce vomiting.		

 Most important symptoms and effects:
 Dizziness

 Indication of any immediate medical attention needed:
 No further relevant information available.

5 Fire-fighting measures Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

Page 2/4

Printing date 06/10/2022	Revised On 06/10/2022			
Trade name: TRAFFIC WHITE				
Protective equipment for firefighters:	(Contd. of page 1) A respiratory protective device may be necessary.			
6 Accidental release measures				
Personal precautions, protective equipment and emergency procedures: Methods and material for containment and cleaning up:	Use respiratory protective device against the effects of fumes/dust/aerosol. Absorb liquid components with liquid-binding material.			
containment and cleaning up.				
7 Handling and storage				
Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.			
8 Exposure controls/personal prote	ection			
Components with limit values that re	equire monitoring at the workplace:			
74-98-6 propane				
PEL (USA) Long-term value: 1800 mg/ REL (USA) Long-term value: 1800 mg/				
TLV (USA) see Appendix F Minimal ox				
106-97-8 n-butane				
REL (USA) Long-term value: 1900 mg/				
TLV (USA) Short-term value: 1000 ppr (EX)	n			
7727-43-7 barium sulfate				
PEL (USA) Long-term value: 15* 5** m *total dust **respirable frac	ig/m ³			
REL (USA) Long-term value: 10* 5** m	ng/m³			
*total dust **respirable frac				
TLV (USA) Long-term value: 5* mg/m ³ *inhalable fraction; E				
Hygienic protection:	Immediately remove all soiled and contaminated clothing.			
	Wash hands after use. Avoid contact with the skin.			
	Avoid contact with the eyes and skin.			
Breathing equipment:	Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In			
	cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.			
Hand protection:	Nitrile gloves.			
Eye protection:	The glove material must be impermeable and resistant to the substance. Tightly sealed goggles			
9 Physical and chemical properties				
Appearance:	Aerosol.			
Odor: Odor threshold:	Aromatic Not determined.			
pH-value:	Not determined.			
Melting point/Melting range				
Boiling point:	-44 °C (-47.2 °F)			
Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.			
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not self-igniting.			
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.			
Lower Explosion Limit: Upper Explosion Limit:	1.7 Vol % 10.9 Vol %			
Vapor pressure:	Not determined.			
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)			
Vapor density Evaporation rate	Not determined. Not applicable.			
Partition coefficient: n-octonal/water	: Not determined.			
Solubility:	Not determined. (Contd. on page 3)			

Safety Data Sheet

Printing date 06/10/2022

Revised On 06/10/2022

Trade name: TRAFFIC WHITE	
Viscosity: Water:	Not determined. 18.0 %
10 Stability and reactivity	
Reactivity: Conditions to avoid: Chemical stability: Possibility of hazardous reactions:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. Not fully evaluated. No dangerous reactions known.
Incompatible materials: Hazardous decomposition:	No further relevant information available. No dangerous decomposition products known.
11 Toxicological information	
LD/LC50 values that are relevant for	classification:
13463-67-7 titanium dioxide	
Oral LD50 >20,000 mg/kg (r Dermal LD50 >10,000 mg/kg (r Inhalative LC50/4 h >6.82 mg/l (rat)	bt)
Information on toxicological effects Skin effects: Eye effects: Sensitization:	: No data available. Irritant to skin and mucous membranes. No irritating effect. No sensitizing effects known.
12 Ecological information	Hezerdeue fer weter, de net empty inte dreine
Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available. No further relevant information available.
13 Disposal considerations Dispose of in accordance with local, st disposed of responsibly. Do not heat or Recommendation:	tate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be r cut empty containers with electric or gas torches. Completely empty cans should be recycled.
14 Transport information	
14 Transport information UN-Number	UN1950
DOT	UN1950
DOT	DOT
ADR	Aerosols, flammable 1950 Aerosols
Transport hazard class(es):	
Class Marine pollutant:	2.1 Gases No
Special precautions for user: EMS Number: Packaging Group:	Warning: Gases F-D,S-U
UN "Model Regulation":	UN1950, Aerosols, 2.1
15 Regulatory information	
SARA Section 355 (extremely hazard	dous substances):
None of the ingredients in this product	
SARA Section 313 (Specific toxic ch	emical listings):
7727-43-7 barium sulfate	
Toxic Substances Control Act (TSCA): Canadian Domestic Substances List	All hazardous ingredients are found on the inventory list of substances.
(DSL): Consumer Product Safety	All ingredients are listed or exempted.
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. (Contd. on page 4)

Ľ

Revised On 06/10/2022

Trade name: TRAFFIC WHITI	5	
		(Contd. of page 3)
California Proposition	65 chemicals known to cause cancer:	
13463-67-7 titanium dio	xide	
100-41-4 ethyl benze	ne	
	wn to cause birth defects or reproductive harm:	
None of the ingredients i	s listed.	
EPA:		
7727-43-7 barium sulfat	e	D, CBD(inh), NL(oral)
16 Other information		
Contact:	Regulatory Affairs	