Date of issue: 03/12/2025 Revised On 03/12/2025

1 Identification of the substance and manufacturer

Trade name:

Other means of identification

80944 Product code:

Article category

Recommended use: Paint and coatings application.

Any that differs from the recommended use. Uses advised against:

Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228

800-233-1294

SCHOOL BUS YELLOW

www.kimballmidwest.com Emergency telephone number: ChemTrec: 800-424-9300



2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Eye irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms

Precautionary statements







GHS02 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

HMIS-ratings (0 - 4):

Health= Fire= Physical Hazard= 3 PPE----B

3 Composition/information on ingredients

Chemical characterization: Mixtures

are dust is a mixture of the substances listed below with perhapprocedure additions

Chemical Description:		Inis product is a mixture of the substances listed below with nonnazardous additions.	
Dangerous components:			
67-64-1	Acetone		15-25%
	propane		15-25%
7727-43-7	barium sulfate		5-10%
	n-butane		5-10%
	Isobutyl Acetate		5-10%
2807-30-9	Glycol Ether EP		≥5-<10%
123-86-4	butyl acetate		1-5%
108-65-6	PM acetate		1-5%
		(C	ontd. on page 2)

Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: SCHOOL BUS YELLOW

(Contd. of page 1) 1-5% 107-87-9 Methyl Propyl Ketone 13463-67-7 titanium dioxide 1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Indication of any immediate medical

Dizziness

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

Protective equipment for

firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective

equipment and emergency procedures:

Methods and material for

Use respiratory protective device against the effects of fumes/dust/aerosol.

containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure c	ontrols/personal protection			
Components with limit values that require monitoring at the workplace:				
67-64-1 Acetone				
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 590 mg/m³, 250 ppm			
TLV (USA)	Short-term value: 1187 mg/m³, 500 ppm			
	Long-term value: 594 mg/m³, 250 ppm			
	A4, BEI			
74-98-6 prop	ane			
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)			
7727-43-7 barium sulfate				
PEL (USA)	Long-term value: 15* 5** mg/m³			
` '	*totăl dust **respirable fraction			

PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction

Long-term value: 5* mg/m3 TLV (USA)

*inhalable fraction; E

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m³, 800 ppm
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm
	I(FX)

110-19-0 Isobutyl Acetate

PEL (USA)	Long-term value: 700 mg/m³, 150 ppm
REL (USA)	Long-term value: 700 mg/m³, 150 ppm
TLV (USA)	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm
` ,	Long-term value: 238 mg/m³, 50 ppm

123-86-4 butyl acetate

PEL (USA)	Long-term value: 710 mg/m³, 150 ppm
REL (USA)	Short-term value: 950 mg/m³, 200 ppm
, ,	Long-term value: 710 mg/m³, 150 ppm

(Contd. on page 3)

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: SCHOOL BUS YELLOW

(Contd. of page 2) TLV (USA)

Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

107-87-9 Methyl Propyl Ketone

PEL (USA) Long-term value: 700 mg/m³, 200 ppm REL (USA) Long-term value: 530 mg/m³, 150 ppm TLV (USA) Short-term value: 529 mg/m³, 150 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

Immediately remove all soiled and contaminated clothing. Hygienic protection:

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Nitrile gloves Hand protection:

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Physical state Aerosol Odor: Aromatic Odor threshold: Not determined. Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47.2 °F) Flammability: Extremely flammable.

Lower Explosion Limit: 1.7 Vol % Upper Explosion Limit: 10.9 Vol % Flash point: -19 °C (-2.2 °F) Extremely flammable. Flammability (solid, gas): **Decomposition temperature:** Not determined. pH-value: Viscosity: Not determined. Not determined. Solubility: Not determined. Vapor pressure: Not determined.

Between 0.77 and 0.85 (Water equals 1.00) **Relative Density:**

Vapor density Not determined. Particle characteristics Not applicable.

Appearance: Aerosol.

Ignition temperature: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

0.0 % Water:

Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known. Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:
110-19-0 Isobutyl Acotato

LD50 4,763 mg/kg (rbt) 123-86-4 butyl acetate

Oral

14,000 mg/kg (rat) Oral LD50 Inhalative LC50/4 h >21 mg/l (rat)

(Contd. on page 4)

Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: SCHOOL BUS YELLOW

(Contd. of page 3)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

13463-67-7 titanium dioxide

>20,000 mg/kg (rat) Oral LD50 LD50 Dermal

>10,000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eve effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Persistence and degradability: Hazardous for water, do not empty into drains.

The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Recommendation: Completely empty cans should be recycled.

Water, if necessary with cleansing agents. Recommended cleansing agent:

14 Transport information

UN-Number UN1950 DOT UN1950 DOT DOT

Aerosols, flammable

ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 Gases

Marine pollutant: No

Special marking (IATA): Packaging Group:

Special precautions for user:

Warning: Gases F-D,S-Ŭ EMS Number:

UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

Toxic Substances Control Act

(TSCA): All ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

108-10-1 methyl isobutyl ketone

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64-1 Acetone 7727-43-7 barium sulfate D, CBD(inh), NL(oral) 110-19-0 Isobutyl Acetate D

Page 5/5

Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: SCHOOL BUS YELLOW

HOOL BOS YELLOW

(Contd. of page 4)

16 Other information

Contact: Regulatory Affairs

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.