Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

## 1 Identification of the substance and manufacturer

Trade name: SANDABLE BLACK PRIMER

Other means of identification

Product code: 80-1102

Article category

Recommended use: Paint and coatings application.

Any that differs from the recommended use. Uses advised against:

Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228

800-233-1294

www.kimballmidwest.com ChemTrec: 800-424-9300 **Emergency telephone number:** 

# 2 Hazard(s) identification

#### Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Eye irritation 2A H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 



Danger



GHS02 GHS07 GHS08

Signal word

**Hazard statements** Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store in a well ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

|           |                       | The production of this constant of the production of the productio |         |  |
|-----------|-----------------------|--|---------|--|
| Dangerou  | Dangerous components: |  |         |  |
|           | Acetone               |  | 25-50%  |  |
|           | propane               |  | 15-25%  |  |
| 67-63-0   | Isopropyl Alcohol     |  | 10-15%  |  |
|           | n-butane              |  | 5-10%   |  |
|           | methyl ethyl ketone   |  | ≥5-<10% |  |
| 2807-30-9 | Glycol Ether EP       |  | 1-5%    |  |
| 108-65-6  | PM acetate            |  | 1-5%    |  |
| 557-05-1  | zinc stearate         |  | 1-5%    |  |

### 4 First-aid measures

After swallowing:

Most important symptoms and

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact:

Rinse mouth with water. Do not induce vomiting.

effects:

Dizziness

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: SANDABLE BLACK PRIMER

Indication of any immediate medical

No further relevant information available.

5 Fire-fighting measures

attention needed:

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

Protective equipment for

firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Methods and material for Use respiratory protective device against the effects of fumes/dust/aerosol.

containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

| 8 Exposure co | ntrols/p | personal | protec | tion |
|---------------|----------|----------|--------|------|
|---------------|----------|----------|--------|------|

| Components with limit values that require monitoring at the workplace: |
|--|
|  |

| 6/ | -6 | 4-1 | ΙA | cet | one |
|----|----|-----|----|-----|-----|
|    |    |     |    |     |     |

Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm PEL (USA) REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm TLV (USA) Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

A4, BEI

#### 74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

see Appendix F Minimal oxygen content (D, EX) TLV (USA)

# 67-63-0 Isopropyl Alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm Short-term value: 1225 mg/m³, 500 ppm REL (USA) Long-term value: 980 mg/m³, 400 ppm

Short-term value: 984 mg/m³, 400 ppm TLV (USA) Long-term value: 491 mg/m³, 200 ppm BEI. A4

#### 106-97-8 n-butane REL (USA)

Long-term value: 1900 mg/m³, 800 ppm Short-term value: 2370 mg/m³, 1000 ppm TLV (USA)

# 78-93-3 methyl ethyl ketone

PEL (USA) Long-term value: 590 mg/m<sup>3</sup>, 200 ppm REL (USA) Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

Short-term value: 150 ppm TLV (USA)

Long-term value: 75 ppm BEI, Skin

#### 108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

#### 557-05-1 zinc stearate

PEL (USA) Long-term value: 15\* 5\*\* mg/m3 \*totăl dust \*\*respirable fraction

Long-term value: 10\* 5\*\* mg/m³ \*total dust \*\*respirable fraction REL (USA)

Long-term value: 10\* 3\*\* mg/m³
\*inhalable, \*\*respirable particulate matter, \*A4 TLV (USA)

### Ingredients with biological limit values:

#### 67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: SANDABLE BLACK PRIMER

67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

78-93-3 methyl ethyl ketone

BEI (USA) 2 mg/L Medium: urine

Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)

Immediately remove all soiled and contaminated clothing. Hygienic protection:

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In **Breathing equipment:** 

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

# 9 Physical and chemical properties

Physical state Aerosol Odor: Aromatic Odor threshold: Not determined. Melting point/Melting range Undetermined. Boiling point: Flammability: -44.5 °C (-48.1 °F Extremely flammable. **Lower Explosion Limit:** 1.7 Vol %

12 Vol % -19 °C (-2.2 °F) Upper Explosion Limit: Flash point: Flammability (solid, gas): Extremely flammable. Decomposition temperature: Not determined. pH-value: Not determined. . Viscositv: Not determined. Solubility: Not determined. Vapor pressure: Not determined. **Relative Density:** 

Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Particle characteristics Not applicable. Appearance: Aerosol.

Ignition temperature:

Product is not self-igniting. Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

Water: 0.0 %

**Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined.

# 10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

### 11 Toxicological information

| LD/LC50 values that are relevant for classification: |                                    |  |  |
|--|------------------------------------|--|--|
| 67-63-0 Isopropyl Alcohol                            |                                    |  |  |
| )ral   | LD50                               | 4,570 mg/kg (rat)                      |  |
| )ermal   | LD50                               | 13,400 mg/kg (rab)                     |  |
| nhalative  | LC50/4 h                           | 30 mg/l (rat)                          |  |
| )  | <b>7-63-0 Is</b><br>Pral<br>Permal | <b>7-63-0 Isopropyl A</b><br>Oral LD50 |  |

#### 78-93-3 methyl ethyl ketone

| Oral   | LD50 | 3,300 mg/kg (rat) |
|--------|------|-------------------|
| Dermal | LD50 | 5,000 mg/kg (rbt) |

#### 108-65-6 PM acetate

|            |          | 8,500 mg/kg (rat) |
|------------|----------|-------------------|
| Inhalative | LC50/4 h | 35.7 mg/l (rat)   |

Information on toxicological effects: No data available.

(Contd. on page 4)

(Contd. of page 3)

# Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: SANDABLE BLACK PRIMER

Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes. Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl

substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

### 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Recommendation: Completely empty cans should be recycled.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

**UN-Number** UN1950 DOT UN1950

DOT Aerosols, flammable ADR 1950 AEROSOLS

Transport hazard class(es):

Class 2.1 Gases

Special marking (IATA):

Packaging Group:

Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ŭ

UN "Model Regulation": **UN 1950 AEROSOLS, 2.1** 

# 15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0 Isopropyl Alcohol 557-05-1 zinc stearate

**Toxic Substances Control Act** 

(TSCA):

All ingredients are found on the inventory list of substances. Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

67-64-1 Acetone

78-93-3 methyl ethyl ketone 557-05-1 zinc stearate D, I, II

16 Other information

Contact: Regulatory Affairs