

## Safety Data Sheet

Printing date 06/09/2022

Revised On 06/09/2022

## 1 Identification of the substance and manufacturer

**Trade name:** RED SELF ETCH PRIMER  
**Product code:** 80-1103  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.  
**Manufacturer/Supplier:** Kimball Midwest  
 4800 Roberts Road  
 Columbus, OH 43228  
 800-233-1294  
 www.kimballmidwest.com  
**Emergency telephone number:** ChemTrec: 800-424-9300

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.  
 Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.  
 Eye Irritation 2A H319 Causes serious eye irritation.  
 Sensitization - Skin 1 H317 May cause an allergic skin reaction.  
 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.  
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

## Additional information:

## GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

## Signal word

## Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 May cause an allergic skin reaction.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 If eye irritation persists: Get medical advice/attention.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## Precautionary statements

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

67-64-1	Acetone	15-25%
74-98-6	propane	10-15%
106-97-8	n-butane	5-10%
110-19-0	Isobutyl Acetate	5-10%
67-63-0	Isopropyl Alcohol	≥5-<10%
78-92-2	Secondary Butyl Alcohol	≥5-<10%
79-20-9	methyl acetate	≥5-<10%
540-88-5	tert-butyl acetate	1-5%
64742-47-8	Mineral Spirits	1-5%
64742-95-6	Solvent naphtha, light aromatic	1-5%
108-31-6	maleic anhydride	0.04%

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
 (Contd. on page 2)

## Safety Data Sheet

Printing date 06/09/2022

Revised On 06/09/2022

Trade name: RED SELF ETCH PRIMER

(Contd. of page 1)

**After swallowing:** Rinse mouth with water. Do not induce vomiting.  
**Most important symptoms and effects:** Dizziness  
**Indication of any immediate medical attention needed:** No further relevant information available.

**5 Fire-fighting measures**

**Extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.  
**Special hazards:** Can form explosive gas-air mixtures.  
**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Use respiratory protective device against the effects of fumes/dust/aerosol.  
**Methods and material for containment and cleaning up:** Absorb liquid components with liquid-binding material.

**7 Handling and storage**

**Precautions for safe handling:** Use only in well ventilated areas.  
**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm  
REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm  
TLV (USA) Short-term value: 500 ppm  
Long-term value: 250 ppm  
A4, BEI

**74-98-6 propane**

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm  
TLV (USA) see Appendix F Minimal oxygen content ( D, EX)

**106-97-8 n-butane**

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm  
TLV (USA) Short-term value: 1000 ppm  
(EX)

**110-19-0 Isobutyl Acetate**

PEL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppm  
REL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppm  
TLV (USA) Short-term value: 150 ppm  
Long-term value: 50 ppm

**67-63-0 Isopropyl Alcohol**

PEL (USA) Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
REL (USA) Short-term value: 1225 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
TLV (USA) Short-term value: 400 ppm  
Long-term value: 200 ppm  
BEI, A4

**78-92-2 Secondary Butyl Alcohol**

PEL (USA) Long-term value: 450 mg/m<sup>3</sup>, 150 ppm  
REL (USA) Short-term value: 455 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 305 mg/m<sup>3</sup>, 100 ppm  
TLV (USA) Long-term value: 100 ppm

**79-20-9 methyl acetate**

PEL (USA) Long-term value: 610 mg/m<sup>3</sup>, 200 ppm  
REL (USA) Short-term value: 760 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 610 mg/m<sup>3</sup>, 200 ppm  
TLV (USA) Short-term value: 250 ppm  
Long-term value: 200 ppm

(Contd. on page 3)

## Safety Data Sheet

Printing date 06/09/2022

Revised On 06/09/2022

Trade name: RED SELF ETCH PRIMER

(Contd. of page 2)

**540-88-5 tert-butyl acetate**

PEL (USA) Long-term value: 950 mg/m<sup>3</sup>, 200 ppm  
 REL (USA) Long-term value: 950 mg/m<sup>3</sup>, 200 ppm  
 TLV (USA) Short-term value: 150 ppm  
 Long-term value: 50 ppm

**108-31-6 maleic anhydride**

PEL (USA) Long-term value: 1 mg/m<sup>3</sup>, 0.25 ppm  
 REL (USA) Long-term value: 1 mg/m<sup>3</sup>, 0.25 ppm  
 TLV (USA) Long-term value: 0.01\* mg/m<sup>3</sup>  
 DSEN, RSEN;\*inh. fraction + vapor, A4

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA) 25 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

**67-63-0 Isopropyl Alcohol**

BEI (USA) 40 mg/L  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Acetone (background, nonspecific)

**Hygienic protection:** Immediately remove all soiled and contaminated clothing.  
Wash hands after use.

**Breathing equipment:** Avoid contact with the eyes and skin.  
Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

**Eye protection:** Tightly sealed goggles

**9 Physical and chemical properties**

**Appearance:** Aerosol.  
**Odor:** Aromatic  
**Odor threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/Melting range** Undetermined.  
**Boiling point:** -44 °C (-47.2 °F)  
**Flash point:** -19 °C (-2.2 °F)  
**Flammability (solid, gas):** Extremely flammable.  
**Decomposition temperature:** Not determined.  
**Auto igniting:** Product is not self-igniting.  
**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
**Lower Explosion Limit:** 1.7 Vol %  
**Upper Explosion Limit:** 10.9 Vol %  
**Vapor pressure:** Not determined.  
**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)  
**Vapor density** Not determined.  
**Evaporation rate** Not applicable.  
**Partition coefficient: n-octanol/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

(Contd. on page 4)

## Safety Data Sheet

Printing date 06/09/2022

Revised On 06/09/2022

Trade name: RED SELF ETCH PRIMER

(Contd. of page 3)

## 11 Toxicological information

## LD/LC50 values that are relevant for classification:

## 110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rbt)

## 67-63-0 Isopropyl Alcohol

Oral LD50 4,570 mg/kg (rat)

Dermal LD50 13,400 mg/kg (rab)

Inhalative LC50/4 h 30 mg/l (rat)

## 78-92-2 Secondary Butyl Alcohol

Oral LD50 6,480 mg/kg (rat)

## 79-20-9 methyl acetate

Oral LD50 6,970 mg/kg (rat)

Information on toxicological effects: No data available.

Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

## 12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Other adverse effects: No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

## 14 Transport information

UN-Number UN1950

DOT UN1950

DOT DOT

ADR Aerosols, flammable

Transport hazard class(es): 1950 Aerosols

Class 2.1 Gases

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group: --

UN "Model Regulation": UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

## SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

## SARA Section 313 (Specific toxic chemical listings):

67-63-0 Isopropyl Alcohol

78-92-2 Secondary Butyl Alcohol

7779-90-0 zinc phosphate

## Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

## Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

## Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

## California Proposition 65 chemicals known to cause cancer:

cumene

## Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

(Contd. on page 5)

## Safety Data Sheet

Printing date 06/09/2022

Revised On 06/09/2022

**Trade name: RED SELF ETCH PRIMER**

(Contd. of page 4)

**EPA:**

67-64-1	Acetone	I
110-19-0	Isobutyl Acetate	D
7779-90-0	zinc phosphate	D, I, II

**16 Other information****Contact:** Regulatory Affairs