### 1 Identification of the substance and manufacturer Trade name: **Gloss Black Brite-Coat 2** 80-1560 Product code: Paint and coatings application. Recommended use: Uses advised against: Any that differs from the recommended use. Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228 800-233-1294 www.kimballmidwest.com ChemTrec: 800-424-9300 **Emergency telephone number:** 2 Hazard(s) identification Classification of the substance or mixture Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Skin Irrititation 2 H315 Causes skin irritation. Eye Irritation 2A H319 Causes serious eye irritation. Toxic to Reproduction 1B H360 May damage fertility or the unborn child. H336 May cause drowsiness or dizziness. Specific Target Organ Toxicity - Single Exposure 3 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. Additional information: **GHS Hazard pictograms** GHS02 GHS04 GHS07 GHS08 Signal word Danger Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May damage fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 Composition/information on ingredients Chemical characterization: Mixtures Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions. Dangerous components: 67-64-1 Acetone 15-25% 15-25% 74-98-6 propane 64742-89-8 VM&P Naphtha 10-15% 106-97-8 n-butane 10-15% 142-82-5 heptane 10-15% 108-88-3 Toluene 1-5% **4 First-aid measures**

After inhalation: After skin contact: Supply fresh air; consult doctor in case of complaints. Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

After eye contact: After swallowing:

Page 2/4

	Revised OII 00/09/2022
Trade name: GLOSS BLACK	
Most important symptoms and effects: Indication of any immediate medica attention needed:	(Contd. of page 1) Dizziness I No further relevant information available.
5 Fire-fighting measures Extinguishing agents: Special hazards: Protective equipment for	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.
firefighters:	A respiratory protective device may be necessary.
6 Accidental release measures	
Personal precautions, protective	
equipment and emergency procedures:	Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Dispose contaminated material as waste according to section 13.
7 Handling and storage Precautions for safe handling Storage requirements:	Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.
8 Exposure controls/personal prot	tection
	require monitoring at the workplace:
67-64-1 Acetone	equite monitoring at the workplace.
PEL (USA) Long-term value: 2400 mg	g/m³, 1000 ppm
REL (USA) Long-term value: 590 mg/ TLV (USA) Short-term value: 500 ppr Long-term value: 250 ppr A4, BEI	n
74-98-6 propane	
PEL (USA) Long-term value: 1800 mg	
REL (USA) Long-term value: 1800 mg	
TLV (USA) see Appendix F Minimal o 106-97-8 n-butane	xygen content ( D, EX)
REL (USA) Long-term value: 1900 mg	a/m³ 800 ppm
TLV (USA) Short-term value: 1000 pp (EX)	om
142-82-5 heptane	
PEL (USA) Long-term value: 2000 mg REL (USA) Long-term value: 350 mg/ Ceiling limit value: 1800* *15-min	m <sup>3</sup> , 85 ppm
TLV (USA) Short-term value: 500 ppr Long-term value: 400 ppr	n 1
108-88-3 Toluene	
PEL (USA) Long-term value: 200 ppm Ceiling limit value: 300; 50 *10-min peak per 8-hr shit	00* ppm
REL (USA) Short-term value: 560 mg Long-term value: 375 mg/	/m³, 150 ppm
TLV (USA) Long-term value: 20 ppm BEI, OTO, A4	
Ingredients with biological limit val	ues:
67-64-1 Acetone	
BEI (USA) 25 mg/L Medium: urine Time: end of shift	
Parameter: Acetone (nons	pecific) (Contd. on page 3)
	(

Revised On 06/09/2022

## Trade name: GLOSS BLACK

		(Contd. of page 2)			
108-88-3 T	108-88-3 Toluene				
BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of Parameter: Toluene	workweek			
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with I	hydrolysis (background)			
Hygienic p		Immediately remove all soiled and contaminated clothing. Wash hands after use. Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.			
Breathing	equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.			
Hand prot		Nitrile gloves. The glove material must be impermeable and resistant to the substance.			
Eye protec		Tightly sealed goggles			

# 9 Physical and chemical properties

9 Physical and chemical properties	
Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.1 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.

# 10 Stability and reactivity Reactivity: Stable at normal temperatures. Orgoditivity: Depart of human temperatures.

Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition:	Not fully evaluated.

# 11 Toxicological information Information on toxicological effects: No data available. Skin effects: Irritant to skin and mucous membranes. Eye effects: Irritating effect. Sensitization: No sensitizing effects known.

Aquatic toxicity: Persistence and degradability: Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. (Contd. on page 4)

EPA:

67-64-1 Acetone 142-82-5 heptane

**16 Other information** 

Contact:

Page 4				
Printing date 06/09/2022	R	evised On 06/09/2022		
Trade name: GLOSS BLACK				
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlor (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium) solvents.	(Contd. of page 3) rofluorocarbons ), or chlorinated		
Bioaccumulative potential: Mobility in soil: Remark:	No further relevant information available. No further relevant information available. Toxic for fish			
Other adverse effects:	No further relevant information available.			
13 Disposal considerations         Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.         Recommendation:       Completely empty cans should be recycled.				
14 Transport information				
UN-Number DOT DOT	UN1950 UN1950 DOT Aerosols, flammable			
ADR Transport hazard class(es): Class Marine pollutant:	1950 Aerosols, 2.1 Gases Yes Symbol (fish and tree)			
Special precautions for user: EMS Number: Packaging Group:	Warning: Gases F-D,S-U			
UN "Model Regulation":	UN1950, Aerosols, 2.1			
15 Regulatory information				
SARA Section 355 (extremely hazard	deue euhetenees)			
None of the ingredients in this product				
SARA Section 313 (Specific toxic ch				
108-88-3 Toluene	iemica notingoj.			
Toxic Substances Control Act		]		
(TSCA): Canadian Domestic Substances Lis	All hazardous ingredients are found on the inventory list of substances.			
(DSL):	All ingredients are listed or exempted.			
Consumer Product Safety Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm o	of lead.		
California Proposition 65 chemicals	s known to cause cancer:			
1333-86-4 Carbon black				
100-41-4 ethyl benzene				

I D

Prop 65 chemicals known to cause birth defects or reproductive harm: 108-88-3 Toluene

Regulatory Affairs