## Safety Data Sheet

Printing date 06/09/2022 Revised On 06/09/2022

### 1 Identification of the substance and manufacturer

Trade name: Gloss Red Brite-Coat 2

80-1564 Product code:

Paint and coatings application. Recommended use:

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Kimball Midwest 4800 Roberts Road Columbus, OH 43228 800-233-1294

www.kimballmidwest.com ChemTrec: 800-424-9300 **Emergency telephone number:** 

#### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Skin Irrititation 2 H315 Causes skin irritation. Eye Irritation 2A H319 Causes serious eye irritation.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child. H336 May cause drowsiness or dizziness. Specific Target Organ Toxicity - Single Exposure 3

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 







Signal word Danger

**Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation. Causes serious eye irritation.

May damage fertility or the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use. **Precautionary statements** 

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions

Cileillicai D	escription.	This product is a mixture of the substances listed below with normazardous additions.	
Dangerous components:			
			15-25%
74-98-6	propane		15-25%
106-97-8	n-butane		10-15%
64742-89-8	VM&P Naphtha		10-15%
142-82-5	heptane		10-15%
108-88-3	Toluene		≥5-<10%
	Dangerous 67-64-1 74-98-6 106-97-8 64742-89-8 142-82-5	Dangerous components:   67-64-1   Acetone   74-98-6   propane   106-97-8   n-butane   64742-89-8   VM&P Naphtha   142-82-5   heptane   108-88-3   Toluene	Dangerous components:           67-64-1         Acetone           74-98-6         propane           106-97-8         n-butane           64742-89-8         VM&P Naphtha           142-82-5         heptane

### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints. Immediately wash with water and soap and rinse thoroughly. After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact:

Rinse out mouth and then drink plenty of water. After swallowing:

Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 06/09/2022 Revised On 06/09/2022

Trade name: RED

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

**Extinguishing agents:** 

Special hazards:

firefighters:

Protective equipment for

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV (USA) Short-term value: 500 ppm

Long-term value: 250 ppm

A4, BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) | Short-term value: 1000 ppm

(EX)

142-82-5 heptane

PEL (USA) Long-term value: 2000 mg/m³, 500 ppm

REL (USA) Long-term value: 350 mg/m<sup>3</sup>, 85 ppm

Ceiling limit value: 1800\* mg/m³, 440\* ppm

\*15-mi̇̀n

TLV (USA) Short-term value: 500 ppm

Long-term value: 400 ppm

108-88-3 Toluene

PEL (USA)

Long-term value: 200 ppm Ceiling limit value: 300; 500\* ppm

\*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

Long-term value: 20 ppm BEI, OTO, A4 TLV (USA)

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific) (Contd. on page 3)

(Contd. of page 2)

Printing date 06/09/2022 Revised On 06/09/2022

Trade name: RED

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

Immediately remove all soiled and contaminated clothing. Hygienic protection:

Wash hands after use.

Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In **Breathing equipment:** cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Aerosol. Odor: Odor threshold: Aromatic Not determined. pH-value: Not determined.

Melting point/Melting range Undetermined. -44 °C (-47.2 °F) **Boiling point:** Flash point: -19 °C (-2.2 °F) Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

**Lower Explosion Limit:** 1.1 Vol % 10.9 Vol % **Upper Explosion Limit:** Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing Conditions to avoid:

temperatures. Not fully evaluated.

Chemical stability: Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

(Contd. on page 4)

D

# Safety Data Sheet

Printing date 06/09/2022 Revised On 06/09/2022

Trade name: RED

(Contd. of page 3)

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: Mobility in soil:

No further relevant information available. No further relevant information available. Toxic for fish

Remark:

Other adverse effects: No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

### 14 Transport information

**UN-Number** UN1950 UN1950 DOT DOT DOT

Aerosols, flammable 1950 Aerosols,

Transport hazard class(es):

2.1 Gases Class Yes

Marine pollutant: Symbol (fish and tree)

Special precautions for user: Warning: Gases

F-D,S-U EMS Number:

Packaging Group: UN "Model Regulation": UN1950, Aerosols, 2.1

### 15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

## SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

**Toxic Substances Control Act** 

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List (DSL):

Consumer Product Safety

All ingredients are listed or exempted.

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

67-64-1 Acetone

142-82-5 heptane

## 16 Other information

Contact: Regulatory Affairs