#### 1 Identification of the substance and manufacturer Trade name: **KB ORANGE** 80-838 Product code: Paint and coatings application. Recommended use: Any that differs from the recommended use. Uses advised against: Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228 800-233-1294 www.kimballmidwest.com ChemTrec: 800-424-9300 **Emergency telephone number:** 2 Hazard(s) identification Classification of the substance or mixture Flammable Aerosols 1 H222 Extremely flammable aerosol. Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Eye Irritation 2A H319 Causes serious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure. Additional information: **GHS Hazard pictograms** GHS02 GHS04 GHS07 GHS08 Signal word Danger Hazard statements Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. Route of exposure: Inhalation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). If eye irritation persists: Get medical advice/attention. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations. 3 Composition/information on ingredients Chemical characterization: Mixtures This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description: Dangerous components: 67-64-1 Acetone 15-25% 74-98-6 propane 15-25% 106-97-8 n-butane 5-10% 7727-43-7 barium sulfate 5-10% 110-19-0 Isobutyl Acetate 5-10% 2807-30-9 Glycol Ether EP ≥5-<10% 108-65-6 PM acetate 1-5% 123-86-4 butyl acetate 1-5% 1-5% 107-87-9 Methyl Propyl Ketone **4 First-aid measures**

After inhalation: After skin contact: After eye contact:

Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 2)

Safety Data Sheet

Printing date 06/09/2022

L

Revised On 06/09/2022

Printing date 06/09/202	Printing date 06/09/2022 Revised On 06/09/2022			
Trade name: KB ORANGE				
After ewaller	wina.	(Contd. of page 1) (Contd. of page 1)		
After swallowing:		Rinse mouth with water. Do not induce vomiting.		
Most import effects:	ant symptoms and	Dizziness		
Indication of	f any immediate medical			
attention nee	eded:	No further relevant information available.		
5 Fire-fightin	•	CO2, extinguishing powder or water aprov. Fight larger fires with water aprov		
Extinguishing agents: Special hazards:		CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.		
Protective e	quipment for			
firefighters:		A respiratory protective device may be necessary.		
6 Assidantal	release measures			
	ecautions, protective			
equipment a	ind emergency			
procedures:	d material for	Use respiratory protective device against the effects of fumes/dust/aerosol.		
	t and cleaning up:	Absorb liquid components with liquid-binding material.		
	V P	· · · · · ·		
7 Handling a	nd storage			
Precautions	for safe handling	Use only in well ventilated areas.		
Storage requ	uirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.		
8 Exposure c	ontrols/personal prot	ection		
-		equire monitoring at the workplace:		
67-64-1 Acet		equire monitoring at the workplace.		
PEL (USA)	Long-term value: 2400 n	ng/m <sup>3</sup> , 1000 ppm		
REL (USA)	Long-term value: 590 m	g/m³, 250 ppm		
TLV (USA)	Short-term value: 500 pp	om		
	Long-term value: 250 pp A4, BEI	im in the second se		
74-98-6 prop				
PEL (USA)	Long-term value: 1800 n			
REL (USA)	Long-term value: 1800 n			
TLV (USA) 106-97-8 n-b	see Appendix F Minimal	oxygen content ( D, EX)		
REL (USA)	Long-term value: 1900 n	ng/m³ 800 ppm		
TLV (USA)	Short-term value: 1000 p			
. ,	(EX)			
7727-43-7 ba		t		
PEL (USA)	Long-term value: 15* 5** *total dust **respirable fi	raction		
REL (USA)	Long-term value: 10* 5*	* ma/m³		
	*total dust **respirable fi			
TLV (USA)	Long-term value: 5* mg/ *inhalable fraction; E	m~		
110-19-0 Iso	butyl Acetate			
PEL (USA)	Long-term value: 700 m			
REL (USA)	Long-term value: 700 m			
TLV (USA)	Short-term value: 150 pp Long-term value: 50 pp	om n		
108-65-6 PM				
	Long-term value: 50 ppr	n		
123-86-4 but				
PEL (USA)	Long-term value: 710 m	g/m³, 150 ppm		
REL (USA)	Short-term value: 950 m Long-term value: 710 m	g/m³, 200 ppm g/m³ 150 ppm		
TLV (USA)	Short-term value: 150 pr			
. ,	Long-term value: 50 ppr	n		
	thyl Propyl Ketone			
PEL (USA)	Long-term value: 700 m	g/m³, 200 ppm (Contd. on page 3)		
		(Contd. on page 3)		

Revised On 06/09/2022

Page 3/4

Trade name: KB ORANGE				
	(Contd. of page 2)			
REL (USA) Long-term value: 530 m TLV (USA) Short-term value: 150 p				
Ingredients with biological limit value	Ies:			
67-64-1 Acetone				
BEI (USA) 25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonsp	pecific)			
Hygienic protection:	Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin.			
Breathing equipment:	Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.			
Hand protection: Eye protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance. Tightly sealed goggles			
9 Physical and chemical properties				
Appearance: Odor: Odor threshold:	Aerosol. Aromatic Not determined.			
pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. -44 °C (-47.2 °F)			
Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.			
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not self-igniting.			
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.7 Vol % 10.9 Vol %			
Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/wate	Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. r: Not determined.			
Solubility: Viscosity: Water:	Not determined. Not determined. 0.0 %			
10 Stability and reactivity				
Reactivity: Conditions to avoid: Chemical stability: Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. Not fully evaluated. No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.			
11 Toxicological information				
LD/LC50 values that are relevant for	classification:			
110-19-0 Isobutyl Acetate   Oral LD50 4,763 mg/kg (rbt)				
108-65-6 PM acetate				
Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)				
123-86-4 butyl acetate				
Oral LD50 14,000 mg/kg (ra Inhalative LC50/4 h >21 mg/l (rat)	t)			
Information on toxicological effects Skin effects:	No irritant effect.			
Eye effects:	Irritating effect. (Contd. on page 4)			

Printing date 06/09/2022

Revised On 06/09/2022

Page 4/4

#### Trade name: KB ORANGE

Sensitization:	No sensitizing effects known. (Contd. of page	e 3)	
12 Ecological information			
Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbo (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinat solvents.	natural weathering processes. rbons (CFC's), hydrochlorofluorocarbons chromium, lead, cadmium), or chlorinated	
Bioaccumulative potential: Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available. No further relevant information available.		

# **13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. **Recommendation:** Completely empty cans should be recycled.

# **14 Transport information**

UN-Number DOT DOT	UN1950 UN1950 DOT Aerosols, flammable
ADR Transport hazard class(es):	1950 Aerosols
Class	2.1 Gases No
Marine pollutant: Special precautions for user: EMS Number:	Warning: Gases F-D.S-U
Packaging Group: UN "Model Regulation":	

# **15 Regulatory information**

re Regulatory micrimation					
SARA Section 355 (extremely hazardous substances):					
None of the ingredients in this product are listed.					
SARA Section 313 (Specific toxic chemical listings):					
7727-43-7 barium sulfate					
Toxic Substances Control Act (TSCA):	All hazardous ingredients are found on the inventory list of substances.				
	All ingredients are listed or exempted.				
<u>, , , , , , , , , , , , , , , , , </u>	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.				
California Proposition 65 chemicals known to cause cancer:					
13463-67-7 titanium dioxide					
108-10-1 methyl isobutyl ketone					
100-41-4 ethyl benzene					
Prop 65 chemicals known to cause birth defects or reproductive harm:					
108-10-1 methyl isobutyl ketone					
EPA:					
67-64-1 Acetone					
7727-43-7 barium sulfate	D, CBD(inh), NL(oral)				
110-19-0 Isobutyl Acetate	D				
16 Other information					

Contact:

**Regulatory Affairs**