

The following SDS references the product below:

SGH2J- Super Glue

Vendor Item Number: SGH2J- Super Glue

Manufactured By:

Pacer Technology

Distributed by Kimball Midwest with the KM product-
identification number:

80-197



SAFETY DATA SHEET



Date Issued : 10/10/2014
SDS No : 11710346_SGH2J-48
Date Revised : 03/30/2020
Revision No : 16

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: SUPER GLUE TUBE 2GR (48)

PRODUCT CODE: 11710346_SGH2J-48

MANUFACTURER

Pacer Technology
3281 E. Guasti Road, Suite 260
Ontario, CA 91761

Emergency Contact: Chemtrec

Emergency Phone: (800) 424-9300

Customer Service: (909) 987-0550

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Eye Irritation, Category 2A
Skin Irritation, Category 2
Target Organ Toxicity (Single exposure), Category 3
Skin Sensitization, Category 1

Physical:

Flammable Liquids, Category 4

GHS LABEL

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H227: Combustible liquid.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash skin and hands thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.

SAFETY DATA SHEET



Date Issued : 10/10/2014
SDS No : 11710346_SGH2J-48
Date Revised : 03/30/2020
Revision No : 16

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P313: Get medical advice/attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P362: Take off contaminated clothing.

P370: In case of fire: Use dry chemical, foam or carbon dioxide to extinguish.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED: Skin contact through clothing may cause burns.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
ETHYL-2-CYANOACRYLATE	85 - 100	7085-85-0
Polymethyl methacrylate	10 - 30	9011-14-7
Hydroquinone	< 0.1	123-31-9

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Peel or roll skin apart.

INGESTION: Peel or roll skin apart. Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment. Not a toxic product.

INHALATION: Remove to fresh air. Prolonged or repeated elevated exposure may cause allergic reactions with asthma-like symptoms in sensitive individuals.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes serious eye irritation. Will bond eyelids. Will cause excessive tearing.

SKIN: Bonds skin in seconds. May cause skin irritation. May cause sensitization by skin contact. Cyanoacrylates generate heat on polymerization, so very large amounts will burn the skin.

INGESTION: Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Not a toxic product.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Avoid exposure to vapor concentration in confined areas.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

SAFETY DATA SHEET



Date Issued : 10/10/2014
SDS No : 11710346_SGH2J-48
Date Revised : 03/30/2020
Revision No : 16

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: Combustible liquid and vapor. Product polymerized to solid by water.

EXTINGUISHING MEDIA: Use dry chemical extinguisher or flush with large amounts of water.

HAZARDOUS COMBUSTION PRODUCTS: Can burn in fire, releasing irritating vapors

EXPLOSION HAZARDS: None known.

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

FIRE EXPLOSION: None known.

SENSITIVE TO STATIC DISCHARGE: None known.

SENSITIVITY TO IMPACT: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide/dioxide.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Polymerize with water. Solid material may be scraped from surface.

LARGE SPILL: Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid breathing (dust, vapor, mist, gas).

STORAGE: Store in a cool place in original container and protect from sunlight.

STORAGE TEMPERATURE: Ideal storage: 41-50F (5-10C)

SHELF LIFE: One year from the date of shipment from Pacer Technology, unless otherwise noted.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m ³
ETHYL-2-CYANOACRYLATE	OSHA PEL	TWA	[1]	[1]
	ACGIH TLV	TWA	0.2	1.0
		STEL	[2]	0.3 ppm [2]
	Supplier OEL	TWA	0.2 ppm	
Hydroquinone	OSHA PEL	TWA		2

Footnotes:

1. NL = Not Listed
2. 1.5 mg/m³

ENGINEERING CONTROLS: Use only in a well ventilated area. Local exhaust ventilation may be necessary to control any air

SAFETY DATA SHEET



Date Issued : 10/10/2014
SDS No : 11710346_SGH2J-48
Date Revised : 03/30/2020
Revision No : 16

contaminants to within their TLVs during the use of this product.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Use Nitrile gloves and aprons to prevent contact. Do not use PVC, Nylon or Cotton materials.

RESPIRATORY: Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: Full-face NIOSH-approved respirator with organic vapor cartridge.

WORK HYGIENIC PRACTICES: Avoid direct contact and breathing vapor. Use with adequate ventilation. Wash hands with soap and water after use.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Characteristic odor, intensely irritating.

ODOR THRESHOLD: Odor Threshold = 1 ppm

APPEARANCE: Transparent, colorless liquid.

pH: Not Established

PERCENT VOLATILE: No data available

FLASH POINT AND METHOD: 80°C (176°F) to 93.4°C (200°F) TAG CC

FLAMMABLE LIMITS: Not Established

AUTOIGNITION TEMPERATURE: 485°C (905°F)

VAPOR PRESSURE: < 0.2 mm Hg

VAPOR DENSITY: No data available

BOILING POINT: > 149°C (300°F)

FREEZING POINT: No data available

MELTING POINT: No data available

THERMAL DECOMPOSITION: Not Established

SOLUBILITY IN WATER: Insoluble

PARTITION COEFFICIENT: N-OCTANOL/WATER: No data available

EVAPORATION RATE: No data available

DENSITY: Not Established

SPECIFIC GRAVITY: 1.06 g/mL at 25°C

VISCOSITY #1: 25 to 50 Centipoise at 22°C (72°F)

MOLECULAR WEIGHT: Not Established

(VOC): < 20.00 g/L Per SCAQMD Method 316B.

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: No

CONDITIONS TO AVOID: Avoid temperatures above 176° F (80° C), moisture and alkalines.

SAFETY DATA SHEET



Date Issued : 10/10/2014
SDS No : 11710346_SGH2J-48
Date Revised : 03/30/2020
Revision No : 16

POSSIBILITY OF HAZARDOUS REACTIONS: Possible polymerization reaction in the presence of water, amines, alkalis and alcohols.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition. Oxides of nitrogen and probably hydrogen cyanide are also possible.

INCOMPATIBLE MATERIALS: Polymerized by water, alcohol, amines, alkaline materials.

COMMENTS: REACTIVITY: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀
ETHYL-2-CYANOACRYLATE	> 5000 mg/kg	> 2000 mg/kg
Hydroquinone	367.3 mg/kg	> 2000 mg/kg

DERMAL LD₅₀: > 2000 mg/kg

Notes: (Estimated)

ORAL LD₅₀: > 5000 mg/kg

Notes: (Estimated)

INHALATION LC₅₀: Vapors may be irritating. Recommended TWA 0.2ppm.

RESPIRATORY OR SKIN SENSITISATION: Possible skin sensitizer.

CARCINOGENICITY

IARC: None

NTP: None

OSHA: None

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA:

This material should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in a manner consistent with federal, state, and local regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: NOT REGULATED

AIR (ICAO/IATA)

SHIPPING NAME: ID8000, CONSUMER COMMODITY, 9 (PKG LESS THAN OR EQUAL TO 30 kg G); or UN3334, AVIATION REGULATED LIQUID, N.O.S (ETHYL CYANOACRYLATE), 9, III (LTD QTY, IP VOL LESS THAN OR EQUAL TO 5.0 L, OP WGT LESS THAN OR EQUAL TO 30 kg G) *

VESSEL (IMO/IMDG)

SAFETY DATA SHEET



Date Issued : 10/10/2014
SDS No : 11710346_SGH2J-48
Date Revised : 03/30/2020
Revision No : 16

SHIPPING NAME: NOT REGULATED

COMMENTS: * This product may be shipped as EXCEPTED QUANTITIES OF CLASS 9, UN3334 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN OR EQUAL TO 1.0 L)

The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HEALTH HAZARDS: Immediate Health, Delayed Health, Fire, Reactive.

313 REPORTABLE INGREDIENTS: None above reporting de minimus.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: None above reporting de minimus.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
ETHYL-2-CYANOACRYLATE	7085-85-0
Polymethyl methacrylate	9011-14-7
Hydroquinone	123-31-9

TSCA STATUS: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

CLEAN AIR ACT

40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION: Not applicable.

CALIFORNIA PROPOSITION 65: Consumer sizes of this product do not require a California Proposition 65 Warning based on potential exposure in normal consumer use. The following information applies to industrial use: **⚠ WARNING:** This product can expose you to chemicals including Sulfur Dioxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Affairs Department

PREPARED BY: Pacer Technology Regulatory Affairs Department **Date Revised:** 03/30/2020

REVISION SUMMARY: This SDS replaces the 08/15/2018 SDS. Revised: **Section 1:** APPROVED BY, PREPARED BY, PRODUCT CODE.

SAFETY DATA SHEET




Date Issued : 10/10/2014
SDS No : 11710346_SGH2J-48
Date Revised : 03/30/2020
Revision No : 16

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY		2
PHYSICAL HAZARD		1
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.