



SAFETY DATA SHEET

Issuing date 18-Mar-2020

Revision Date 15-Jul-2026

Version 1.03

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 80-1558 QUART ACRY-MAXX

Other means of identification

Product code 801558

Product Type Highly Flammable Liquid and Vapor
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use MULTI-PURPOSE SOLVENT.

Uses advised against No information available

Manufactured For:

Kimball Midwest
4800 Roberts Rd.
Columbus, OH 43228
800-233-1294

Emergency telephone number

Chemical Emergency Phone NumberCHEMTREC :
1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation
 Causes serious eye irritation
 Suspected of causing cancer
 Suspected of damaging fertility or the unborn child
 May cause respiratory irritation. May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 May cause damage to organs (Eyes, Skin, Respiratory System, Central Nervous System, and Hearing ,) through prolonged or repeated exposure.
 Highly flammable liquid and vapor



Appearance Clear **Physical state** Liquid **Odor** Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection
 Do not breathe dust, fumes, gas, mist, vapors, spray.
 Wash face, hands and any exposed skin thoroughly after handling
 Use only outdoors or in a well-ventilated area
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground and bond container and receiving equipment
 Use explosion-proof electrical, ventilating and lighting equipment
 Use only non-sparking tools
 Take action to prevent static discharges

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific treatment (see first aid on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Keep cool
Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Hazards not otherwise classified (HNOX)

Not applicable

Other information

No information available.

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
PETROLEUM DISTILLATES	64742-89-8	65-85
XYLENE	1330-20-7	10-30
N-OCTANE	111-65-9	3-7
HEPTANE	142-82-5	3-7
ETHYL BENZENE	100-41-4	1-5
TOLUENE	108-88-3	0.1-1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures****General advice**

Avoid contact with eyes, skin, and clothing. Avoid contact with eyes, skin, and clothing.
Avoid breathing vapors, mist, or gas.

Eye contact

Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.

Skin contact

If on skin (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower for a minimum of 15 minutes. If skin irritation persists, call a physician.
Remove and wash contaminated clothing before re-use.

Inhalation

Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.

Ingestion Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Protection of First-aiders Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Main Symptoms Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Dry chemical. Carbon dioxide (CO₂). Cool containers / tanks with water spray. Alcohol resistant foam, Water fog, Dry chemical powder, Carbon dioxide.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Highly Flammable/Flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Should not be released into the environment.

Methods and material for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter,

non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up. Keep cool.

Incompatible products

Strong acids, alkalis, oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
XYLENE 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	Not Established
N-OCTANE 111-65-9	TWA: 300 ppm	TWA: 500 ppm TWA: 2350 mg/m ³ (vacated) TWA: 300 ppm (vacated) TWA: 1450 mg/m ³ (vacated) STEL: 375 ppm (vacated) STEL: 1800 mg/m ³	IDLH: 1000 ppm Ceiling: 385 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 75 ppm TWA: 350 mg/m ³
HEPTANE 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
ETHYL BENZENE 100-41-4	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
TOLUENE 108-88-3	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)
NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tightly fitting safety goggles.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid
Appearance Clear
Color Clear

Odor
Odor Threshold Solvent

Property

Values

Remarks • Method

pH	No information available	Based on lowest flashpoint of the products constituents. Closed cup
Melting/freezing point	No information available	
Boiling point/boiling range	No information available	
Flash Point	10 °C / 50 °F	
Relative Evaporation rate (butyl acetate=1)	No information available	
Flammability	Highly Flammable Liquid	
Vapor pressure	No information available	
Relative Vapor density at 20°C	No information available	
Relative Density	0.770	
Water solubility	Practically insoluble	
Partition coefficient: n-octanol/water	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Viscosity, Kinematic	No information available	
Viscosity, Dynamic	No information available	
Explosive limits	No information available	
Explosive properties	No information available	
Oxidizing properties	Not Ozidizing	
Particle Characteristics		Not Applicable

Other information

VOC Content(%) 100

10. STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage conditions

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Strong acids, alkalis, oxidizing agents.

Hazardous decomposition products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	May cause respiratory irritation, May cause drowsiness or dizziness.
Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
N-OCTANE 111-65-9	-	-	> 24.88 mg/L (Rat) 4 h
HEPTANE 142-82-5	-	= 3000 mg/kg (Rabbit)	> 73.5 mg/L (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Causes skin and serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause respiratory irritation. May cause damage to organs (listed below) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Eye damage/irritation	Irritating to eyes.
Sensitization	Not a known sensitizer.
Germ cell mutagenicity	Not a germ cell mutagen.
Carcinogenicity	The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
XYLENE 1330-20-7	-	Group 3	-	-
ETHYL BENZENE	A3	Group 2B	-	X

100-41-4				
TOLUENE 108-88-3	-	Group 3	-	-

Legend:

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A4 - Not Classifiable as a Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity

Product is or contains a chemical which is a known or suspected reproductive hazard.

Specific target organ systemic toxicity (single exposure)

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ systemic toxicity (repeated exposure)

May cause damage to Target Organs listed below through prolonged or repeated exposure.

Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

Target organ effects

Eyes, Ears, Skin, Respiratory system, Central nervous system.

Neurological effects

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

The following ATE values have been calculated for the mixture

ATEmix (oral) 8,333.30 mg/kg

ATEmix (dermal) 50,000.00 mg/kg ppm mg/l

ATEmix (inhalation-dust/mist) 9.79 mg/l

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

ATEmix (inhalation-vapor) 286.5 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
PETROLEUM DISTILLATES 64742-89-8	EC50: =4700mg/L (72h, Pseudokirchneriella subcapitata)	-	-	-
XYLENE 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)

		LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)		
N-OCTANE 111-65-9	-	-	-	EC50: =0.38mg/L (48h, water flea)
HEPTANE 142-82-5	-	LC50: =375.0mg/L (96h, Cichlid fish)	-	-
ETHYL BENZENE 100-41-4	EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)	-	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)
TOLUENE 108-88-3	EC50: >433mg/L (96h, Pseudokirchneriella subcapitata) EC50: =12.5mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 15.22 - 19.05mg/L (96h, Pimephales promelas) LC50: =12.6mg/L (96h, Pimephales promelas) LC50: 5.89 - 7.81mg/L (96h, Oncorhynchus mykiss) LC50: 14.1 - 17.16mg/L (96h, Oncorhynchus mykiss) LC50: =5.8mg/L (96h, Oncorhynchus mykiss) LC50: 11.0 - 15.0mg/L (96h, Lepomis macrochirus) LC50: =54mg/L (96h, Oryzias latipes) LC50: =28.2mg/L (96h, Poecilia reticulata) LC50: 50.87 - 70.34mg/L (96h, Poecilia reticulata)	-	EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) EC50: =11.5mg/L (48h, Daphnia magna)

Persistence and degradability**Bioaccumulation**

Chemical name	Partition coefficient
XYLENE 1330-20-7	3.15
N-OCTANE 111-65-9	5.18
HEPTANE 142-82-5	4.66
ETHYL BENZENE 100-41-4	3.6
TOLUENE 108-88-3	2.73

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods

Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground

LIMITED QUANTITY

IATA

UN1993, FLAMMABLE LIQUIDS, N.O.S (PETROLEUM DISTILLATES, XYLENE), 3, PG II, LTD. QTY.

IMDG

UN1993, FLAMMABLE LIQUIDS, N.O.S (PETROLEUM DISTILLATES, XYLENE), 3, PG II, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	X	X	X	X	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
N-OCTANE	X	X	X	X	X	X	X	X
HEPTANE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
XYLENE - 1330-20-7	1330-20-7	10-30	1.0
ETHYL BENZENE - 100-41-4	100-41-4	1-5	0.1
TOLUENE - 108-88-3	108-88-3	0.1-1	1.0
BENZENE - 71-43-2	71-43-2	<0.1	0.1
NAPHTHALENE - 91-20-3	91-20-3	<0.1	0.1
CUMENE - 98-82-8	98-82-8	<0.1	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
TOLUENE 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
TOLUENE 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical name	California Proposition 65
---------------	---------------------------

ETHYL BENZENE - 100-41-4	Cancer/ 1-5%
TOLUENE - 108-88-3	Developmental / 0.1-1%
BENZENE - 71-43-2	Carcinogen Developmental Male Reproductive/ <0.1%
NAPHTHALENE - 91-20-3	Cancer / <0.1%
CUMENE - 98-82-8	Cancer / <0.1%

Note

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM DISTILLATES 64742-89-8			X
XYLENE 1330-20-7	X	X	X
N-OCTANE 111-65-9	X	X	X
HEPTANE 142-82-5	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
TOLUENE 108-88-3	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 3	Instability 0	Special hazards -
HMIS	Health hazards 2*	Flammability 3	Physical hazards 0	Personal protection B

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By	Regulatory Affairs
Issuing date	18-Mar-2020
Revision Date	15-Jul-2026
Revision Note	

Disclaimer

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

End of Safety Data Sheet