

# SAFETY DATA SHEET

## 1. Product And Company Identification

**GHS product identifier:** Ultra-Can RTV Original Formula Silicone Gasket  
**Other means of identification:** 801047 80796 801049 80802 801050 801048 80803 801051 80965

**Relevant identified uses of the substance or mixture and uses advised against:**  
Silicone sealant

**Supplier's details:** Kimball Midwest  
4800 Roberts Road  
Columbus, OH 43228  
Corporate Telephone: 800.233.1294

**Emergency telephone number:** CHEMTREC, **24 hours/day, 7 days/  
week**  
U.S.: 1-800-424-9300  
International: +1-703-527-3887

**SDS Date of Preparation:** 07/19/2024

## 2. Hazards Identification

### GHS Classification:

Physical:	Health:
Aerosol Category 3	Non-Hazardous

### GHS Label Elements:

### Warning!

Statements of Hazard	Precautionary phrases
Pressurized container: may burst if heated.	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

## 3. Composition/Information on Ingredients

Component	CAS No.	Amount
1,1-Difluoroethane	75-37-6	<1%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First Aid Measures

**Inhalation:** If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problem or irritation persists.

# SAFETY DATA SHEET

**Skin Contact:** Wash exposed skin with soap and water for several minutes. If skin irritation develops, seek medical attention.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice or attention.

**Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

**Most Important Symptoms:** Vapors may cause mild respiratory irritation.

**Indication of Immediate Medical Attention/Special Treatment:** None known.

## 5. Firefighting Measures

**Suitable (and Unsuitable) Extinguishing Media:** Use extinguishing media suitable for surrounding fire.

**Specific Hazards Arising from the Chemical:** Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce silicon oxides, carbon oxides. Exposure of containers to heat and flames can cause them to rupture often with violent force.

**Special Fire Fighting Procedures:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

## 6: Accidental Release Measures

**Personal Precautions, Protective Equipment, and Emergency Procedures:** Ventilate the area. Wear appropriate protective clothing and equipment.

**Methods and Materials for Containment and Clean-Up:** Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

**Environmental Precautions:** Report release as required by local and national regulations.

## 7. Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes and skin. Avoid breathing vapors or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store in a cool, dry, well-ventilated area, away from strong oxidizers and other incompatible materials. Do not store in direct sunlight or above 120°F.

**U.F.C. (NFPA 30B) Level 1 Aerosol.**

## 8. Exposure Controls / Personal Protection

**Exposure Guidelines:**

CHEMICAL	EXPOSURE LIMIT
1,1-Difluoroethane	1000 ppm TWA AIHA WEELs

# SAFETY DATA SHEET

**Appropriate Engineering Controls:** General ventilation should be adequate for normal use. For operations where the exposure limits may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

## Personal Protective Equipment

**Respiratory Protection:** None under normal use conditions. For operations where the exposure limits may be exceeded, a NIOSH approved supplied air respirators recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

**Gloves:** Impervious gloves recommended to avoid skin contact.

**Eye Protection:** Safety glasses are recommended if eye contact is possible.

**Other Protective Equipment/Clothing:** None required.

## 9. Physical and Chemical Properties

**Appearance and Odor:** Clear viscous paste with acetic acid odor.

<b>Physical State:</b> Thick liquid under pressure	<b>Odor Threshold:</b> Not determined
<b>pH:</b> Not determined	<b>Specific Gravity:</b> 1.007 (Liquid component)
<b>Initial Boiling Point/Range:</b> Not determined	<b>Vapor Pressure:</b> Not determined
<b>Melting/Freezing Point:</b> Not determined	<b>Relative Vapor Density:</b> (Air = 1) Not determined
<b>Solubility In Water:</b> Not determined	<b>Percent Volatile:</b> Not determined
<b>Kinematic Viscosity:</b> Not determined	<b>Evaporation Rate:</b> (n-butyl acetate = 1.0): Not determined
<b>Decomposition Temperature:</b> Not available	<b>VOC Content:</b> Not determined
<b>Coefficient Of Water/Oil Distribution:</b> Not determined	<b>Autoignition Temp:</b> Not determined
<b>Flash Point:</b> > 100 °C (> 212 °F) CC (Liquid component)	<b>Flame extension:</b> Not determined
<b>Flammability Limits:</b> LEL: Not applicable UEL: Not applicable	<b>Flammability:</b> Not applicable
<b>Particle Characteristics:</b> Not applicable	

## 10. Stability and Reactivity

**Reactivity:** Not normally reactive

**Chemical Stability:** Stable under normal storage and handling conditions

**Possibility of Hazardous Reactions:** None expected.

**Conditions to Avoid:** Keep away from excessive heat, and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

**Incompatible Materials:** Strong oxidizing agents, strong bases, and strong acids.

**Hazardous Decomposition Products:** Burning may produce silicon oxides; carbon oxides.

## 11. Toxicological Information

### Potential Health Effects:

#### Acute Hazards:

**Inhalation:** Vapors can irritate the throat and respiratory tract.

# SAFETY DATA SHEET

**Skin Contact:** May cause mild irritation.

**Eye Contact:** May cause mild irritation.

**Ingestion:** Swallowing may cause gastrointestinal disturbances.

**Chronic Effects:** None expected.

**Carcinogenicity Listing:** None of the components listed is a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA

## **Numerical Measures of Toxicity:**

1,1-Difluoroethane: LC50 Inhalation Rat: 437,500ppm/4h

## **12. Ecological Information**

### **Ecotoxicity:**

1,1-Difluoroethane: LC50 Fish 719.61 mg/L/ 96hr (Calculated)

**Persistence and Degradability:** No data available for product.

**Bio accumulative Potential:** No data available for product.

**Mobility in Soil:** No data available for product.

**Other Adverse Effects:** No data available

## **13. Disposal Considerations**

Dispose of in accordance with all local, state/provincial, and federal regulations. Offer empty containers for recycling.

## **14. Transport Information**

**DOT Hazardous Materials Description:** UN1950, Aerosols, 2.2 LTD QTY

**IMDG Dangerous Goods Description:** UN1950, Aerosols 2.2 LTD QTY

## **15. Regulatory Information**

### **United States:**

**EPA TSCA INVENTORY:** All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

**CERCLA Section 103:** This product has no RQ, however, oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state, and local regulations.

**SARA Hazard Category (311/312):** Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

**SARA 313:** This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): None

# SAFETY DATA SHEET

**California Proposition 65:** This product does not contain substances known to the state of California to cause cancer and/or reproductive toxicity.

<b>16. Other Information</b>
------------------------------

REVISION DATE: 07/19/2024

REVISION SUMMARY: General review and update: Updated to OSHA HCS 2024.  
Changes to Sections 2, 9 & 15.

DATE OF PREVIOUS REVISION: 05/25/2021

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.