

Version 1.4 Revision Date 12/09/2022

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : High Strength Torque-Lok Bullet™

Product code : 80-143

Manufacturer or supplier's details

Company : Kimball Midwest

4800 Roberts Road

Address : Columbus, OH 43228

Telephone : 800.233.1294

Emergency Phone Number (CHEMTREC): 1-800-424-9300

## Recommended use of the chemical and restrictions on use

Recommended use : Anaerobic Cure Adhesive

Restrictions on use : For industrial use only.

#### **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid
Color	red
Odor	characteristic

#### **GHS Classification**

Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitization : Category 1

Specific target organ toxicity - : Category 3 (Respiratory system)

single exposure

**GHS** label elements

Hazard pictograms :



Signal Word : Warning

## **Hazard Statements:**

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Version 1.4

Revision Date 12/09/2022

## **Precautionary Statements:**

**Prevention:** P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection. **Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

**Storage:** P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store

locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

#### **Potential Health Effects**

Carcinogenicity:

**IARC** Group 2B: Possibly carcinogenic to humans

cumene 98-82-8

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Reasonably anticipated to be a human carcinogen

cumene 98-82-8

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous ingredients**

Chemical name	CAS-No.	Concentration [%]
2-phenoxyethyl methacrylate	10595-06-9	30 - 50
Poly(oxy-1,2-ethanediyl), .alpha(2-methyl-1-oxo-2-propenyl)omega[(2-methyl-1-oxo-2-	25852-47-5	30 - 50
propenyl)oxy]-		
methacrylic acid, monoester with propane-1,2-diol	27813-02-1	30 - 50
α,α-dimethylbenzyl hydroperoxide	80-15-9	0.1 - 1
cumene	98-82-8	0.1 - 1
2'-phenylacetohydrazide	114-83-0	0.1 - 1
maleic acid	110-16-7	0.1 - 1

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Show this material safety data sheet to the doctor in

attendance.

Cyberbond™ 7262

Version 1.4 Revision Date 12/09/2022

If inhaled : Move to fresh air.

Keep patient warm and at rest.

Consult a physician after significant exposure.

In case of skin contact : Wash off immediately with soap and plenty of water.

Call a physician if irritation develops or persists.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids.

Seek medical advice.

If swallowed, call a poison control center or doctor

immediately.

Do not induce vomiting without medical advice.

**SECTION 5. FIRE-FIGHTING MEASURES** 

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: Water spray jet

Hazardous combustion

products

: Nitrogen oxides (NOx)

Specific extinguishing

methods

Sulfur oxides

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

**SECTION 6. ACCIDENTAL RELEASE MEASURES** 

Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

: Ventilate the area.

eaning up Soak up with inert absorbent material.

Shovel or sweep up.

**SECTION 7. HANDLING AND STORAGE** 

Local/Total ventilation : Use only with adequate ventilation.

Version 1.4 Revision Date 12/09/2022

Advice on safe handling : Wear personal protective equipment.

Do not get on skin or clothing. Keep away from heat and flame.

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-

ventilated place.

Store in original container.

Materials to avoid : Do not store together with oxidizing and self-igniting products.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
cumene	98-82-8	TWA	5 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0
		PEL	50 ppm 245 mg/m3	CAL PEL

# Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Neoprene gloves

Nitrile rubber

butyl-rubber

Eye protection : Tightly fitting safety goggles

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Long sleeved clothing

Preventive skin protection

Version 1.4 Revision Date 12/09/2022

Protective measures : Avoid contact with skin.

Hygiene measures : Avoid contact with skin, eyes and clothing.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid Color : red

Odor : characteristic
Odor Threshold : no data available
pH : is not determined
Melting point/freezing point : is not determined
Boiling point/boiling range : is not determined
Flash point : Not applicable
Evaporation rate : is not determined

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Vapor pressure : is not determined

Density

Solubility(ies)
Water solubility

: 1.06 g/cm3
: is not determined

Partition coefficient: n-

octanol/water

: no data available

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : is not determined

## **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : The product is chemically stable.

Hazardous decomposition

products

: Nitrogen oxides (NOx)

Sulfur oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Version 1.4 Revision Date 12/09/2022

## **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

**Components:** 

 $\alpha,\alpha$ -dimethylbenzyl hydroperoxide:

Acute oral toxicity : LD50 Oral Rat: 382 mg/kg

Acute inhalation toxicity : LC50 Rat: 220 ppm

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal Rat: 500 mg/kg

cumene:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

maleic acid:

Acute oral toxicity : LD50 Oral Rat: 708 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,560 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

Version 1.4 Revision Date 12/09/2022

No data available

## STOT-repeated exposure

No data available

## **Aspiration toxicity**

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

## **Components:**

methacrylic acid, monoester with propane-1,2-diol:

Toxicity to fish : LC50 (Fish): 493 mg/l

Exposure time: 48 h Test Method: static test

α,α-dimethylbenzyl hydroperoxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l

Exposure time: 96 h
Test Method: static test

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 7 mg/l

Exposure time: 24 h Test Method: static test

cumene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.7 mg/l

Exposure time: 96 h

Test Method: semi-static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 0.6 mg/l

Exposure time: 48 h Test Method: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 2.6 mg/l

Exposure time: 72 h

Test Type: flow-through test

maleic acid:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5 mg/l

Exposure time: 96 h Test Method: static test

## Persistence and degradability

No data available

**Bioaccumulative potential** 

Version 1.4

Revision Date 12/09/2022

## Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : Do not dispose of together with household waste.

Do not dispose of waste into sewer.

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more

restrictive requirements.

#### **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

### IATA-DGR

Not regulated as a dangerous good

# IMDG-Code

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **Domestic regulation**

## 49 CFR

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

SARA 311/312 Hazards : Respiratory or skin sensitization

Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Version 1.4 Revision Date 12/09/2022

**SARA 302** : This material does not contain any components with a section 302

EHS TPQ.

**SARA 313** : The following components are subject to reporting levels established

by SARA Title III, Section 313:

2-phenoxyethyl methacrylate 10595-06-9 1,2-benzisothiazol-3(2H)-one 1,1- 81-07-2

dioxide

cumene 98-82-8

#### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

2-phenoxyethyl methacrylate 10595-06-9 cumene 98-82-8

## **US State Regulations**

California Prop 65 Please contact Supplier for more information.

## The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory

IECSC On the inventory, or in compliance with the inventory Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)


# **SECTION 16. OTHER INFORMATION**

Prepared by: Regulatory

Version 1.4

Revision Date 12/09/2022

#### **Further information**



Special hazard

#### HMIS III:

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.