

Issuing date 11-Nov-2015

Revision Date 27-Oct-2022

Version 1.04

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product identifier****Product name** TORQ 2 PENETRATING OIL**Recommended use of the chemical
and restrictions on use****Product code** 80-921**Product Type** Extremely Flammable Aerosol
Synonyms None**Supplier's details****Recommended Use** Penetrating Oil.**Uses advised against** No information available**Manufactured For:**Kimball Midwest
4800 Roberts Rd.
Columbus, OH 43228
800-233-1294**Emergency telephone number****Chemical Emergency Phone Number** 1-800-424-9300**Company Emergency Phone
Number** 1-800-233-1294

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation. May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Extremely Flammable Aerosol
Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling.
Wear protective gloves, eye protection, face protection.
Avoid breathing fumes, gas, mist, vapors, spray.
Use only outdoors or in a well-ventilated area.
Keep away from heat, sparks, open flames, hot surfaces - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

Specific treatment (see first aid on this label).
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice, attention
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice, attention.
Take off contaminated clothing and wash it before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor, physician if you feel unwell.
IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
Distillates (petroleum), hydrotreated Light	64742-47-8	20-30
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
NAPHTHENIC OIL, SEVERELY HYDROTREATED	64742-52-5	10-20
ACETONE	67-64-1	10-20
HYDROCARBON SOLVENT	64742-96-7	10-20
MINERAL OIL, DEWAXED	64742-65-0	1-10

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water for 15 minutes and seek medical advice.
Skin contact	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.
Protection of First-aiders	Remove all sources of ignition.

Most important symptoms/effects, acute and delayed

Main Symptoms	Causes skin and serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
----------------------	--

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers. In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods for cleaning up Soak up with inert absorbent material. Contain liquid and collect with an inter, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly . After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkali , or oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Distillates (petroleum), hydrotreated Light 64742-47-8	TWA: 200 PPM 8 hours	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8: TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5: TWA: 800 ppm TWA: 1900 mg/m ³
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
MINERAL OIL, DEWAXED 64742-65-0	ACGIH TLV: 5 mg/m ³ (oil mist)	OSHA PEL: 5 mg/m ³ (oil mist)	-
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
DIETHYL PHTHALATE 84-66-2	TWA: 5 mg/m ³	(vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures

Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits. Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol		
Appearance	Clear	Odor	Solvent
Color	Amber	Odor Threshold	

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH	No information available	No information available
Melting/freezing point	No information available	
Boiling point/boiling range		
Flash Point	-97 °C / -142 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	0.772	
Water solubility	Practically insoluble	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

Other information

VOC Content(%)	22.78
-----------------------	-------

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

Incompatible Materials

Strong acids, alkali , or oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

Inhalation	May cause respiratory irritation, May cause drowsiness or dizziness.
Eye contact	Causes serious eye irritation.

Skin contact	Causes skin irritation.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated Light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
NAPHTHENIC OIL, SEVERELY HYDROTREATED 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
ACETONE 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
HYDROCARBON SOLVENT 64742-96-7	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
MINERAL OIL, DEWAXED 64742-65-0	-	-	> 2400 mg/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause respiratory irritation. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Eye damage/irritation Irritating to eyes.
Sensitization Not a known sensitizer.
Germ cell mutagenicity Not a germ cell mutagen.
Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
MINERAL OIL, DEWAXED 64742-65-0	A2	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity This product does not contain any known or suspected reproductive hazards.
Specific target organ systemic toxicity (single exposure) May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ systemic toxicity (repeated exposure) None known.
Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects Skin, Eyes, Respiratory System, and Central Nervous System.
Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2617 mg/kg

ATEmix (dermal) 7509 mg/kg

ATEmix (inhalation-gas) 198334 mg/l
 ATEmix (inhalation-dust/mist) 245.6 mg/l
 ATEmix (inhalation-vapor) 19.7 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Distillates (petroleum), hydrotreated Light 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
NAPHTHENIC OIL, SEVERELY HYDROTREATED 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
MINERAL OIL, DEWAXED 64742-65-0	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h

Persistence and degradability

Bioaccumulation

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
ACETONE 67-64-1	-0.24

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods

Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Do not re-use empty containers. Empty containers should be taken to an approved waste handling site for recycling or disposal. Pressurized container: Do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

DOT Ground

LIMITED QUANTITY

IATA

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD .QTY.

IMDG

UN1950, AEROSOLS, 2.1, LTD.QTY

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Distillates (petroleum), hydrotreated Light	X	X	X	Not listed	X	X	X	X
PROPANE/ISOBUTANE/N-BUTANE	X	X	X	x	X	X	X	X
NAPHTHENIC OIL, SEVERELY HYDROTREATED	X	X	X	Not listed	X	X	X	X
ACETONE	X	X	X	X	X	X	X	X
HYDROCARBON SOLVENT	X	X	X	Not listed	X	X	X	X
MINERAL OIL, DEWAXED	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain chemical(s) known to the State of California to cause cancer , birth defects, or other reproductive harm.

No warning is required.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
2-BUTOXYETHANOL 111-76-2	X	X	X
ZINC DINONYLNAPHTHALENESULFON A 28016-00-4	X		X
DIETHYL PHTHALATE 84-66-2	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B
Chronic Hazard Star Legend	Chronic Health Star Hazard Repeated or prolonged exposure may cause central nervous system damage			

Prepared By Regulatory Affairs
Issuing date 11-Nov-2015
Revision Date 27-Oct-2022
Revision Note

This SDS has been reviewed and remains the same . No changes were needed.

Disclaimer

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

End of Safety Data Sheet