

# Safety Data Sheet

Classified in accordance with SOR/2015-17

## 1. Product Identification

**Product Information:** 80-701

**Product Identifier:** WHITE LITHIUM GREASE

**Recommended Use:** Lubricant

**Manufacturer/Importer/Supplier Information:** KIMBALL MIDWEST  
4800 ROBERTS RD  
COLUMBUS, OH 43228  
US  
1-800-233-1294

**Emergency Telephone:** 1-800-424-9300

## 2. Hazard(s) identification

### Classification

Flammable Aerosol, category 1  
Compressed Gas  
Aspiration Hazard, category 1  
Carcinogenicity, category 2

### Label elements

#### HAZARD PICTOGRAMS



### SIGNAL WORD

Danger

### GHS HAZARD STATEMENTS

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H351 Suspected of causing cancer.

### GHS PRECAUTIONARY STATEMENTS

#### Prevention

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves and protective clothing

**Response**

P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.

**Storage**

P405 Store locked up.  
 P410+P403 Protect from sunlight. Store in a well-ventilated place.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

**Disposal**

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other Information**

None

### 3. Composition/Information on Ingredients

**Mixtures**

<u>Chemical Identity</u>	<u>Common Name and Synonyms</u>	<u>CAS Number</u>	<u>Content in Percent (%)*</u>
Distillates (Petroleum), Hydrotreated Light		64742-47-8	15-40
Propane		74-98-6	10-30
Naphtha, (Petroleum), Hydrotreated Light		64742-49-0	3-7
n-Heptane		142-82-5	1-5
Titanium dioxide		13463-67-7	0.1-1.0
Paraffin oils, petroleum, catalytic dewaxed heavy		64742-70-7	0.1-1.0

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition Comments:** Other components are not hazardous or are below required disclosure limits.

The exact concentration has been withheld as a trade secret.

### 4. First-aid Measures

**SKIN CONTACT:** Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

**EYE CONTACT:** Rinse immediately with plenty of water.

**INHALATION:** Move to fresh air.

**INGESTION:** Keep the victim calm and warm. Do NOT induce vomiting. If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Get immediate medical attention.

**IMPORTANT SYMPTOMS:** Suspected of causing cancer. Aspiration hazard: Harmful or fatal if swallowed.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:** Get medical attention if symptoms occur. Immediate medical attention is required for ingestion.

### 5. Fire-fighting Measures

**EXTINGUISHING MEDIA:** Use fire-extinguishing media appropriate for surrounding materials.

**UNSUITABLE EXTINGUISHING MEDIA:** Do not use water jet as an extinguisher, as this will spread the fire.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Extremely flammable aerosol. Contents under pressure. Keep away from ignition sources and open flames. Prolonged exposure to temperatures above 120°F may cause cans to burst. Vapors may travel considerable distance to a source of ignition and flash back. Combustion may produce carbon dioxide and carbon monoxide.

**SPECIAL FIREFIGHTING PROCEDURES:** No data available

## 6. Accidental Release Measures

**PERSONAL PRECAUTIONS :** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Leaking cans should be placed in a plastic bag or open pail away from ignition sources until the pressure has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

**ENVIRONMENTAL PRECAUTIONS:** Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

## 7. Handling and Storage

**HANDLING:** Keep away from sources of ignition - No smoking. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

**SAFE HANDLING ADVICE:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

**STORAGE:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

**NFPA 30B:** Aerosol Level 3

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>TLV-TWA</u>	<u>TLV-STEL</u>	<u>PEL-TWA</u>	<u>PEL-CEILING</u>
Distillates (Petroleum), Hydrotreated Light	200 mg/m3	N.E.	N.E.	N.E.
Propane	N.E.	N.E.	1000 ppm	N.E.
Naphtha, (Petroleum), Hydrotreated Light	N.E.	N.E.	100 ppm	N.E.
n-Heptane	400 ppm	500 ppm	500 ppm	N.E.
Titanium dioxide	0.2 mg/m3	N.E.	15 mg/m3	N.E.
Paraffin oils, petroleum, catalytic dewaxed heavy	N.E.	N.E.	N.E.	N.E.

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

**ENGINEERING CONTROLS:** No data available

### Personal Protection

**EYE/FACE PROTECTION:** Wear goggles/face shield.

**SKIN PROTECTION:** No data available

**RESPIRATORY PROTECTION:** Seek advice from local supervisor. In case of inadequate ventilation use suitable respirator.

**HYGIENIC PRACTICES:** When using do not smoke. Observe good industrial hygiene practices.

## 9. Physical and Chemical Properties

### Appearance:

Physical State:	Liquid
Form:	White liquid
Color:	White
Odor:	Solvent
Odor Threshold:	No data available
pH:	No data available
Freeze Point, °C:	No data available
Boiling Point, °C:	88
Flash Point, °C:	-104
Flammability (solid, gas):	No data available
Evaporation Rate:	Slower than Diethyl Ether
Combustibility:	Supports Combustion
Explosive Limits, %:	0.5 - 9.5
Vapor Pressure @20°C, PSI:	No data available
Vapor Density:	Heavier than air
Relative Density:	0.773
Solubility in Water:	No data available
Partition Coefficient, n-octanol/water:	No data available
Auto-Ignition Temperature, °C:	No data available
Decomposition temperature, °C:	No data available
Kinematic Viscosity:	No data available

## 10. Stability and Reactivity

**REACTIVITY:** Not reactive under normal conditions of use.

**STABILITY:** Material is stable under normal conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:** No data available

**CONDITIONS TO AVOID:** Keep away from heat, sparks, flames, and other sources of ignition. Do not puncture or incinerate containers. Dropping containers may cause bursting.

**INCOMPATIBILITY:** No data available

**HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion may produce carbon dioxide and carbon monoxide.

## 11. Toxicological Information

### Information on Likely Routes of Exposure

**SKIN CONTACT EFFECTS:** May cause irritation on prolonged or repeated contact.

**EYE CONTACT EFFECTS:** May cause slight irritation with tearing.

**INHALATION EFFECTS:** Inhalation of high concentrations of mists may cause irritation of the nose throat and upper respiratory tract.

**INGESTION EFFECTS:** Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal.

**Carcinogenicity:** contains 1 component (Titanium dioxide) present at a level greater or equal to 0.1% that have been identified as possible carcinogenic to humans by IARC (Group 2B).

The following values are calculated based on chapter 3.1 of the GHS document. The product itself has not been tested.

<b><u>ATE ORAL</u></b>	8,437 mg/kg
<b><u>ATE DERMAL</u></b>	7,299 mg/kg
<b><u>ATE INHALATION</u></b>	Not classified for acute toxicity based on available data.

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<b><u>CAS-No.</u></b>	<b><u>Chemical Name</u></b>	<b><u>Oral LD50</u></b>	<b><u>Dermal LD50</u></b>	<b><u>Vapor LC50</u></b>
64742-47-8	Distillates (Petroleum), Hydrotreated Light	5,000 mg/kg	5000 mg/kg	>100 mg/l
74-98-6	Propane	5,000 mg/kg	5,000 mg/kg	100 mg/l
64742-49-0	Naphtha, (Petroleum), Hydrotreated Light	5,000 mg/kg	3,750 mg/kg	100 mg/l
142-82-5	n-Heptane	5,000 mg/kg	2,000 mg/kg	29.29 mg/l
13463-67-7	Titanium dioxide	5,000 mg/kg	5,000 mg/kg	100 mg/l
64742-70-7	Paraffin oils, petroleum, catalytic dewaxed heavy	>15000 mg/kg Rat	>5000 mg/kg Rabbit	100 mg/l

N.I. = No Information

#### Skin Corrosion & Irritation:

**Product:** No data available

#### Serious Eye Damage & Irritation:

**Product:** No data available

#### Respiratory or Skin Sensitization:

**Product:** No data available

#### STOT-Single Exposure:

**Product:** No data available

#### STOT-Repeated Exposure:

**Product:** No data available

#### Aspiration Hazard:

**Product:** No data available

##### Components:

Distillates (Petroleum), Hydrotreated Light	64742-47-8	May be fatal if swallowed and enters airways.
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	May be fatal if swallowed and enters airways.
n-Heptane	142-82-5	May be fatal if swallowed and enters airways.

#### Carcinogenicity:

**Product:** No data available

##### Components:

Titanium dioxide	13463-67-7	Suspected of causing cancer
------------------	------------	-----------------------------

#### Reproductive Toxicity:

**Product:** No data available

#### Germ Cell Mutagenicity:

**Product:** No data available

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** No data available

**PERSISTENCE:** No data available

**BIOACCUMULATE:** No data available

**MOBILITY IN SOIL:** No data available

**OTHER ECOLOGICAL:** No data available

## 13. Disposal Information

**DISPOSAL INFORMATION:** Consult with your local, regional and federal agencies for information on proper disposal.

**CONTAMINATED PACKAGING :** Consult with your local, regional and federal agencies for information on proper disposal.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No data available

### TDG

UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk	N/A
Packing Group:	N/A

### IATA

UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk:	N/A
Packing Group:	N/A

### IMDG

UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk:	N/A
Packing Group:	N/A

The classification shown in this section may be eligible for use of an exception, such as 'Limited Quantity', per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

## 15. Regulatory Information

### CHEMICAL INVENTORY STATUS:

TSCA	On or in compliance with the inventory
DSL	All ingredients in this product are listed on the DSL or are exempt.

## 16. Other Information

Revision Date: 3/10/2023  
Datasheet produced by: Regulatory Department

### Legend

N/A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

TLV - Threshold Limit Values (TLVs®), as established by the American Conference of Governmental Industrial Hygienists (ACGIH®)

PEL - Permissible Exposure Limit, as established by the U.S. Occupational Safety and Health Administration (OSHA), as amended

TSCA - U.S. Toxic Substance Control Act

DSL - Canada Environmental Protection Act: Domestic Substance List

This information is being provided in accordance with the Hazardous Products Regulations (HPR) regulation (SOR/2015-17). The information supplied is designed for workplaces where the product use and frequency of exposure exceeds that established for the labeled consumer use.

### **Further Information**

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

