1 Identification of the substance and manufacturer		
Trade name: Other means of identification	Olive Drab Ultra Pro•Max	
Product code: Article category Recommended use: Uses advised against: Manufacturer/Supplier:	80653 Paint and coatings application. Any that differs from the recommended use. Kimball Midwest 4800 Roberts Road Columbus, OH 43228 800-233-1294 www.kimballmidwest.com	
Emergency telephone number:	ChemTrec: 800-424-9300	
2 Hazard(s) identification		
Classification of the substance or n		
Aerosols 1	H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.	
Eye irritation 2A Carcinogenicity 2	<ul><li>H319 Causes serious eye irritation.</li><li>H351 Suspected of causing cancer. Route of exposure: Inhalation.</li></ul>	
Specific target organ toxicity (single e		
Specific target organ toxicity (single e. Specific target organ toxicity (repeated Additional information: GHS Hazard pictograms		
	GHS02 GHS07 GHS08	
Signal word Hazard statements	Danger Extremely flammable aerosol. Pressurized container: may burst if heated. Causes serious eye irritation. Suspected of causing cancer. Route of exposure: Inhalation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.	
Precautionary statements	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing fume/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store in a well ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents/container in accordance with local/regional/national/international regulations.	
3 Composition/information on ing		
Chemical characterization: Mixtures Chemical Description:	<b>s</b> This product is a mixture of the substances listed below with nonhazardous additions.	
Dangerous components:		
67-64-1 Acetone	15-25%	

	Chemical D	escription.	This product is a mixture of the substances listed below with hornazardous additions.	
		components:		
	67-64-1	Acetone		15-25%
		propane		15-25%
	1317-65-3	Calcium Carbonate		10-15%
		n-butane		5-10%
		Isobutyl Acetate		5-10%
	2807-30-9	Glycol Ether EP		≥5-<10%
	7631-86-9	Silicon Dioxide		1-5%
		PM acetate		1-5%
		butyl acetate		1-5%
[	64742-89-8	VM&P Naphtha		1-5%

- 4 First-aid measures
  - After inhalation:

Supply fresh air; consult doctor in case of complaints.

(Contd. on page 2)

Revised On 03/12/2025

effects:	wing: ant symptoms and f any immediate medical	Contd. of page Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse mouth with water. Do not induce vomiting. Dizziness No further relevant information available.
5 Fire-fightin	a measures	
Extinguishir Special haza Protective e	ng agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.
firefighters:		A respiratory protective device may be necessary.
6 Accidental	release measures	
Personal pre	ecautions, protective	
equipment a procedures:	ind emergency	Lies rearritations protective devices against the effects of fumes (dust/screed)
	d material for	Use respiratory protective device against the effects of fumes/dust/aerosol.
	t and cleaning up:	Absorb liquid components with liquid-binding material.
7 Handling a	nd storago	
	for safe handling	Use only in well ventilated areas.
Storage requ		Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.
	ontrolo/noroonal prat	
-	controls/personal prote	ection equire monitoring at the workplace:
67-64-1 Acet		
PEL (USA)	Long-term value: 2400 m	na/m³, 1000 ppm
REL (USA)	Long-term value: 590 mg	
TLV (USA)	Short-term value: 1187 r	ng/m³, 500 ppm
, , , , , , , , , , , , , , , , , , ,	Long-term value: 594 mg	y/m³, 250 ppm
74.00.0	A4, BEI	
74-98-6 prop PEL (USA)	Long-term value: 1800 n	ng/m³ 1000 nnm
REL (USA)	Long-term value: 1800 m	
TLV (USA)	see Appendix F Minimal	
106-97-8 n-b		oxygen content ( D, EX)
REL (USA)	Long-term value: 1900 m	ng/m³ 800 ppm
TLV (USA)	Short-term value: 2370 r	
120 (00/1)	(EX)	
110-19-0 Iso	butyl Acetate	
PEL (USA)	Long-term value: 700 mg	
REL (USA)	Long-term value: 700 mg	g/m³, 150 ppm
TLV (USA)	Short-term value: 712 m	g/m³, 150 ppm
108-65-6 PM	Long-term value: 238 mg	j/m², əu ppm
	Long-term value: 50 ppm	
		1
	Long-term value: 710 mg	1/m³ 150 ppm
123-86-4 but		
123-86-4 but PEL (USA)	Short-term value: 950 m	d/m <sup>°</sup> . 200 ppm
123-86-4 but	Short-term value: 950 m Long-term value: 710 m	ý/m³, 150 ppm
123-86-4 but PEL (USA)	Long-term value: 710 mg Short-term value: 712 mg	ỹ/m³, 150 ppm g/m³, 150 ppm
<b>123-86-4 but</b> PEL (USA) REL (USA) TLV (USA)	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg	ỹ/m³, 150 ppm g/m³, 150 ppm
123-86-4 but PEL (USA) REL (USA) TLV (USA) 64742-89-8 V	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg /M&P Naphtha	ỹ/m³, 150 ppm g/m³, 150 ppm g/m³, 50 ppm
123-86-4 but PEL (USA) REL (USA) TLV (USA) 64742-89-8 V TLV (USA)	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg /M&P Naphtha Long-term value: 100 pp Skin, A3	ỹ/m³, 150 ppm g/m³, 150 ppm g/m³, 50 ppm m
123-86-4 but PEL (USA) REL (USA) TLV (USA) 64742-89-8 V TLV (USA) Ingredients	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg /M&P Naphtha Long-term value: 100 pp Skin, A3 with biological limit valu	ỹ/m³, 150 ppm g/m³, 150 ppm g/m³, 50 ppm m
123-86-4 but PEL (USA) REL (USA) TLV (USA) 64742-89-8 V TLV (USA) Ingredients 67-64-1 Acet	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg /M&P Naphtha Long-term value: 100 pp Skin, A3 with biological limit valu tone	ỹ/m³, 150 ppm g/m³, 150 ppm g/m³, 50 ppm m
123-86-4 but PEL (USA) REL (USA) TLV (USA) 64742-89-8 V TLV (USA) Ingredients 67-64-1 Acet BEI (USA) 2	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg /M&P Naphtha Long-term value: 100 pp Skin, A3 with biological limit valu tone 5 mg/L	ỹ/m³, 150 ppm g/m³, 150 ppm g/m³, 50 ppm m
123-86-4 but PEL (USA) REL (USA) TLV (USA) 64742-89-8 V TLV (USA) Ingredients 67-64-1 Ace BEI (USA) 2	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg /M&P Naphtha Long-term value: 100 pp Skin, A3 with biological limit valu tone 5 mg/L fedium: urine	ỹ/m³, 150 ppm g/m³, 150 ppm g/m³, 50 ppm m
123-86-4 but PEL (USA) REL (USA) TLV (USA) 64742-89-8 V TLV (USA) Ingredients 67-64-1 Acet BEI (USA) 2 M T	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg /M&P Naphtha Long-term value: 100 pp Skin, A3 with biological limit valu tone 5 mg/L	ỹ/m³, 150 ppm g/m³, 150 ppm g/m³, 50 ppm m es:
123-86-4 but PEL (USA) REL (USA) TLV (USA) 64742-89-8 V TLV (USA) Ingredients 67-64-1 Acet BEI (USA) 2 M T	Long-term value: 710 mg Short-term value: 712 mg Long-term value: 238 mg /M&P Naphtha Long-term value: 100 pp Skin, A3 with biological limit valu tone 5 mg/L ledium: urine ime: end of shift arameter: Acetone (nonsp	ğ/m³, 150 ppm g/m³, 50 ppm g/m³, 50 ppm m es:

Page 3/4

	(Contd. of page 2)
Breathing equipment:	Avoid contact with the eyes and skin. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical
Hand protection:	hygiene. Nitrile gloves.
Eye protection:	The glove material must be impermeable and resistant to the substance. Tightly sealed goggles

## 9 Physical and chemical properties

•	i nyelear ana enemiear propertiee	
	Physical state	Aerosol
	Odor:	Aromatic
	Odor threshold:	Not determined.
	Melting point/Melting range	Undetermined.
	Boiling point:	-44.5 °C (-48.1 °F)
	Flammability:	Extremely flammable.
	Lower Explosion Limit:	1.7 Vol %
	Upper Explosion Limit:	10.9 Vol %
	Flash point:	-19 °C (-2.2 °F)
	Flammability (solid, gas):	Extremely flammable.
	Decomposition temperature:	Not determined.
	pH-value:	Not determined.
	Viscosity:	Not determined.
	Solubility:	Not determined.
	Vapor pressure:	Not determined.
	Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
	Vapor density	Not determined.
	Particle characteristics	Not applicable.
	Appearance:	Aerosol.
	Ignition temperature:	Product is not self-igniting.
	Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
	Water:	0.0 %
	Evaporation rate	Not applicable.
	Partition coefficient: n-octonal/water:	Not determinea.

## 10 Stability and reactivity

Reactivity:	Stable at normal temperatures.	
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit.	Do not warehouse in subfreezing
	temperatures.	Ũ
Chemical stability:	Not fully evaluated.	
Possibility of hazardous reactions:	No dangerous reactions known.	
Incompatible materials:	No further relevant information available.	
Hazardous decomposition:	No dangerous decomposition products known.	

## **11 Toxicological information**

LD/LC50 values that are relevant for classification:		
110-19-0 Isobutyl Acetate		
Oral LD50 4,763 mg/kg (rbt)		
7631-86-9 Silicon Dioxide		
Oral LD50 10,000 mg/kg (rat)		
108-65-6 PM acetate		
Oral LD50 8,500 mg/kg (rat)		
Inhalative LC50/4 h 35.7 mg/l (rat)		
123-86-4 butyl acetate		
Oral LD50 14,000 mg/kg (rat)		
Inhalative LC50/4 h >21 mg/l (rat)		
Information on toxicological effects: No data available.   Skin effects: No irritant effect.   Eye effects: Irritating effect.   Sensitization: No sensitizing effects known.		

12 Ecological information	
Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's),
Bioaccumulative potential:	perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkýl substances (PFA's), or chlorinated solvents. No further relevant information available.
Mobility in soil:	No further relevant information available.

Page 4/4

Other adverse effects:	(Contd. of page 3) (Contd. of page 3)	
13 Disposal considerations Dispose of in accordance with local, s disposed of responsibly. Do not heat of Recommendation: Recommended cleansing agent:	state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be or cut empty containers with electric or gas torches. Completely empty cans should be recycled. Water, if necessary with cleansing agents.	
14 Transport information		
UN-Number DOT DOT ADR Transport hazard class(es): Class Special marking (IATA): Packaging Group: Special precautions for user: EMS Number: UN "Model Regulation":	UN1950 UN1950 Aerosols, flammable, containing substances in Class 8, Packing Group III 1950 AEROSOLS 2.1 Gases  Warning: Gases F-D,S-U UN 1950 AEROSOLS, 2.1 (8)	
15 Regulatory information   SARA Section 355 (extremely hazardous substances):		
None of the ingredients in this product are listed.   SARA Section 313 (Specific toxic chemical listings):   None of the ingredients is listed.		
		Toxic Substances Control Act (TSCA): Canadian Domestic Substances Lis (DSL):
Consumer Product Safety Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
California Proposition 65 chemicals		
13463-67-7 titanium dioxide		
1333-86-4 Carbon black		
100-41-4 ethyl benzene 108-10-1 methyl isobutyl ketone		
Prop 65 chemicals known to cause	hirth defects or reproductive harm:	
108-10-1 methyl isobutyl ketone		
EPA:		
67-64-1 Acetone 110-19-0 Isobutyl Acetate	     	
16 Other information	16 Other information	
Contact:	Regulatory Affairs	

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.