



The following SDS references the products below:

Isopropyl Fuel Dryer & Antifreeze

Vendor Item Number: PYFDI12

Manufactured By:

Niteo products

Distributed by Kimball Midwest with the KM product  
identification number:

80-980

# SAFETY DATA SHEET



## Pyroil™ FUEL DRYER & ANTIFREEZE

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue:             |
| 3.3     | 04/10/2024     | 600000000450 | 04/09/2024                      |
|         |                |              | Date of first issue: 05/23/2016 |

### SECTION 1. IDENTIFICATION

Product name : PYROIL FUEL DRYER & ANTIFRZ 12/12 OZ

Product code : PYFDI12

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use : FUEL DRIER ISOPROPYL

Restrictions on use : Use only outdoors or in a well-ventilated area.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
Keep away from heat/ sparks/ open flames/ hot surfaces. No

# SAFETY DATA SHEET



## Pyroil™ FUEL DRYER & ANTIFREEZE

Version 3.3      Revision Date: 04/10/2024      SDS Number: 600000000450      Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ eye protection/ face protection.

### Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/ attention.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---------------|---------|-----------------------|
| Isopropanol   | 67-63-0 | >= 90 - < 100         |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : Move to fresh air.  
IF INHALED: Call a POISON CENTER/ doctor if you feel unwell.

# SAFETY DATA SHEET



## Pyroil™ FUEL DRYER & ANTIFREEZE

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 04/09/2024  |
| 3.3     | 04/10/2024     | 600000000450 | Date of first issue: 05/23/2016 |

- If unconscious, place in recovery position and seek medical advice.  
Keep patient warm and at rest.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
If on skin, rinse well with water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.  
May cause drowsiness or dizziness.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Ensure adequate ventilation.

**Pyroil™ FUEL DRYER & ANTIFREEZE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue:             |
| 3.3     | 04/10/2024     | 600000000450 | 04/09/2024                      |
|         |                |              | Date of first issue: 05/23/2016 |

- Avoid breathing dust.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Evacuate personnel to safe areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.  
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.  
Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

## Pyroil™ FUEL DRYER &amp; ANTIFREEZE

Version 3.3      Revision Date: 04/10/2024      SDS Number: 600000000450      Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

| Components  | CAS-No. | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis     |
|-------------|---------|----------------------------------|--|-----------|
| Isopropanol | 67-63-0 | TWA                              | 200 ppm  | ACGIH     |
|             |         | STEL                             | 400 ppm  | ACGIH     |
|             |         | TWA                              | 400 ppm<br>980 mg/m <sup>3</sup>               | NIOSH REL |
|             |         | ST                               | 500 ppm<br>1,225 mg/m <sup>3</sup>             | NIOSH REL |
|             |         | TWA                              | 400 ppm<br>980 mg/m <sup>3</sup>               | OSHA Z-1  |
|             |         | TWA                              | 400 ppm<br>980 mg/m <sup>3</sup>               | OSHA P0   |
|             |         | STEL                             | 500 ppm<br>1,225 mg/m <sup>3</sup>             | OSHA P0   |

## Biological occupational exposure limits

| Components  | CAS-No. | Control parameters | Biological specimen | Sampling time                    | Permissible concentration | Basis     |
|-------------|---------|--------------------|---------------------|----------------------------------|---------------------------|-----------|
| Isopropanol | 67-63-0 | Acetone            | Urine               | End of shift at end of work-week | 40 mg/l                   | ACGIH BEI |

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

## Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear as appropriate:  
Impervious clothing  
Flame-resistant clothing  
Safety shoes

# SAFETY DATA SHEET



## Pyroil™ FUEL DRYER & ANTIFREEZE

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 04/09/2024  |
| 3.3     | 04/10/2024     | 600000000450 | Date of first issue: 05/23/2016 |

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not smoke.  
When using do not eat or drink.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|  |   |
|--|---|
| Appearance                                       | : liquid  |
| Colour   | : colourless  |
| Odour  | : alcohol-like                                      |
| pH   | : No data available                                 |
| Melting point/freezing point                     | : No data available                                 |
| Boiling point/boiling range                      | : 82.5 °C<br>(1,013 hPa)<br>The value is calculated |
| Flash point                                      | : 10 °C<br>Method: Tag closed cup                   |
| Evaporation rate                                 | : No data available                                 |
| Flammability (solid, gas)                        | : No data available                                 |
| Self-ignition                                    | : No data available                                 |
| Upper explosion limit / Upper flammability limit | : 12 %(V)<br>The value is calculated                |
| Lower explosion limit / Lower flammability limit | : 2.5 %(V)<br>The value is calculated               |
| Vapour pressure                                  | : 60.53 hPa (25 °C)<br>The value is calculated      |
| Density  | : 0.790 g/cm <sup>3</sup> (25 °C)                   |
| Solubility(ies)                                  |   |
| Water solubility                                 | : No data available                                 |
| Partition coefficient: n-octanol/water           | : No data available                                 |
| Viscosity  |   |
| Viscosity, dynamic                               | : No data available                                 |
| Viscosity, kinematic                             | : No data available                                 |
| Oxidizing properties                             | : No data available                                 |

### SECTION 10. STABILITY AND REACTIVITY

**Pyroil™ FUEL DRYER & ANTIFREEZE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 04/09/2024  |
| 3.3     | 04/10/2024     | 600000000450 | Date of first issue: 05/23/2016 |

|                                    |   |  |
|------------------------------------|---|--|
| Reactivity                         | : | No decomposition if stored and applied as directed.  |
| Chemical stability                 | : | No decomposition if stored and applied as directed.  |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed.<br>Vapours may form explosive mixture with air.  |
| Conditions to avoid                | : | Heat, flames and sparks.   |
| Incompatible materials             | : | Acids<br>Aldehydes<br>Bases<br>Amines<br>Ethylene oxide<br>Halogenated compounds<br>halogens<br>isocyanates<br>Strong oxidizing agents<br>Do not use with aluminum equipment at temperatures above 49C or 120 degrees F. |
| Hazardous decomposition products   | : | Carbon oxides  |

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Eye contact  
Skin contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:****Isopropanol:**

|                           |   |  |
|---------------------------|---|--|
| Acute oral toxicity       | : | LD50 (Rat): 5.84 g/kg  |
| Acute inhalation toxicity | : | LC50 (Rat): 16000 ppm<br>Exposure time: 4 h<br>Test atmosphere: vapour |
| Acute dermal toxicity     | : | LD50 (Rabbit): 12,800 mg/kg  |

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks: May cause skin irritation in susceptible persons.

**Components:****Isopropanol:**



**Pyroil™ FUEL DRYER & ANTIFREEZE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 04/09/2024  |
| 3.3     | 04/10/2024     | 600000000450 | Date of first issue: 05/23/2016 |

---

Result: Possibly irritating to skin

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:****Isopropanol:**

Result: Irritating to eyes.

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:****Isopropanol:**

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

# SAFETY DATA SHEET



## Pyroil™ FUEL DRYER & ANTIFREEZE

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 04/09/2024  |
| 3.3     | 04/10/2024     | 600000000450 | Date of first issue: 05/23/2016 |

### **Product:**

No aspiration toxicity classification

### **Further information**

### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## SECTION 12. ECOLOGICAL INFORMATION

### **Toxicity**

Additional ecological information : No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### **International Regulations**

#### **IATA-DGR**

UN/ID No. : UN 1219  
Proper shipping name : Isopropanol Mixture, Isopropanol  
Class : 3  
Packing group : II  
Labels : 3  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

#### **IMDG-Code**

UN number : UN 1219  
Proper shipping name : ISOPROPANOL MIXTURE, ISOPROPANOL  
Class : 3  
Packing group : II  
Labels : 3

# SAFETY DATA SHEET



## Pyroil™ FUEL DRYER & ANTIFREEZE

Version 3.3      Revision Date: 04/10/2024      SDS Number: 600000000450      Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

EmS Code : F-E, S-D  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### 49 CFR

UN/ID/NA number : UN 1219  
Proper shipping name : Isopropanol Mixture, Isopropanol

Class : 3  
Packing group : II  
Labels : 3  
ERG Code : 129  
Marine pollutant : no

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

| Components | CAS-No.   | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|-----------|--------------------|-----------------------------|
| Xylene     | 1330-20-7 | 100                | 100 (F003)                  |
| Xylene     | 1330-20-7 | 100                | *                           |

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and Methanol, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# SAFETY DATA SHEET



## Pyroil™ FUEL DRYER & ANTIFREEZE

Version  
3.3

Revision Date:  
04/10/2024


SDS Number:  
600000000450

Date of last issue: 04/09/2024  
Date of first issue: 05/23/2016

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA:



Revision Date : 04/10/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN