Date of issue: 03/12/2025 Revised On 03/12/2025

1 Identification of the substance and manufacturer

Trade name: AC/OM Orange Ultra Pro•Max

Other means of identification

80627 Product code:

Article category Recommended use:

Paint and coatings application.

Any that differs from the recommended use. Uses advised against:

Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228

800-233-1294

www.kimballmidwest.com Emergency telephone number: ChemTrec: 800-424-9300



2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Eye irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms

Precautionary statements







GHS02 GHS07 GHS08

Signal word

Hazard statements Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Wear protective gloves/protective clothing/eye protection/face protection.

If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store in a well ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Citetinical Decemption		This product is a mixture of the substantees herea below that hermazarasas additions.					
Dangerous components:							
67-64-1	Acetone		15-25%				
74-98-6	propane		15-25%				
7727-43-7	barium sulfate		5-10%				
	n-butane		5-10%				
	Isobutyl Acetate		5-10%				
2807-30-9	Glycol Ether EP		≥5-<10%				
123-86-4	butyl acetate		1-5%				
	PM acetate		1-5%				
107-87-9	Methyl Propyl Ketone		1-5%				

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

(Contd. on page 2)

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: AC ORANGE

After eye contact:

After swallowing: Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

(Contd. of page 1) Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse mouth with water. Do not induce vomiting.

Dizziness

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Methods and material for

containment and cleaning up:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

PEL (USA)

REL (USA)

TLV (USA)

Long-term value: 700 mg/m³, 200 ppm

Long-term value: 530 mg/m³, 150 ppm

Short-term value: 529 mg/m3, 150 ppm

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store lockéd up.

8 Exposure controls/personal protection

8 Exposure con	ntrois/personal protection							
Components w	rith limit values that require monitoring at the workplace:							
67-64-1 Aceton	ne							
PEL (USA) Lo	ong-term value: 2400 mg/m³, 1000 ppm							
REL (USA) L	A) Long-term value: 590 mg/m³, 250 ppm							
TLV (ÙSA) S	Short-term value: 1187 mg/m³, 500 ppm							
L	ong-term value: 594 mg/m³, 250 ppm .4, BEI							
74-98-6 propan	ie							
	ong-term value: 1800 mg/m³, 1000 ppm							
REL (USA) L	ong-term value: 1800 mg/m³, 1000 ppm							
TLV (USA) se	ee Appendix F Minimal oxygen content (D, EX)							
7727-43-7 bariu								
PEL (USA) Le	ong-term value: 15* 5** mg/m³ total dust **respirable fraction							
	ong-term value: 10* 5** mg/m³ total dust **respirable fraction							
TLV (USA) Lo	ong-term value: 5* mg/m³ inhalable fraction; E							
106-97-8 n-buta	ane							
REL (USA) L	ong-term value: 1900 mg/m³, 800 ppm							
	Short-term value: 2370 mg/m³, 1000 ppm EX)							
110-19-0 Isobu	tyl Acetate							
PEL (USA) L	ong-term value: 700 mg/m³, 150 ppm							
	ong-term value: 700 mg/m³, 150 ppm							
TLV (USA) S	Short-term value: 712 mg/m³, 150 ppm ong-term value: 238 mg/m³, 50 ppm							
123-86-4 butyl a								
	ong-term value: 710 mg/m³, 150 ppm							
	Short-term value: 950 mg/m³, 200 ppm							
	ong-term value: 710 mg/m³, 150 ppm							
TLV (USA) S	Short-term value: 712 mg/m³, 150 ppm ong-term value: 238 mg/m³, 50 ppm							
108-65-6 PM ac								
	ong-term value: 50 ppm							
107-87-9 Methy	rl Propyl Ketone							

(Contd. on page 3)

(Contd. of page 2)

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: AC ORANGE

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Physical state Aerosol Odor: Aromatic Odor threshold: Not determined. Melting point/Melting range Undetermined. Boiling point: -44.5 °C (-48.1 °F) Flammability: Extremely flammable.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % -19 °C (-2.2 °F) Upper Explosion Limit: Flash point: Flammability (solid, gas): Extremely flammable. Decomposition temperature: Not determined. pH-value: Not determined. Viscosity: Not determined. Solubility: Not determined. Vapor pressure: Not determined.

Between 0.77 and 0.85 (Water equals 1.00) Relative Density:

Vapor density Not determined. Particle characteristics Not applicable. Appearance: Aerosol.

Ignition temperature: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture. Water: 0.0 %

Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Not fully evaluated.

Chemical stability: Possibility of hazardous reactions:

No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LI	D	'L	C	5(0	va	lu	es	t	hat	aı	re	rel	ev	ant	for	С	las	si	fic	at	ioi	n:

110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rbt)

123-86-4 butyl acetate

LD50 14,000 mg/kg (rat) Inhalative LC50/4 h >21 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eve effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: AC ORANGE

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkýl

substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable, containing substances in Class 8, Packing Group III

ADR 1950 AEROSOLS

Transport hazard class(es):

Class 2.1 Gases

Special marking (IATA):

Packaging Group:

Warning: Gases Special precautions for user:

EMS Number: F-D,S-Ŭ

UN 1950 AEROSOLS, 2.1 (8) **UN "Model Regulation":**

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

Toxic Substances Control Act

All ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:								
108-10-1	methyl isobutyl ketone							

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

EPA:

67-64	1 Acetone	I
7727-43	7 barium sulfate	D, CBD(inh), NL(oral)
110-19	0 Isobutyl Acetate	D

16 Other information

Contact: Regulatory Affairs