Date of issue: 03/12/2025 Revised On 03/12/2025

# 1 Identification of the substance and manufacturer

Trade name: TRAFFIC WHITE

Other means of identification

80-892 Product code:

Article category

Paint and coatings application. Recommended use:

Any that differs from the recommended use. Uses advised against:

Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228

800-233-1294

www.kimballmidwest.com ChemTrec: 800-424-9300 **Emergency telephone number:** 

## 2 Hazard(s) identification

### Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Specific target organ toxicity (single exposure) 3 H335 May cause respiratory irritation.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 



GHS02 GHS07 GHS08

Signal word Danger

**Hazard statements** Extremely flammable aerosol. Pressurized container: may burst if heated.

Suspected of causing cancer. Route of exposure: Inhalation.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell.

Store in a well ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

Chemical Description his product is a mixture of the substances listed below with pophazardous additions

Chemical Description.		This product is a mixture of the substances listed below with normazardous additions.	
Dangerous components:			
64742-89-8	VM&P Naphtha		25-50%
74-98-6	propane		10-15%
13463-67-7	titanium dioxide		5-10%
106-97-8	n-butane		5-10%
7727-43-7	barium sulfate		5-10%
1317-65-3	Calcium Carbonate		5-10%
64742-47-8	Mineral Spirits		1-5%

## 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. After eye contact:

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects: Dizziness

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: TRAFFIC WHITE

Can form explosive gas-air mixtures.

Special hazards: Protective equipment for

firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for

containment and cleaning up:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store lockéd up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

64742-89-8 VM&P Naphtha

TLV (USA) Long-term value: 100 ppm Skin, A3

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) | Short-term value: 2370 mg/m³, 1000 ppm

(EX)

7727-43-7 barium sulfate

PEL (USA) Long-term value: 15\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

REL (USA) Long-term value: 10\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

TLV (USA) Long-term value: 5\*\_mg/m³ \*inhalable fraction; E

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the skin. Avoid contact with the eyes and skin.

Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile aloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Physical state Aerosol Odor: Aromatic

Odor threshold: Not determined. Melting point/Melting range Undetermined. Boiling point: -44.5 °C (-48.1 °F) Flammability: Extremely flammable.

1.7 Vol % 10.9 Vol % Lower Explosion Limit: Upper Explosion Limit: -19 °C (-2.2 °F) Flash point: Extremely flammable. Flammability (solid, gas): **Decomposition temperature:** Not determined. pH-value: Not determined. . Viscosity: Not determined. Solubility: Not determined. Vapor pressure: Not determined.

**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. **Particle characteristics** Not applicable. Appearance: Aerosol.

(Contd. on page 3)

(Contd. of page 2)

# Safety Data Sheet

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: TRAFFIC WHITE

Ignition temperature: Product is not self-igniting.

In use, may form flammable/explosive vapour-air mixture. Danger of explosion:

Water: 18.0 % **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

No dangerous reactions known. Possibility of hazardous reactions:

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

## 11 Toxicological information

### LD/LC50 values that are relevant for classification:

#### 13463-67-7 titanium dioxide

LD50 >20,000 mg/kg (rat) Oral Dermal LD50 >10,000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

## 12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

No further relevant information available.

Bioaccumulative potential: Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

#### 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

**UN-Number** UN1950 DOT UN1950

DOT Aerosols, flammable **ADR** 1950 AEROSOLS

Transport hazard class(es):

2.1 Gases Class

Special marking (IATA):

Packaging Group:

Special precautions for user: Warning: Gases

EMS Number: F-D.S-Ŭ

UN "Model Regulation": **UN 1950 AEROSOLS, 2.1** 

## 15 Regulatory information

## SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

#### SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

Toxic Substances Control Act

All ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

(DSL):

All ingredients are listed or exempted. Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

(Contd. on page 4)

# **Safety Data Sheet**

Date of issue: 03/12/2025 Revised On 03/12/2025

Trade name: TRAFFIC WHITE

(Contd. of page 3)

California Proposition 65 chemicals known to cause cancer:

13463-67-7 | titanium dioxide

100-41-4 | ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

7727-43-7 | barium sulfate

D, CBD(inh), NL(oral)

# 16 Other information

Contact: Regulatory Affairs