

Safety Data Sheet

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Food Grade Chain Lubricant
PRODUCT CODE: 80-7712
RECOMMENDED USE: Food Grade Semi-Synthetic Chain Lube
RESTRICTIONS ON USE: None known.
COMPANY NAME: Kimball Midwest
COMPANY ADDRESS: 4800 Roberts Road Columbus Ohio
COMPANY PHONE: 800.233.1294
EMERGENCY PHONE: Chemtrec 1.800.424.9300

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 2
Gases Under Pressure: Liquefied Gas
Aspiration Hazard: Category 1

HAZARD STATEMENT(S): **DANGER:** Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: N/A

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, regional or national guidelines.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
White mineral oil	8042-47-5	50-60%
Propane/n-Butane	68476-86-8	15-25%

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Keep head below hips if vomiting occurs. Seek immediate medical attention. Aspiration hazard. Never give anything by mouth to an unconscious person.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.

SKIN: Remove contaminated clothes. Wash skin thoroughly with soap and water for 15 minutes. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: Prolonged contact with skin may cause irritation. Contact with eyes may cause irritation, redness, tearing. Inhalation of mist or vapors may cause respiratory irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

CHRONIC HEALTH HAZARDS: None known.

NOTE TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical condition. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

Safety Data Sheet

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water spray or fog.

UNSUITABLE EXTINGUISHING MEDIA: Water jets or streams.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Shut off all sources of ignition. Use water spray to disperse vapor and cool fire exposed containers. Prevent run off from entering streams, sewers, or drinking water supply.

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLAMMABLE. Contents under pressure. Exposure to temperatures above 120 °F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Cool containers with water spray. Rapid depolymerization can occur in a fire and produce flammable vapors. May depolymerize at temperatures above 392 °F (200 °C) with the production of extremely flammable butene monomers. Vapor may cause fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and nitrogen.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. Wear appropriate personal protective equipment. Clean up using rag or use some non-combustible material like vermiculite, sand or earth. Prevent spill from entering sewers, storm drains and natural waterways. Place waste in proper containers for disposal.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Wear proper personal protective equipment when using this product. Store in a cool, dry area. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling.

OTHER PRECAUTIONS: Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong oxidizing agents.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
White mineral oil	5 mg/m ³ (oil mist)	5 mg/m ³ (oil mist)
Propane/n-Butane	Not Established	1000 ppm

ENGINEERING CONTROLS / VENTILATION: General ventilation should be used. Provide sufficient mechanical ventilation (general and/or local exhaust) to maintain exposure below the recommended exposure limits.

RESPIRATORY PROTECTION: Not required with normal use. If vapors are present or irritation is experienced, use NIOSH/MSHA approved respirator.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles.

ADDITIONAL MEASURES: No smoking or open flames. Wash hands thoroughly with soap and water after use.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, colorless spray.

ODOR: Bland.

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

Safety Data Sheet

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: Slow.

FLAMMABILITY(solid/gas): Flammable Aerosol

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOSIVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H₂O=1): 0.875 - 0.890 @ 77 °F (25 °C).

SOLUBILITY(IES): Non-soluble in water.

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

AUTOIGNITION TEMPERATURE: N/D

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None known.

CHEMICAL STABILITY: Stable.

POSSIBLE HAZARDOUS REACTIONS: May depolymerize at temperatures above 392 °F (200 °C) with the production of extremely flammable butene monomers.

CONDITIONS TO AVOID: Temperatures greater than 122 °F and sources of ignition. Avoid incompatibles.

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **White mineral oil** (8042-47-5): LD₅₀ (Oral, Rat) > 5000 mg/kg; LD₅₀ (Dermal) > 2000 mg/kg; LC₅₀ (Inhalation Dust/Mist, Rat, 4h) > 5 g/L. **Propane** (74-98-6): LC₅₀ (Inhalation, Rat, 4h) 658 mg/L. **n-Butane** (106-97-8): LC₅₀ (Inhalation, Rat, 4h) 30957 mg/m³.

ROUTES OF ENTRY: Eyes, Inhalation, Skin

EYES: May cause irritation, redness, tearing.

INGESTION: Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation, nausea, diarrhea, vomiting. Harmful if swallowed. Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia or edema.

INHALATION: May cause respiratory tract irritation, dizziness.

SKIN: May cause irritation, dryness.

MEDICAL CONDITION AGGRAVATED: None known.

ACUTE HEALTH HAZARDS: Prolonged contact with skin may cause irritation. Contact with eyes may cause irritation, redness, tearing. Inhalation of mist or vapors may cause respiratory irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

CHRONIC HEALTH HAZARDS: None known.

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: **White mineral oil** (8042-47-5): LC₅₀ (*Oncorhynchus mykiss*, 96h) 5000 mg/L; EC₅₀ (*Daphnia magna*, 48h) 1000 mg/L.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.

MOBILITY IN SOIL: This product is not mobile in soil.

OTHER ADVERSE EFFECTS: None known.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

Safety Data Sheet

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None.

SARA 311/312 HAZARD CATEGORIES: Flammable (gases, aerosols, liquids, solids). Gas under pressure. Aspiration hazard.

SARA 313 REPORTABLE INGREDIENTS: This product does not contain any chemicals which are subject to the reporting requirements at Title 40 of the Code of Federal Regulations, Part 372.

CLEAN WATER ACT: None.

STATE REGULATIONS: California Proposition 65: This product does not contain chemicals regulated by California Proposition 65.

INTERNATIONAL REGULATIONS: No information available.

VOLATILE ORGANIC COMPOUNDS (VOC): 20%

NFPA HEALTH: 2

HMIS HEALTH: 2

NFPA FLAMMABILITY: 2

HMIS FLAMMABILITY: 2

NFPA REACTIVITY: 1

HMIS REACTIVITY: 1

NFPA OTHER: None

HMIS PROTECTION: A

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Regulatory

DATE PREPARED: 12/16/2016

REVISION DATE: 09/16/2022

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.