

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 08/07/2025

Revised On 08/07/2025

1 Identification

Trade name: DW ORANGE
Other means of identification
Product code: 80-1281
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Kimball Midwest
 4800 Roberts Road
 Columbus, OH 43228
 800-233-1294
 www.kimballmidwest.com
Emergency telephone number: 1-800-255-3924

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
 Eye irritation 2A H319 Causes serious eye irritation.
 Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.
 Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labeling:

Acetone
butyl acetate

Hazard statements

Extremely flammable aerosol. Pressurized container: may burst if heated.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Avoid breathing fume/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 Get medical advice/attention if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store in a well ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

Effects of chronic overexposure:

Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	15-25%
74-98-6	propane	15-25%
106-97-8	n-butane	5-10%
7727-43-7	barium sulfate	5-10%
110-19-0	Isobutyl Acetate	5-10%
2807-30-9	Glycol Ether EP	≥5-<10%
123-86-4	butyl acetate	1-5%
108-65-6	PM acetate	1-5%

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 08/07/2025

Revised On 08/07/2025

Trade name: DW ORANGE

(Contd. of page 1)

107-87-9 Methyl Propyl Ketone

1-5%

4 First-aid measures

Description of first aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards:

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

Additional information

Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions:

Do not allow product to reach sewage systems or ground water.

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Fire/explosion protection:

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Conditions for safe storage:

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

67-64-1 Acetone

PEL Long-term value: 2400 mg/m³, 1000 ppmREL Long-term value: 590 mg/m³, 250 ppmTLV Short-term value: 1187 mg/m³, 500 ppmLong-term value: 594 mg/m³, 250 ppm

A4, BEI

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppmREL Long-term value: 1800 mg/m³, 1000 ppm

TLV see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL Long-term value: 1900 mg/m³, 800 ppmTLV Short-term value: 2370 mg/m³, 1000 ppm (EX)

7727-43-7 barium sulfate

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fractionREL Long-term value: 10* 5** mg/m³
*total dust **respirable fractionTLV Long-term value: 5* mg/m³
*inhalable fraction; E

110-19-0 Isobutyl Acetate

PEL Long-term value: 700 mg/m³, 150 ppm

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 08/07/2025

Revised On 08/07/2025

Trade name: DW ORANGE

(Contd. of page 2)

REL	Long-term value: 700 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm
	Long-term value: 238 mg/m ³ , 50 ppm

123-86-4 butyl acetate

REL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm
	Long-term value: 238 mg/m ³ , 50 ppm

108-65-6 PM acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

107-87-9 Methyl Propyl Ketone

REL	Long-term value: 700 mg/m ³ , 200 ppm
REL	Long-term value: 530 mg/m ³ , 150 ppm
TLV	Short-term value: 529 mg/m ³ , 150 ppm

Ingredients with biological limit values:**67-64-1 Acetone**

BEI	25 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

Exposure controls**Hygienic protection:**

Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.

Eye protection:

The glove material must be impermeable and resistant to the substance.
Tightly sealed goggles

9 Physical and chemical properties**General Information:****Physical state**

Aerosol

Odor:

Aromatic

Odor threshold:

Not determined.

Melting point/Melting range

Undetermined.

Boiling point:

-44.5 °C (-48.1 °F)

Flammability:

Extremely flammable.

Lower Explosion Limit:

1.7 Vol %

Upper Explosion Limit:

10.9 Vol %

Flash point:

-19 °C (-2.2 °F)

Decomposition temperature:

Not determined.

pH-value:

Not determined.

Viscosity:

Not determined.

Kinematic:

Not determined.

Dynamic:

Not determined.

Solubility:

Not determined.

Vapor pressure:

40 PSI, 2750 hPa

Vapor Pressure:

40 PSI, 2750 hPa

Relative Density:

Between 0.77 and 0.85 (Water equals 1.00)

Vapor density

Not determined.

Particle characteristics

Not applicable.

Appearance:

Aerosol.

Ignition temperature:

Product is not self-igniting.

Danger of explosion:

Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.

Water:

In use, may form flammable/explosive vapour-air mixture.

Evaporation rate

0.0 %

Partition coefficient: n-octanol/water:

Not applicable.

Not determined.

10 Stability and reactivity**Conditions to avoid:**

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

Possibility of hazardous reactions:

No dangerous reactions known.

Conditions to avoid

No further relevant information available.

Incompatible materials:

No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 08/07/2025

Revised On 08/07/2025

Trade name: DW ORANGE

Hazardous decomposition: No dangerous decomposition products known.

(Contd. of page 3)

11 Toxicological information

LD/LC50 values that are relevant for classification:

110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rabbit)

123-86-4 butyl acetate

Oral LD50 14,000 mg/kg (rat)

Inhalative LC50/4 h >21 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

Aspiration hazard

Interactive effects No interactive effects between components are known.

IARC (International Agency for Research on Cancer)

1309-37-1 red iron oxide pigment

3

NTP (National Toxicology Program)

None of the ingredients is listed.

Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological information

Toxicity

Aquatic toxicity:

Hazardous for water, do not empty into drains.

Persistence and degradability:

The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential:

No further relevant information available.

Mobility in soil:

No further relevant information available.

Results of PBT and vPvB assessment

PBT:

Not applicable.

vPvB:

Not applicable.

Other adverse effects:

No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Waste treatment methods

Recommendation:

Completely empty cans should be recycled.

Recommended cleansing agent:

Water, if necessary with cleansing agents.

14 Transport information

UN-Number

UN1950

DOT

UN1950

UN proper shipping name:

DOT

Aerosols, flammable, containing substances in Class 8, Packing Group II

Transport hazard class(es):

Class

2.1 Gases

Label

2.1+8

DOT

Packaging Group:

--

Special precautions for user:

Warning: Gases

EMS Number:

F-D,S-U

15 Regulatory information

Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

Toxic Substances Control Act

(TSCA):

All ingredients are found on the inventory list of substances.

Consumer Product Safety

Comission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 08/07/2025

Revised On 08/07/2025

Trade name: DW ORANGE

(Contd. of page 4)

Hazardous Air Pollutants

108-10-1	methyl isobutyl ketone
1330-20-7	xylene (mix)
100-41-4	ethyl benzene
136-52-7	cobalt bis(2-ethylhexanoate)

California Proposition 65 chemicals known to cause cancer:

108-10-1	methyl isobutyl ketone
100-41-4	ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-10-1	methyl isobutyl ketone
----------	------------------------

CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1	Acetone	I
7727-43-7	barium sulfate	D, CBD(inh), NL(oral)
110-19-0	Isobutyl Acetate	D

GHS label elements**Precautionary statements**

The product is classified and labeled according to the Globally Harmonized System (GHS).
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Avoid breathing fume/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 Get medical advice/attention if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store in a well ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 A Chemical Safety Assessment has not been carried out.

Chemical safety assessment:**16 Other information**

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs**Date of previous version** 11/07/2024**Date of preparation** 08/07/2025**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 EPA: Environmental Protection Agency
 IARC: International Agency for the Research of Cancer
 NIOSH: National Institute for Occupational Safety and Health
 TSCA: Toxic Substances Control Act
 CPSC: Consumer Product Safety Commission
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Aerosols 1: Aerosols – Category 1
 Eye irritation 2A: Serious eye damage/eye irritation – Category 2A
 Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
 Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2