Date of issue: 08/07/2025 Revised On 08/07/2025

### 1 Identification of the substance and manufacturer

Trade name: **NI DARK GRAY** 

Other means of identification

80-1118 Product code:

Article category

Paint and coatings application. Recommended use:

Any that differs from the recommended use. Uses advised against:

Kimball Midwest Manufacturer/Supplier: 4800 Roberts Road Columbus, OH 43228

800-233-1294

www.kimballmidwest.com Emergency telephone number: ChemTrec: 800-424-9300

#### 2 Hazard(s) identification

#### Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

Eye irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Reproductive toxicity 2 H361 Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 





GHS02 GHS07 GHS08

Signal word Danger

**Hazard statements** Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use. **Precautionary statements** 

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray.

Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store in a well ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 3 Composition/information on ingredients

**Chemical characterization: Mixtures** 

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions

Chemical Description.		escription.	This product is a mixture of the substances listed below with horniazardous additions.	
Dangerous components:		components:		
	67-64-1	Acetone		25-50%
		propane		15-25%
	1317-65-3	Calcium Carbonate		10-15%
	106-97-8	n-butane		5-10%
		Toluene		≥5-<10%
	64742-89-8	VM&P Naphtha		1-5%
		PM acetate		1-5%
	13463-67-7	titanium dioxide		1-5%
	108-10-1	methyl isobutyl ketone		1-5%
		Isobutyl Acetate		1-5%
	107-87-9	Methyl Propyl Ketone		1-5%

(Contd. on page 2)

## Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: NI DARK GRAY

(Contd. of page 1) 1-5% 2807-30-9 Glycol Ether EP

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse mouth with water. Do not induce vomiting. Dizziness

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

Special hazards:

Protective equipment for

firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective

equipment and emergency procedures:

Methods and material for

containment and cleaning up:

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

108-10-1 methyl isobutyl ketone

Long-term value: 410 mg/m³, 100 ppm

PEL (USA)

REL (USA) TLV (USA)

Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Store lockéd up.

9 Evnesure controls/nersonal protection							
8 Exposure controls/personal protection							
Components with limit values that require monitoring at the workplace:							
0. 0	67-64-1 Acetone						
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm						
REL (USA)	Long-term value: 590 mg/m³, 250 ppm						
TLV (USA)	Short-term value: 1187 mg/m³, 500 ppm						
	Long-term value: 594 mg/m³, 250 ppm A4, BEI						
74-98-6 prop	·						
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm						
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm						
TLV (USA)	see Appendix F Minimal oxygen content ( D, EX)						
106-97-8 n-butane							
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm						
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm (EX)						
108-88-3 Tol	108-88-3 Toluene						
PEL (USA)	Long-term value: 200 ppm						
	Ceiling limit value: 300; 500* ppm						
	*10-min peak per 8-hr shift						
REL (USA)	Short-term value: 560 mg/m³, 150 ppm						
TI \ ( (110 A )	Long-term value: 375 mg/m³, 100 ppm						
TLV (USA)	Long-term value: 20 ppm BEI, OTO, A4						
64742-89-8 \	/M&P Naphtha						
TLV (USA)	Long-term value: 100 ppm						
` ,	Skin, A3						
108-65-6 PM acetate							
WEEL (USA)	Long-term value: 50 ppm						

Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm Short-term value: 307 mg/m³, 75 ppm Long-term value: 82 mg/m³, 20 ppm BEI, A3 (Contd. on page 3)

## Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: NI DARK GRAY

(Contd. of page 2) 110-19-0 Isobutyl Acetate Long-term value: 700 mg/m³, 150 ppm PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm TLV (USA) 107-87-9 Methyl Propyl Ketone PEL (USA) Long-term value: 700 mg/m³, 200 ppm REL (USA) Long-term value: 530 mg/m³, 150 ppm TLV (USA) Short-term value: 529 mg/m<sup>3</sup>, 150 ppm Ingredients with biological limit values: 67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

## 108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

#### 108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L Medium: urine Time: end of shift Parameter: MIBK

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile aloves.

The glove material must be impermeable and resistant to the substance. Eye protection: Tightly sealed goggles

#### 9 Physical and chemical properties

Vapor pressure:

Physical state Aerosol Odor: Aromatic Odor threshold: Not determined. Melting point/Melting range Undetermined. -44.5 °C (-48.1 °F) **Boiling point:** Flammability: Extremely flammable.

1.7 Vol % 10.9 Vol % Lower Explosion Limit: **Upper Explosion Limit:** Flash point: -19 °C (-2.2 °F) Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined. pH-value: Not determined. Viscosity: Not determined. Solubility: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Particle characteristics Not applicable. Appearance: Aerosol.

Ignition temperature: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Not determined.

Water: 0.0 %

**Evaporation rate** Not applicable.

(Contd. on page 4)

Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: NI DARK GRAY

Partition coefficient: n-octonal/water: Not determined.

(Contd. of page 3)

#### 10 Stability and reactivity

Reactivity:

Stable at normal temperatures.

Conditions to avoid:

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Chemical stability: Not fully evaluated.

Possibility of hazardous reactions:

No dangerous reactions known.

Incompatible materials: Hazardous decomposition:

No further relevant information available. No dangerous decomposition products known.

#### 11 Toxicological information

LD/LC50 v	LD/LC50 values that are relevant for classification:					
108-65-6 F	108-65-6 PM acetate					
Oral	LD50	8,500 mg/kg (rat)				
Inhalative	LC50/4 h	35.7 mg/l (rat)				
13463-67-	3-67-7 titanium dioxide					
Oral	LD50	>20,000 mg/kg (rat)				
Dermal	LD50	>10,000 mg/kg (rabbit)				
Inhalative	LC50/4 h	>6.82 mg/l (rat)				
108-10-1 n	108-10-1 methyl isobutyl ketone					
Oral	LD50	2,100 mg/kg (rat)				
Dermal	LD50	16,000 mg/kg (rab)				
Inhalative	LC50/4 h	11 mg/l (ATE)				
		8.3-16.6 mg/l (rat)				
110-19-0 l	110-19-0 Isobutyl Acetate					
Oral	LD50	4.763 mg/kg (rabbit)				

4,763 mg/kg (rabbit) LD50

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

#### 12 Ecological information

Aquatic toxicity:

Hazardous for water, do not empty into drains.

Persistence and degradability: Other information:

The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's),

perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkýl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

#### 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

#### 14 Transport information

**UN-Number** UN1950 DOT UN1950

Aerosols, flammable DOT 1950 AEROSOLS ADR

Transport hazard class(es):

Special marking (IATA):

2.1 Gases

Packaging Group:

Special precautions for user: Warning: Gases

**EMS Number:** F-D,S-Ŭ

**UN "Model Regulation": UN 1950 AEROSOLS, 2.1** 

## 15 Regulatory information

## SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

(Contd. on page 5)

I D

# Safety Data Sheet

Date of issue: 08/07/2025 Revised On 08/07/2025

Trade name: NI DARK GRAY

	(Contd. of page 4		
	cific toxic chemical listings):		
108-88-3 Toluene			
108-10-1 methyl isobutyl	ketone		
Toxic Substances Cont			
(TSCA):	All ingredients are found on the inventory list of substances.		
Canadian Domestic Sul	********		
(DSL): Consumer Product Safe	All ingredients are listed or exempted.		
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
	55 chemicals known to cause cancer:		
13463-67-7 titanium diox			
108-10-1 methyl isobu			
1333-86-4 Carbon blac	k		
100-41-4 ethyl benzer	ne ne		
Prop 65 chemicals known to cause birth defects or reproductive harm:			
108-88-3 Toluene			
108-10-1 methyl isobutyl	ketone		
EPA:			
67-64-1 Acetone			

## 16 Other information

108-10-1 methyl isobutyl ketone 110-19-0 Isobutyl Acetate

Contact: Regulatory Affairs