



The following SDS references the products
below: WD-40 WD-40 ® Precision Pen Vendor
Item Number: N/A

Manufactured By:
WD-40 Company

Distributed by Kimball Midwest with the KM product-
identification number:
80-621



Safety Data Sheet

1 - Chemical Product and Company Identification

Trade Name: WD-40 Precision Pen	Manufacturer: WD-40 Company
Product Use: Lubricant, Penetrant, Drives Out Moisture, and Protects Surfaces from Corrosion	Address: 9715 Businesspark Avenue San Diego, California, USA 92131
Restrictions on Use: None identified.	Telephone:
SDS Date of Preparation: November 13, 2024	Emergency: 1-888-324-7596
	Information: 1-888-324-7596
	Chemical Spills: 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls)

2 – Hazards Identification

HCS 2024/GHS Classification:

Flammable Liquid Category 3

Aspiration Toxicity Category 1

Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)

Note: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to larger containers sold for industrial/professional use.

Label Elements:



DANGER!

Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Prevention

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. – No smoking.

Keep container tightly closed.

Ground and bond containers and receiving equipment.

Use explosion-proof electrical equipment.

Use non-sparking tools.

Take action to prevent static discharge.

Avoid breathing mists or vapors.

Use only outdoors or in a well-ventilated area.

Wear eye protection.

Response

IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

In case of fire: Use water fog, dry chemical, carbon dioxide or foam to extinguish.

Storage

Store locked up.

Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Disposal

Dispose of contents and containers in accordance with local and national regulations.

3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent	HSC 2024/GHS Classification
LVP Aliphatic Hydrocarbon	64742-47-8	40-50%	Aspiration Toxicity Category 1
Petroleum Base Oil	64742-56-9 64742-65-0 64742-53-6 64742-54-7 64742-71-8	<35%	Not Hazardous
Aliphatic Hydrocarbon	64742-47-8	20-30%	Flammable Liquid Category 3 Aspiration Toxicity Category 1 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)

Note: The specific chemical identity and exact percentages are a trade secret.

4 – First Aid Measures

Ingestion (Swallowed): Ingestion is an unlikely route of exposure for solid products. The liquid content in the pen is an Aspiration hazard. If the liquid contents are swallowed, DO NOT induce vomiting. Call a physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: If there is contact with the liquid contents, flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.

Skin Contact: If there is contact with the liquid contents, wash with soap and water. If irritation develops and persists, get medical attention.

Inhalation (Breathing): If liquid contents are inhaled and If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

Signs and Symptoms of Exposure: Harmful or fatal if swallowed. Aspiration of liquid content into the lungs during swallowing or vomiting may cause lung damage. Contact with liquid may cause eye and skin irritation. Inhalation of mists or vapors may cause drowsiness, dizziness, and other nervous system effects. Prolonged or repeated skin contact may cause drying of the skin.

Indication of Immediate Medical Attention/Special Treatment Needed: Immediate medical attention is needed for ingestion.

5 – Fire Fighting Measures

Suitable (and unsuitable) Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

Specific Hazards Arising from the Chemical: This product contains a flammable liquid but the small amount in the pen reduces any fire hazard. Combustion will produce oxides of carbon and hydrocarbons.

Special Protective Equipment and Precautions for Fire-Fighters: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water.

6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area.

Methods and Materials for Containment/Cleanup: Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors. Use with adequate ventilation. Keep away from heat, sparks, hot surfaces, and open flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children.

Conditions for Safe Storage: Store in a cool, well-ventilated area, away from incompatible materials. NFPA 30 Class II Liquid.

8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
LVP Aliphatic Hydrocarbon	1200 mg/m ³ TWA (manufacturer recommended)
Petroleum Base Oil	5 mg/m ³ TWA (Inhalable) ACGIH TLV (as Mineral oil) 5 mg/m ³ TWA OSHA PEL (as Oil mist, mineral)
Aliphatic Hydrocarbon	1200 mg/m ³ TWA (manufacturer recommended)

The Following Controls are Recommended for Normal Consumer Use of this Product

Engineering Controls: No special ventilation required for normal use.

Personal Protection:

Eye Protection: None required for normal use. Avoid eye contact.

Skin Protection: None required for normal use. Avoid prolonged skin contact.

Respiratory Protection: None needed for normal use with adequate ventilation.

For Bulk Processing or Workplace Use the Following Controls are Recommended

Engineering Controls: No special ventilation required for normal use. Use adequate general and local exhaust ventilation in bulk processing to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: None required for normal use. Safety goggles recommended for bulk processing.

Skin Protection: None required for normal use. Wear chemical resistant gloves for bulk processing.

Respiratory Protection: None required for normal use. For bulk processing: if the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

Work/Hygiene Practices: Wash with soap and water after handling.

9 – Physical and Chemical Properties

Physical State:	Liquid	Color:	Light green to amber
Odor:	Mild petroleum odor	Flammable Limits: (Solvent Portion)	LEL: 0.8% UEL: 5.6%
Relative Vapor Density:	Greater than 1 (air=1)	Vapor Pressure:	1 psi @38°C (100°F) ASTM D323
pH:	Not Applicable	Relative Density:	0.8 – 0.82 @ 60°F
Melting/Freezing Point:	Not established	Solubilities:	Insoluble in water
Boiling Point/Range:	322 - 388°F (161 - 198°C)	Partition Coefficient; n-octanol/water:	Not established
Flash Point:	138°F (59°C) Tag Closed Cup	Autoignition Temperature:	Not established
Particle Characteristics:	Not applicable	Decomposition Temperature:	Not established
Flammability:	Flammable liquid	Kinematic Viscosity:	2.79-2.96 cSt @ 100°F
VOC:	24.8% MIR=0.43 gO ₃ /gVOC (204 grams/liter)	Pour Point:	-63°C (-81.4°F) ASTM D-97

10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions

Chemical Stability: Stable

Possibility of Hazardous Reactions: May react with strong oxidizers generating heat.

Conditions to Avoid: Avoid heat, sparks, flames, and other sources of ignition.

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

11 – Toxicological Information

Symptoms of Overexposure: Each pen contains only a small amount of liquid. No effects of exposure are expected in normal use.

Inhalation: High concentrations of liquid contents may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness, and nausea.

Skin Contact: Prolonged and/or repeated contact with the liquid contents may produce mild irritation and defatting with possible dermatitis.

Eye Contact: Contact with the liquid contents may be mildly irritating to eyes. May cause redness and tearing.

Ingestion: This product has low oral toxicity. Swallowing liquid content may cause gastrointestinal irritation, nausea, vomiting and diarrhea. The liquid in this product is an aspiration hazard. If swallowed, can enter the lungs, and may cause chemical pneumonitis, severe lung damage and death.

Chronic Effects: None expected.

Carcinogen Status: None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

Reproductive Toxicity: None of the components is considered a reproductive hazard.

Numerical Measures of Toxicity:

Acute Toxicity Estimates: Oral > 5,000 mg/kg; Dermal >2,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

12 – Ecological Information

Ecotoxicity: No specific aquatic toxicity data is currently available; however, components of this product are not expected to be harmful to aquatic organisms

Persistence and Degradability: Components are readily biodegradable.

Bioaccumulative Potential: Bioaccumulation is not expected based on an assessment of the ingredients.

Mobility in Soil: No data available

Other Adverse Effects: None known

13 - Disposal Considerations

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations.

14 – Transportation Information

DOT Surface Shipping Description: Excepted from Hazmat (49CFR 173.150 (F)).

IMDG Shipping Description: UN1268, Petroleum Distillates, n.o.s. 3, PG III

ICAO Shipping Description: UN1268, Petroleum Distillates, n.o.s. 3, PG III

NOTE: WD-40 Company does not test containers to assure that they meet the pressure differential and other requirements for transport by air. We do not recommend that our products be transported by air.

15 – Regulatory Information

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have

more stringent release reporting requirements. Report spills required under federal, state, and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Refer to Section 2 for the OSHA Hazard Classification.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not require a California Proposition 65 warning.

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

16 – Other Information

HMIS Hazard Rating:

Health – 1 (slight hazard), Fire Hazard – 2 (moderate hazard), Physical Hazard – 0 (minimal hazard)

Revision Date: November 13, 2024

Supersedes: May 31, 2023

Revision Summary: Updates to conform to HCS 2024 – changes to sections 2, 3 and 9.

Prepared by: IHSC, LLC. Milford, CT, USA

Reviewed By: I. Kowalski

Regulatory Affairs Dept.

1022200/No.00192603