

Safety Data Sheet

Date Issued: May 6, 2025

Revision No:

Supersedes Date: New

Section 1. Product Description

1.1 Product Name: 077 Multi-Purpose Spray Adhesive 80237

1.2 Recommended Use: Industrial adhesive applications 1.3

Manufacturer: and address: Kimball Midwest
4800 Roberts Road
Columbus Ohio 43228
Phone: 800-233-1294

Emergency Contact: 800-424-9300 (CHEMTREC- Transportation Spill Response 24 hours)

Section 2. Hazard Identification

Classification in accordance with 29 CFR 1900.1200

2.1 Hazard Classification

Extremely Flammable Aerosol: Category 1

2.2.1 Label elements

Signal Word: Danger

DANGER

Symbols



Hazard Statements:

Extremely flammable aerosol.

Pressurized Container: may burst if heated

Causes serious eye irritation.

Causes skin irritation

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

PRECAUTIONARY STATEMENTS:

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces and other ignition sources– No smoking.
Do not spray on open flames or other ignition sources
Do not pierce or burn even after use
Do not breathe dust/fumes/gas/vapor/mist/spray.
Use only outdoors or in well-ventilated areas.
Wear protective clothing and eye/face protection.
Do not eat, drink, or smoke when using this product.
Wash thoroughly after handling.

Response:

IF INHALED: Remove to fresh air and keep comfortable for breathing.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water and shower. If irritation persist, seek medical attention. Continue to rinse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens if present and easy to do. Continue rinsing. If irritation persist, seek medical attention.

STORAGE:

Protect from sunlight.
Do not expose to temperatures exceeding 122 oF (50 oC)
Store locked up in a well-ventilated place.

DISPOSAL:

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3. *Composition/ Information on Ingredients*

Chemical Name	C.A.S. Number	%
Acetone	67-64-1	10 - 25 %
2-Methylpentane	107-83-5	30 - 40 %
Propane	74-98-6	15 - 25 %

Section 4. *First Aid Measures*

Skin Contact: Wash with plenty of water. Wash contaminated clothing after use.

Inhalation: Remove person to fresh air and keep comfortable for breathing. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek medical assistance. If breathing has stopped, give artificial respiration.

Eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Ingestion: Rinse mouth. If you feel unwell get medical advice/attention.

Section 5. *Firefighting Procedures*

Extinguishing Media: Use water spray, dry chemical, CO₂, or appropriate foam.

In case of fire, use a firefighting agent for flammable liquid.

Hazardous decomposition or by product: Aldehydes, hydrocarbons, carbon monoxide and carbon dioxide, ketones, oxides of nitrogen, sulfur and other toxic vapor, gas, and particulate.

Special protective actions for fire-fighters: Keep containers cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, bunker coat and pants, face mask, and protective covering for exposed area of head.

Section 6. *Accidental Release Measures*

Personal Precautions: Use personal protective equipment. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation. Remove all sources of ignition. Vapors can accumulate in low areas.

Clean-Up: Cover with commercially available nonflammable inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Collect waste and dispose of in accordance with all applicable local/state/federal regulations.

SECTION 7. *Handling and Storage*

Handling: Avoid breathing vapors. Use personal protection equipment as required. In case of inadequate ventilation wear respiratory protection. Do not eat, drink, or smoke when using this product. Wash contaminated clothing and skin after use.

Storage: Store in a well-ventilated space. Protect from direct sunlight.

SECTION 8. Protection Information

Hazardous Component	Authority	Type	Limit
Acetone	ACGIH	TWA	250 ppm
Acetone	ACGIH	STEL	500 ppm
Acetone	OSHA	TWA	1000 ppm
2-Methylpentane	ACGIH	TWA	500 ppm
2-Methylpentane	ACGIH	STEL	500 ppm
Propane	OSHA	TWA	1000 ppm
Propane	ACGIH	TWA	1000 ppm

SOURCES OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene

IARC: International Agency for the Research on Cancer

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

WEEL Workplace Environmental Exposure Level

Control Parameters

Engineering Measures: Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment (PPE):

Eyes/Face: Safety goggles or safety glasses with side shields.

Skin: Protective gloves such as Viton, PVA or equivalent and impervious clothing.

Respiratory: In operations where exposure limits are exceeded, use a NIOSH approved respirator suitable for the specific work conditions.

Hygiene: Avoid contact with skin, eyes, and clothing. Wash promptly with soap and water if skin is contaminated. Remove and wash contaminated clothing. Do not eat, drink, or smoke when using.

SECTION 9. Physical Data

Odor, Color: Organic solvent odor, clear or red in color
Boiling point: Not determined
Vapor Pressure: Not Determined
Vapor Density: Not Determined
Specific Gravity: .60 – .70 g/cc
Solubility in Water: Negligible
Volatile Organic Compounds: 55 – 65 % by weight
Volatile Organic Compounds: 350 – 450 g/L
Flash Point: -156° F (-104 C)
LEL – 2.2% volume
UEL – 9.5 % volume

SECTION 10. *Stability and Reactivity*

Chemical Stability: Stable under normal conditions.

Conditions to Avoid: Avoid high temperatures.

Incompatible Materials: None known.

Hazardous Polymerization: Will not occur.

Hazardous By-Products: Combustion may result in formation of aldehydes, hydrocarbons, carbon monoxide and carbon dioxide.

SECTION 11. *Toxicological Information*

Typical Routes of Entry: Inhalation, skin absorption, eye contact

Aspiration Hazard: No data

Acute toxicity: No data

Irritation: No data

Corrosivity: No data

Sensitization: No data

SECTION 12. *Ecological Data*

Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

SECTION 13. *Disposal Consideration*

Dispose of in accordance with all applicable local/regional/national/international/state/federal regulations.

SECTION 14. *Transportation Information*

DOT Proper Shipping Name:

Aerosols – Domestic

Aerosol Cans, Limited Quantity

Aerosols – Air and Ocean

UN1950, Aerosol, Flammable, 2.1

SECTION 15. *Regulatory Information*

311/312 Hazard Categories:

Fire Hazard – Yes

Pressure Hazard – Yes

Reactivity Hazard – No

Immediate Hazard – Yes

Delayed Hazard – Yes

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65: None known.

HMIS Hazard Rating – NFPA Hazard classification

0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

Health: 2

Flammability: 3

Reactivity: 0

Special Hazard: None

SECTION 16. *Other Information*

DISCLAIMER: The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

