

## Safety Data Sheet

Date of issue: 02/17/2026

Revised On 02/17/2026

## 1 Identification of the substance and manufacturer

Trade name: FLUOR PINK SURVEY MRK PAINT  
 Other means of identification  
 Product code: KB00801042  
 Article category  
 Recommended use: Paint and coatings application.  
 Uses advised against: Any that differs from the recommended use.  
 Manufacturer/Supplier:

Kimball Midwest  
 4800 Roberts Road  
 Columbus Ohio  
 43228  
 Phone: 800-233-1294

Emergency telephone number: Chemtrec 800-424-9300

## 2 Hazard(s) identification

## Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.  
 Skin irritation 2 H315 Causes skin irritation.  
 Reproductive toxicity 2 H361 Suspected of damaging fertility or the unborn child.  
 Specific target organ toxicity (single exposure) 3 H335 May cause respiratory irritation.  
 Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:  
GHS Hazard pictograms

GHS02 GHS07 GHS08

## Signal word

## Hazard statements

Danger  
 Extremely flammable aerosol. Pressurized container: may burst if heated.  
 Causes skin irritation.  
 Suspected of damaging fertility or the unborn child.  
 May cause respiratory irritation.  
 May cause damage to organs through prolonged or repeated exposure.  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Avoid breathing fume/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 Wear protective gloves.  
 If on skin: Wash with plenty of water.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 Get medical advice/attention if you feel unwell.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 Store in a well ventilated place. Keep container tightly closed.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## Precautionary statements

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

|            |                   |          |
|------------|-------------------|----------|
| 1317-65-3  | Calcium Carbonate | ≥20-≤25% |
| 64742-89-8 | VM&P Naphtha      | 15-25%   |
| 74-98-6    | propane           | 15-25%   |
| 106-97-8   | n-butane          | 5-10%    |
| 64742-47-8 | Mineral Spirits   | 5-10%    |
| 108-88-3   | Toluene           | ≥5-<10%  |
| 67-63-0    | Isopropyl Alcohol | 1-5%     |
| 142-82-5   | heptane           | 1-5%     |

## 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.  
 After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.  
 After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 2)

## Safety Data Sheet

Date of issue: 02/17/2026

Revised On 02/17/2026

Trade name: FLUOR PINK SURVEY MRK PAINT

(Contd. of page 1)

**After swallowing:** Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects:** Dizziness

**Indication of any immediate medical attention needed:** No further relevant information available.

**5 Fire-fighting measures**

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.

**Special hazards:** No further relevant information available.

**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Use respiratory protective device against the effects of fumes/dust/aerosol.

**Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.

**7 Handling and storage**

**Precautions for safe handling:** Use only in well ventilated areas.

**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****64742-89-8 VM&P Naphtha**

TLV (USA) Long-term value: 100 ppm  
Skin, A3

**74-98-6 propane**

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content ( D, EX)

**106-97-8 n-butane**

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm  
(EX)

**108-88-3 Toluene**

PEL (USA) Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV (USA) Long-term value: 20 ppm  
BEI, OTO, A4

**67-63-0 Isopropyl Alcohol**

PEL (USA) Long-term value: 980 mg/m<sup>3</sup>, 400 ppm

REL (USA) Short-term value: 1225 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 980 mg/m<sup>3</sup>, 400 ppm

TLV (USA) Short-term value: 984 mg/m<sup>3</sup>, 400 ppm  
Long-term value: 491 mg/m<sup>3</sup>, 200 ppm  
BEI, A4

**142-82-5 heptane**

PEL (USA) Long-term value: 2000 mg/m<sup>3</sup>, 500 ppm

REL (USA) Long-term value: 350 mg/m<sup>3</sup>, 85 ppm  
Ceiling limit value: 1800\* mg/m<sup>3</sup>, 440\* ppm  
\*15-min

TLV (USA) Short-term value: 400 ppm  
Long-term value: 200 ppm  
OTO

(Contd. on page 3)

## Safety Data Sheet

Date of issue: 02/17/2026

Revised On 02/17/2026

Trade name: FLUOR PINK SURVEY MRK PAINT

(Contd. of page 2)

**Ingredients with biological limit values:****108-88-3 Toluene**

|           |                                                                                                                |
|-----------|----------------------------------------------------------------------------------------------------------------|
| BEI (USA) | 0.02 mg/L<br>Medium: blood<br>Time: prior to last shift of workweek<br>Parameter: Toluene                      |
|           | 0.03 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Toluene                                         |
|           | 0.3 mg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: o-Cresol with hydrolysis (background) |

**67-63-0 Isopropyl Alcohol**

|           |                                                                                                                   |
|-----------|-------------------------------------------------------------------------------------------------------------------|
| BEI (USA) | 40 mg/L<br>Medium: urine<br>Time: end of shift at end of workweek<br>Parameter: Acetone (background, nonspecific) |
|-----------|-------------------------------------------------------------------------------------------------------------------|

|                             |                                                                                                                                                                                                                                                                                                        |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Hygienic protection:</b> | Immediately remove all soiled and contaminated clothing.<br>Wash hands after use.<br>Store protective clothing separately.<br>Avoid contact with the skin.<br>Avoid contact with the eyes and skin.<br>Do not eat or drink while working.                                                              |
| <b>Breathing equipment:</b> | A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene. |
| <b>Hand protection:</b>     | Nitrile gloves.<br>The glove material must be impermeable and resistant to the substance.                                                                                                                                                                                                              |
| <b>Eye protection:</b>      | Safety glasses                                                                                                                                                                                                                                                                                         |

**9 Physical and chemical properties**

|                                                |                                           |
|------------------------------------------------|-------------------------------------------|
| <b>Physical state</b>                          | Aerosol                                   |
| <b>Odor:</b>                                   | Aromatic                                  |
| <b>Odor threshold:</b>                         | Not determined.                           |
| <b>Melting point/Melting range</b>             | Undetermined.                             |
| <b>Boiling point:</b>                          | -44.5 °C (-48.1 °F)                       |
| <b>Flammability:</b>                           |                                           |
| <b>Lower Explosion Limit:</b>                  | 1.7 Vol %                                 |
| <b>Upper Explosion Limit:</b>                  | 10.9 Vol %                                |
| <b>Flash point:</b>                            | -19 °C (-2.2 °F)                          |
| <b>Flammability (solid, gas):</b>              |                                           |
| <b>Decomposition temperature:</b>              | Not determined.                           |
| <b>pH-value:</b>                               | Not determined.                           |
| <b>Viscosity:</b>                              | Not determined.                           |
| <b>Solubility:</b>                             | Not determined.                           |
| <b>Vapor pressure:</b>                         | Not determined.                           |
| <b>Relative Density:</b>                       | Between 0.77 and 0.85 (Water equals 1.00) |
| <b>Vapor density</b>                           | Not determined.                           |
| <b>Particle characteristics</b>                | Not applicable.                           |
| <b>Appearance:</b>                             | Aerosol.                                  |
| <b>Ignition temperature:</b>                   | Product is not self-igniting.             |
| <b>Danger of explosion:</b>                    | Not determined.                           |
| <b>Evaporation rate</b>                        | Not applicable.                           |
| <b>Partition coefficient: n-octanol/water:</b> | Not determined.                           |

**10 Stability and reactivity**

|                                            |                                                                                                  |
|--------------------------------------------|--------------------------------------------------------------------------------------------------|
| <b>Reactivity:</b>                         | Stable at normal temperatures.                                                                   |
| <b>Conditions to avoid:</b>                | Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. |
| <b>Chemical stability:</b>                 | Not fully evaluated.                                                                             |
| <b>Possibility of hazardous reactions:</b> | No dangerous reactions known.                                                                    |
| <b>Incompatible materials:</b>             | No further relevant information available.                                                       |
| <b>Hazardous decomposition:</b>            | No dangerous decomposition products known.                                                       |

(Contd. on page 4)

## Safety Data Sheet

Date of issue: 02/17/2026

Revised On 02/17/2026

Trade name: FLUOR PINK SURVEY MRK PAINT

(Contd. of page 3)

## 11 Toxicological information

## LD/LC50 values that are relevant for classification:

## 67-63-0 Isopropyl Alcohol

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | 4,570 mg/kg (rat)  |
| Dermal     | LD50     | 13,400 mg/kg (rab) |
| Inhalative | LC50/4 h | 30 mg/l (rat)      |

**Information on toxicological effects:** No data available.  
**Skin effects:** Irritant to skin and mucous membranes.  
**Eye effects:** No irritating effect.  
**Sensitization:** No sensitizing effects known.

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:**  
**Remark:** Toxic for fish

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.  
**Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

**UN-Number** UN1950  
**DOT** UN1950  
**DOT** Aerosols, flammable  
**ADR** 1950 AEROSOLS  
**Transport hazard class(es):**  
**Class** 2.1 Gases  
**Special marking (IATA):**  
**Packaging Group:** --  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

## SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

## SARA Section 313 (Specific toxic chemical listings):

|          |                   |
|----------|-------------------|
| 108-88-3 | Toluene           |
| 67-63-0  | Isopropyl Alcohol |

## Toxic Substances Control Act

(TSCA): All ingredients are found on the inventory list of substances.

## Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

## Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

## California Proposition 65 chemicals known to cause cancer:

|          |               |
|----------|---------------|
| 100-41-4 | ethyl benzene |
|----------|---------------|

## Prop 65 chemicals known to cause birth defects or reproductive harm:

|          |         |
|----------|---------|
| 108-88-3 | Toluene |
|----------|---------|

## EPA:

|          |         |
|----------|---------|
| 142-82-5 | heptane |
|----------|---------|

D

## 16 Other information

**Contact:** Regulatory Affairs

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.