

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : KIMBALL MIDWEST LIQUID ELECTRICAL TAPE - BLACK :
Product code 83526

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : Other adhesives and sealants.

1.3. Details of the supplier of the safety data sheet

Supplier Kimball Midwest
4800 Roberts Road
Columbus Ohio43228
Phone: 800-233-1294

Website : www.kimballmidwest.com

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:
US - Telephone : (800)424-9300 (During office hours only)

EMERGENCY TELEPHONE NUMBER (for DOCTORS only):
Chemtrec 001 703 5273887 (24/7)

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification (HCS §1910.1200) : Flammable liquid, category 2. Skin irritation, category 2. Eye irritation, category 2. Specific target organ toxicity after single exposure, category 3. Specific target organ toxicity — repeated exposure, category 2.

2.2. Label elements

Label elements (1910.1200)
Hazard pictograms :



Signal word : Danger

H- and P-phrases : H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe vapours.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection or face protection.
P302+P352	IF ON SKIN: Wash with plenty of water/soap.
P303+P361 +P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351 +P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see section 4 on the SDS).
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use carbondioxide, foam, dry chemical, water fog to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to an official chemical waste depot.

Additional labelling (for all packaging sizes)

: 23 per cent of the mixture consists of component(s) of unknown acute toxicity.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture.

Information on hazardous substances:

Substance name	Concentration (w/w%)	CAS nr.	Additional CAS nr.	Hazards
Butanone	30 - < 60	78-93-3	-----	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Xylene	10 - < 30	1330-20-7	-----	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 Aquatic Chronic 3; H412
Acetone	5 - <10	67-64-1	-----	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

Substance name	Concentration (w/w%)	CAS nr.	Additional CAS nr.	Hazards
Ethylbenzene	1 - < 5	100-41-4	-----	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373 Aquatic Chronic 3; H412
Talc	1 - < 5	14807-96-6	13376-74-4	-----

Occupational exposure limit(s), if relevant, are listed in section 8. The actual concentration has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variations.

Reference is made to chapter 16 for full text of each relevant H phrase.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures

- Inhalation : Move victim into fresh air. Consult a doctor.
- Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up. Consult a doctor if irritation persists.
- Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor.
- Ingestion : Do not induce vomiting. Do rinse the mouth. Give one glass of water. Never give anything by mouth to an unconscious person. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

- Inhalation : May cause headache, drowsiness, dizziness and a feeling of sickness.
- Skin contact : Irritant. May cause redness.
- Eye contact : Irritant. May cause redness and pain.
- Ingestion : May cause a feeling of sickness, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

- Suitable : Carbondioxide (CO2). Alcohol resistant foam. Dry chemical. Water fog.
- Not suitable : Water jet. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

- Special exposure hazards : None known.
- Hazardous thermal decomposition and combustion products : Carbon monoxide may be evolved if incomplete combustion occurs.

5.3. Advice for firefighters

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

Special protective equipment for fire-fighters : Use adequate respiratory equipment in case of insufficient ventilation.
NFPA hazard rating :



SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with spilled or released material. Keep away from sources of ignition — No smoking. Vapours are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

6.2. Environmental precautions

Environmental precautions : Avoid release of product into sewers, surface water and/or ground water. In case of large spills: contain with dike.
Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Dispose at an authorised waste collection point. Clean contaminated surface preferably with a special cleaner. Avoid use of solvents.

6.4. Reference to other sections

Reference to other sections : See also section 8.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe vapour. Avoid contact with eyes and unnecessary contact to skin. Avoid splashing. Wear protective clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep frost-free, in a cool, dry and well-ventilated place (< 35 °C). Protect from sunlight. Keep away from oxidizing agents. Keep away from food, drink and animal feedingstuffs.
Recommended packaging : Keep only in the original container.
Non recommended packaging : PE and PP.

7.3. Specific end use(s)

Use : Use only as directed.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

8.1. Control parameters

Occupational exposure limits : Occupational exposure limits have not been established for this product.

Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour (mg/m ³)	STEL 15 min (mg/m ³)	Comments	Source
Butanone	US	590	885	-	OSHA
Xylene	US	435	655	-	OSHA
Acetone	US	594	1187	-	OSHA
Talc	US	2	-	Respirable fraction, containing no asbestos, < 1% crystalline silica	OSHA
Talc	US	2	-	resp	NIOSH REL
Talc	US	2	-	respirable particulate matter [2009]	ACGIH TLV
Talc	US	2	-	respirable dust	CAL/OSHA PEL
Carbon Black	US	3	-	Inhalable particulate matter	OSHA


8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.



- Body protection : Use of specific protective industrial clothing is not required for momentary use. Wear suitable protective clothing, overalls or suit, and similar boots in case of frequent or prolonged use and in case of large scale exposure. Suitable material: laminated film. Indication of permeation breakthrough time: not known.
- Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask.
- Hand protection : Wear appropriate safety gloves. Suitable material: laminated film. ± 0,5 mm. Indication of permeation breakthrough time: not known.
- Eye protection : Wear appropriate safety glasses with side shields when there is danger of possible eye contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

*

9.1. Information on basic physical and chemical properties

- Physical state : Liquid.
- Colour : Black.
- Odour : Characteristic.
- Odour threshold : Not known.
- pH : Not applicable. Waterfree product.
- Solubility in water : Not soluble.
- Partition coefficient (n-octanol/water) : Not applicable. Not measured. Not relevant for mixtures.

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

Flash point	: -5 °C	Closed cup.
Flammability (solid, gas)	: Not applicable.	Liquid. See flashpoint.
Auto ignition temperature	: > 183 °C	
Boiling point/boiling range	: 69 °C	
Freezing point	: < 0 °C	
Explosion limits (% in air)	: Not known.	Lower explosion limit in air (%): 1 (Xylene)
	:	Upper explosion limit in air (%): 13 (Acetone)
Oxidising properties	: Not applicable.	Does not contain oxidizing substances.
Decomposition temperature	: Not applicable.	
Viscosity (20°C)	: Not known.	
Viscosity (40°C)	: 2157 mm ² /sec	
Vapour pressure (20°C)	: > 2300 Pa	
Relative vapour density	: Not known	(air = 1)
Relative density (20°C)	: 0,965 g/ml	
Evaporation rate	: Not known.	(n-butyl acetate = 1) Mixture of liquids and solids.
Particle characteristics	: Not applicable.	Liquid.

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

Stability : Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid : See section 7.

10.5. Incompatible materials

Materials to avoid : Keep away from oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products : Not known.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Toxicological (health) effects

No toxicological research has been carried out on this product.

Inhalation

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

Acute toxicity	: Calculated LC50: > 10 mg/l. Ingredients of unknown toxicity: 53 %. ATE: > 5 mg/l. Not classified - based on available data, the classification criteria are not met. May cause damage to organs. Target organ(s): Central nervous system. Effect(s): Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.
Corrosion/irritation	: Not classified - based on available data, the classification criteria are not met.
Sensitisation	: Does not contain substances classified as respiratory sensitiser. Not classified - based on available data, the classification criteria are not met.
Carcinogenicity	: Not expected to be carcinogenic. Not classified - based on available data, the classification criteria are not met.
Mutagenicity	: Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.
Skin contact	
Acute toxicity	: Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 5000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
Corrosion/irritation	: Irritant. May cause redness. Repeated exposure may cause skin dryness or cracking.
Sensitisation	: Does not contain skin sensitisers. Not classified - based on available data, the classification criteria are not met.
Mutagenicity	: Does not contain mutagenic substances. Not classified - based on available data, the classification criteria are not met.
Eye contact	
Corrosion/irritation	: Irritant.
Ingestion	
Acute toxicity	: Calculated LD50: > 2723 mg/kg.bw. Ingredients of unknown toxicity: 23 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
Aspiration	: Highly viscous liquid. Not classified - based on available data, the classification criteria are not met. Contains a substance/substances with an aspiration hazard. After ingestion, at vomiting, risk of aspiration in the lungs.
Chronic toxicity (STOT RE)	: Possibility of organ or organ system damage due to prolonged exposure. Target organ(s): Central nervous system. Effect: Repeated exposure affects the nervous system. May cause toxic encephalopathy.
Corrosion/irritation	: May cause a feeling of sickness, vomiting and diarrhoea.
Carcinogenicity	: Not expected to be carcinogenic. Not classified - based on available data, the classification criteria are not met.
Mutagenicity	: Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.
Reprotoxicity	: Development: Not expected to be reprotoxic. Development: Not classified - Based on available data, the classification criteria are not met. Fertility: not expected to be reprotoxic. Fertility: Not classified - based on available data, the classification criteria are not met.

11.2. Information on other hazards

IARC	: Chemical(s) present at levels greater than or equal to 0.1% found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs: Ethylbenzene , Carbon Black
OSHA	: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity	: Calculated LC50 (fish): 13 mg/l. Calculated EC50 (waterflea): 7 mg/l. Contains 25 % of components with unknown hazards to the aquatic environment.
-------------	--

12.2. Persistence and degradability

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

Persistence – degradability : No specific information known.

12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

12.4. Mobility in soil

Mobility : Adsorbs to soil and has low mobility.

12.6. Other adverse effects

Other information : Not applicable.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product residues : Do not dispose empty pack with waste produced by households. Containers may be recycled. Treat product residues and non-empty pack as hazardous waste.

Additional warning : Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

Waste water discharge : Do not dispose of into the environment, drains, sewers or water courses.

EPA RCRA code : D0001

Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number or ID number

UN nr. : UN 1993

14.2. UN proper shipping name

Transport name : FLAMMABLE LIQUID, N.O.S. (Butanone ; Acetone)

Transport name (IMDG, IATA) : FLAMMABLE LIQUID, N.O.S. (Butanone ; Acetone)

14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

DOT (land)

Class : 3

Classification code : F1

Packaging group : II

Danger label : 3

ERG number : 128



Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

Other information : Not intended for carriage by tank-vessels on inland waterways. This product is exempted from labeling, specification packaging, shipping paper, and placarding requirements when shipped in inner packagings not over 1L, each package in strong outer packaging under 30 kg, unless shipped by aircraft or vessel.

IMDG (sea)

Class : 3
Packaging group : II
EmS (fire / spill) : F - E / S - E
Marine pollutant : No

IATA (air)

Class : 3
ERG code : 3H

14.6. Special precautions for user

Other information : Country specific variations may apply.

14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO) instruments. Packaged liquids are not considered bulk.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations : OSHA HazCom 2024, 29 CFR 1910.1200 and other Regulations.
: This product is exempted from classification as "May be fatal if swallowed and enters airways" on basis of subpart A.10, paragraph A.10.3.3.1 of Appendix A to §1910.1200.

United States TSCA (Toxic Substances Control Act) inventory

: All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

US State Regulation

California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer. WARNING: Contains traces of the following substances known to the state of California to cause cancer, birth defects or other reproductive harm

Chemical name	CAS	Type of toxicity	NSRL or MADL (ug/d)
Ethylbenzene	100-41-4	cancer	54 (inhalation) 41 (oral)
Carbon Black	1333-86-4	cancer	
Cumene	98-82-8	cancer	
Silicon dioxide	7631-86-9	cancer	
Benzene	71-43-2	cancer	6.4 (oral) 13 (inhalation)
		developmental	24 (oral) 49 (inhalation)
		male	24 (oral) 49 (inhalation)
Styrene	100-42-5	cancer	27

SECTION 16 OTHER INFORMATION

*

16.1. Other information

Product name : Kimball Midwest Liquid Electrical Tape - Black
Revision : 2025-12-02 Replaces issue dated

: 2025-10-10
Page 9/11
INFO CARE SDS

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

The information in this safety data sheet is compiled in compliance with Hazcom 1910.1200. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

List of abbreviations and acronyms that could be used (but not necessarily are used) in this safety data sheet:

ATE	: Acute Toxicity Estimate
CMR	: Carcinogenic, Mutagenic or toxic for Reproduction
DOT	: Department of Transportation
DSL	: Domestic Substances List
GHS	: Globally Harmonized System of Classification and Labelling of Chemicals
HPA	: Hazardous Products Act
HPR	: Hazardous Products Regulations
IATA	: International Air Transport Association
IBC code	: The IMO International Code for construction and equipment of ships carrying dangerous chemicals in bulk.
IMDG	: International Maritime Dangerous Goods Code
LD50/LC50	: Lethal Dose/Concentration for 50% of a population
MARPOL	: International Convention for the Prevention of Pollution From Ships
NO(A)EL	: No Observed (Adverse) Effect Level
OECD	: Organisation for Economic Co-operation and Development
OSHA	: United States Occupational Safety and Health Administration
PBT	: Persistent, Bioaccumulative and Toxic
REACH	: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	: Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	: Sewage Treatment Plant
TWA/STEL	: Time-Weighted Average/Short Term Exposure Limit
UN	: United Nations
VOC	: Volatile Organic Compounds
vPvB	: Very Persistent and Very Bioaccumulative
WHMIS	: Workplace Hazardous Materials Information System

Key data used to compile the Safety Data Sheet are from, but not limited to, one or more sources of information e.g. toxicological data from material suppliers, CONCAWE, IFRA, CESIO, Regulation EG 1272/2008, etc. Also used: OSHA HazCom 2024, 29 CFR 1910.1200.

Full text of H-phrases mentioned in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Advice on any training appropriate for workers: none.

Country / Language code	: US / EN
Number format	: ", " used as decimal separator.

Safety data sheet

According to OSHA HazCom
2024, 29 CFR 1910.1200

Date of preparation or latest revision : 2025-12-02

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

End of safety data sheet.