

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Food Grade Chain Lubricant
PRODUCT CODE: 807712
RECOMMENDED USE: Food Grade Semi-Synthetic Chain Lube
RESTRICTIONS ON USE: None known.
COMPANY NAME: Kimball Midwest
COMPANY ADDRESS: 4800 Roberts Road Columbus Ohio 43228
COMPANY PHONE: 800-233-1294
EMERGENCY PHONE: 800-424-9300

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Aerosols Category 2
Aspiration Hazard: Category 1
HAZARD STATEMENT(S): DANGER: Flammable aerosol. Pressurized container: may burst if heated. May be fatal if swallowed and enters airways.
This product contains the following percentage of chemicals of unknown toxicity: N/A
PRECAUTIONARY STATEMENTS: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn even after use. Protect from sunlight. Do not expose to temperature exceeding 50°C/ 122°F. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
White mineral oil	8042-47-5	30-60%
Propane/Butane	68476-86-8	10-30%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation develops: Get medical advice or attention.
INGESTION: Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Keep head below hips if vomiting occurs. Seek immediate medical attention. Aspiration hazard. Never give anything by mouth to an unconscious person.
INHALATION: Move to fresh air. If the person is breathing and has a pulse, do not start CPR. CPR is only for cardiac arrest (no pulse) or respiratory arrest (not breathing). For someone affected by aspiration, focus on airway management, oxygen, and keeping them comfortable while waiting for medical help. If the person is not breathing or has no pulse, CPR is appropriate, following standard guidelines. However, be aware that aspiration may have caused obstruction or chemical damage to the lungs. Rescue breaths should be performed carefully to avoid pushing more material into the lungs.
SKIN: Wash skin thoroughly with soap and water for 15 minutes. Remove contaminated clothes. Seek medical attention if irritation develops.
ACUTE HEALTH HAZARDS: May be fatal if swallowed and enters airways.
CHRONIC HEALTH HAZARDS: None known.
NOTE TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical condition. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

Safety Data Sheet
Link Wise

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, and water spray or fog.

UNSUITABLE EXTINGUISHING MEDIA: Water jets or streams which may spread flames.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Shut off all sources of ignition. Use water spray to disperse vapor and cool fire exposed containers. Prevent run off from entering streams, sewers, or drinking water supply.

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLAMMABLE. Contents under pressure. Exposure to temperatures above 120 °F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Cool containers with water spray. Rapid depolymerization can occur in a fire and produce flammable vapors. May depolymerize at temperatures above 392 °F (200 °C) with the production of extremely flammable butene monomers. Vapor may cause fire. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and nitrogen.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. Wear appropriate personal protective equipment. Clean up using rag or use some non-combustible material like vermiculite, sand or earth. Prevent spill from entering sewers, storm drains and natural waterways. Place waste in proper containers for disposal.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Avoid contact with skin, eyes and clothing. Wear proper personal protective equipment when using this product. Store in a cool, dry area. Do not use or store with strong oxidizers. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Do not pierce or burn, even after use. Wash hands thoroughly after handling.

OTHER PRECAUTIONS: Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong oxidizing agents.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
White mineral oil	5 mg/m ³ (oil mist)	5 mg/m ³ (oil mist)
Propane/Butane	Not Established	1000 ppm

ENGINEERING CONTROLS / VENTILATION: General ventilation should be used. Provide sufficient mechanical ventilation (general and/or local exhaust) to maintain exposure below the recommended exposure limits.

RESPIRATORY PROTECTION: Not required with normal use. If vapors are present or irritation is experienced, use NIOSH/MSHA approved respirator.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles.

ADDITIONAL MEASURES: No smoking or open flames. Wash hands thoroughly with soap and water after use.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, colorless spray.

ODOR: Bland.

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: Slow.

FLAMMABILITY(solid/gas): Flammable Aerosol

Safety Data Sheet

Link Wise

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D
UPPER FLAMMABILITY LIMIT: N/D
EXPLOSIVE LIMIT LOWER (%): N/D
EXPLOSIVE LIMIT UPPER (%): N/D
VAPOR PRESSURE (mm Hg): N/D
VAPOR DENSITY (AIR=1): N/D
RELATIVE DENSITY (H₂O=1): 0.875 - 0.890 @ 77 °F (25 °C).
SOLUBILITY(IES): Non-soluble in water.
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
AUTOIGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None known.
CHEMICAL STABILITY: Stable under normal storage conditions.
POSSIBLE HAZARDOUS REACTIONS: May depolymerize at temperatures above 392 °F (200 °C) with the production of extremely flammable butene monomers.
CONDITIONS TO AVOID: Temperatures greater than 122 °F and sources of ignition. Avoid incompatibles.
INCOMPATIBLE MATERIALS: Strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: Stable under normal storage conditions.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **White mineral oil** (8042-47-5): LD₅₀ (Oral, Rat) > 5000 mg/kg; LD₅₀ (Dermal) > 2000 mg/kg; LC₅₀ (Inhalation Dust/Mist, Rat, 4h) > 5 g/L. **Propane** (74-98-6): LC₅₀ (Inhalation, Rat, 4h) 658 mg/L. **Butane** (106-97-8): LC₅₀ (Inhalation, Rat, 4h) 30957 mg/m³.
ROUTES OF ENTRY: Eyes, Inhalation, Skin
EYES: May cause irritation, redness, tearing.
INGESTION: Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation, nausea, diarrhea, vomiting. Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia or edema.
INHALATION: May cause respiratory tract irritation, dizziness.
SKIN: May cause irritation, dryness.
MEDICAL CONDITION AGGRAVATED: None known.
ACUTE HEALTH HAZARDS: May be fatal if swallowed and enters airways.
CHRONIC HEALTH HAZARDS: None known.
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: **White mineral oil** (8042-47-5): LC₅₀ (*Oncorhynchus mykiss*, 96h) 5000 mg/L; EC₅₀ (*Daphnia magna*, 48h) 1000 mg/L.
PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.
BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.
MOBILITY IN SOIL: This product is not mobile in soil.
OTHER ADVERSE EFFECTS: None known.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.
RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN1950

Safety Data Sheet

Link Wise

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None.

SARA 311/312 HAZARD CATEGORIES: Physical & health hazards

SARA 313 REPORTABLE INGREDIENTS: This product does not contain any chemicals which are subject to the reporting requirements at Title 40 of the Code of Federal Regulations, Part 372.

CLEAN WATER ACT: None.

STATE REGULATIONS: California Proposition 65: This product does not contain chemicals regulated by California Proposition 65.

INTERNATIONAL REGULATIONS: No information available.

VOLATILE ORGANIC COMPOUNDS (VOC): 20%

NFPA HEALTH: 2

HMIS HEALTH: 2

NFPA FLAMMABILITY: 2

HMIS FLAMMABILITY: 2

NFPA REACTIVITY: 1

HMIS REACTIVITY: 1

NFPA OTHER: None

HMIS PROTECTION: A

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Regulatory

DATE PREPARED: 12/16/2016

REVISION DATE: 03/20/2026

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.